

Wall Mount Light Fixtures



Wall Ceiling Flood-Light Butterfly Adjustable

Energy-saving, wall-mounted ceiling luminaire with swivelling reflector. LI-1050



Wallwasher Luminaire for indoor or outdoor use. The light is emitted either upwards or downwards. With ballast and igniter for energy-saving lamps. Suitable for lamp: TC-D 26W G24d3 Please order bulbs separately. Housing matt silver, reflector swivels. Protection class IP65 splash water protected.

Dimensions:
W max. 399mm, H 120mm, D 160 mm.
Reflector 220mm high.
Weight: 2,5 kg



Wall Light Fixture Edge

Noble wall lamp in chrome for Linestra lamp. For bathroom, mirror, wardrobe, wall lighting.

Only 1 piece available for Linestra lamp 35W or 60W with one base, or LED or energy-saving line lamp. Please order bulb separately. Maximum length of the lamp 500mm Body width: 100mm Discontinued items only single pieces in stock. LI-1078

Accessories for indoor lights




Diffusor Glass For Edge LI-1079-B

Wall Mount Light Fixtures



LED Wall Light Bar RAJA 50cm

Decorative light strip with LED Discontinued article LI-1088




Lighting with warm white LEDs. Integrated LED driver Supply voltage 230V Power 3W Life time aprx. 50,000 h Aluminium, matt silver Plastic diffusor with satin finish. Dimensions: 514mm length, 54mm W, 38mm H Weight: 1,2 kg



LED Wall Light Bar RAJA 100cm

Decorative light strip with LED Discontinued article LI-1089




Lighting with warm white LEDs. Integrated LED driver Supply voltage 230V Power 6W Life time aprx. 50,000 h Aluminium, matt silver Plastic diffusor with satin finish. Dimensions: 10514mm length, 54mm W, 38mm H Weight: 2,5 kg

Display Lights



LED Exhibition Light with long arm and clamp



Bright trade fair display spotlight with wall arm. With LED, corresponding to approx. 50 - 100W halogen light.

LI-1160-SL

Incl. replaceable LED bulb

Available in the following versions:

LED output in 5W, 7W, 10W or 11W

Beam angle: spot (individual pictures or smaller objects) or flood (wide pictures)

Light colour: 3000K warm white or 4000K natural white

The spotlight does not get hot and is therefore suitable for illuminating heat-sensitive articles.

Lamp head: Metal silver.

S : Metal silver, length 50cm

Connection cable 2,5m and Schuko plug.

With stable screw clamp for mounting on vertical partition walls, clamping range 8 ... 46 mm.

Weight: 0,6 kg



Exhibition Floodlight 150W Long Arm and Bracket

Dainty halogen wide floodlight with long arm for clipping onto exhibition stands.

Only 1 left in stock, no longer available for reorder.

(Replacement lamps are still available)

Lamp head: metal white

S : Metal white, length 50cm

With screw clamp for mounting on vertical partition walls,

Clamping range 8 ... 46 mm.

Please order the halogen R7s 78mm 150W separately.

Delivery incl. mains cable and plug.

LI-1166W



Exhibition Spot 515 Halogen with arm and clamp



Clampable bracket-mounted display spotlight with amazingly bright light.

Delicate design incl. transformer and LV halogen lamp 50W.

LI-1167

Filigra display spot light with flexible arm 50cm and metal head lamp.

Includes 12V halogen dichroic lamp 50W 60°.

As bright as the normal 100W PAR38 reflector lamp.

With a strong screw for fixing to vertical walls.

Clamping range 8 ... 46 mm.

With 2,5 m connection cable and plug.

With a small transformer in the supply line,

Operating voltage 230 V

Color: silver-aluminum (at 10 pcs. also white colour on order)

Weight: 0,6 kg



Long Arm Light / Display Spot Pilas

Stainless steel cabinet luminaire with long arm for 12V halogen lamp MR16 up to 50W.

For trade fairs, salesrooms, exhibitions, shelving, libraries.

LI-1168

Long-arm spotlight surface-mounted luminaire, brushed stainless steel,

luminaire head can be swivelled and rotated

Suitable for lamp MR 16, 12V max. 50 Watt

Incl. connection cable 25cm with AMP-plug.

Please order bulbs and transformer separately.

Several luminaires can also be operated via one transformer. The load capacity of the transformer (W) must be at least as high as the total power of all connected lamps.

Length 43cm, mounting plate 48x 50mm.

Weight: 0,3 kg

	<p>LED On-Mount Display Light Pilas Set 3 pcs.</p>	<p>3 * Stainless steel long arm display fixture with halogen lamps and transformer. 3 surface-mounted lights, brushed stainless steel, Luminaire head swiveling and rotatable including bulb MR 16, 12V 3 Watt Electronic transformer 230V / 15W short circuit proof. With power cord and plug. With AMP connection cable 200cm to connect the lights to the transformer. Length of the lamps 43cm, mounting plate 48x 50mm. LI-1168-L</p>
---	---	--

	<p>LED Display Light 16W Long Arm</p>	<p>Elegant LED clamp spotlight that does not emit heat. With long arm for exhibition, salesroom and trade fair stand. Comparable with 150W halogen light. LI-1172</p>
		<p>Bright LED display spotlight for uniform illumination of posters, showcases, shelves and exhibits. For easy clamping on vertical exhibition walls or on tabletops. The spotlight is pivotable. Bulb Type: SMD LED LED lamp 16 watts included. The brightness corresponds to 100 watts of halogen light. Light distribution 80° very wide Available in the light colors: 4000K natural white or 3000K warm white Luminous flux: 1560 Lm / 4000K or 1060Lm / 3000K LED lamps have a very long life and are insensitive to shocks. There is no heat and no UV radiation emitted. Therefore also suitable for food, textiles, pictures and other sensitive goods. Incl. LED power supply for 230V With power cable 2m and Euro plug. Lamp head: plastic silver gray Bar: aluminum Clamping range 5 - 55mm Only suitable for indoor use Dimensions: length 40 cm, spotlight head: 164mm x 101mm Weight: 0,69 kg</p>

Wieland and AMP Connectors

	<p>AMP Distributor Connector</p>	<p>With 3 / 6 AMP connection sockets. LI-1179</p>
---	---	--

Display Lights

	<p>Long Arm Light / Display Spot Hibit</p>	<p>Surface mounted cabinet luminaire with long arm made of metal for halogen lamp GU10 up to 75W. LI-1180</p>
		<p>Cabinet luminaire, aluminium and brass, Suitable for lamps GU10, 230V, 75 watts max. Incl. 60cm cable. Operating voltage 230V GU10 lamp to be ordered extra. Length 43cm, 48 x 50mm mounting plate. Colour: silvergrey Weight: 0,3 kg</p>

	<p>Display Clamp Light Metal E27</p>	<p>Metal clamp lamp with mains cable and plug for E27 reflector lamp. For trade fair, market stall, exhibition. LI-1190</p> <p>White metal enclosure with pivoting lamp head. Bracket made of white plastic. Rotate and swivel, for clamping to vertical or horizontal walls. Please order separately: reflector bulb R80 E27 Max. 60 watts. Incl. Power cord and plug. Weight: 0,4 kg</p>
		
	<p>LED clamp spotlight metal for sales stand 6W(50W)</p>	<p>Metal clamp lamp with LED reflector lamp, mains cable and plug. For trade fairs, sales stands, exhibitions. Comparable with 50W halogen light. LI-1194</p> <p>White metal enclosure with pivoting lamp head. Included: LED reflector lamp E27 R63, 6 watt. Bracket made of white plastic. Rotate and swivel, for clamping to vertical or horizontal walls. Incl. Power cord and plug. Weight: 0,4 kg</p>
		
	<p>Energy-saving clamp-on spotlight for market stall 15W(75W)</p>	<p>Metal clamp lamp with energy-saving reflector lamp, mains cable and plug. The spotlight does not get hot. For trade fairs, sales stands, exhibitions. Comparable with 75W halogen light. LI-1196</p> <p>White metal housing with swivelling lamp head. Included in delivery: Reflector lamp energy saving E27 R95, 15 Watt. Large clamp made of white plastic. Rotatable and swivelling, for clamping to vertical or horizontal walls. With mains cable and plug. Weight: 0,4 kg</p>
		

Recessed Light Fixtures Rectangular

	<p>Recessed Downlight Module Kardan CDM-T70</p>	<p>Recessed downlight gimbal-mounted for CDM-T 70W lamp G12. LI-2005MH</p> <p>Pivoting spotlight for ceramic metal halide discharge lamp G12 / 70 watts. Built-in aluminum reflector. The light output is about 300W halogen light. Frame 150 x 150mm, silver Mounting cutout Ø 145mm, depth 200mm Ballast and lamp sold separately. Weight: 0,7 kg</p>
		
	<p>Recessed Light Fixture Kardan MR16, rectangular</p>	<p>Low-voltage recessed downlight gimbal-mounted 50W. LI-2010</p> <p>Square recessed light for halogen reflector bulb MR16 GU 5.3 Max. 50 watts. Operating voltage 12V. Please order separately: 12V bulb and transformer. The light may be dimmed. Dimensions: 135 x 135mm, Mounting hole: 110 x 110mm, depth 115mm. Color: titanium gray Weight: 0,95 kg</p>

Recessed Fixtures Round	
	<p>Recessed Fluorescent Downlight Deco Electronic</p> <p>Recessed ceiling luminaire with electronic ballast for fluorescent lamp G24q 18W. Sheet steel housing, steel retaining ring, white powder-coated. For fluorescent lamps G24q 18W. Please order lamp separately. With external, energy-saving, electronic ballast. Protection class: IP20 Dimensions: External Ø 230mm, recessed Ø 215mm, depth 100mm.</p> <p>OUTLET MODEL LI-2056</p>
<p>Recessed Fluorescent Downlight IP44 2 x 26W TC-D</p>	<p>Recessed ceiling luminaire 230mm with CCG ballast for compact fluorescent lamp. Also for damp rooms. Due to the new EU energy directive, this luminaire may only be used as a replacement in existing installations, but no longer for new installations. LI-2061K</p>
 	<p>Recessed Fluorescent Downlight 2x 18W 26W IP44</p> <p>Fluo recessed ceiling luminaire for compact fluorescent lamp. Damp rooms, swimming pool or outdoors. LI-2061L</p> <p>For outdoor areas, swimming pools, changing rooms ... Sheet steel housing with matt glass diffuser. Cover ring of white polycarbonate. For 2 compact fluorescent lamps. 18W TC-DE/ G24q-2 (4-pin) 26W TC-DE/ G24q-3 (4-pin) The lamps must be ordered separately. Voltage: 220 - 240V 50Hz Dimensions: External Ø 238mm, recessed Ø 220mm, depth 110mm. Protection class: IP44 The electronic ballast is included in the delivery. Weight: 1,6 kg</p>
	<p>Recessed Fluorescent Downlight 2x 18W Decorative</p> <p>Recessed ceiling luminaire 254mm with VVG ballast for compact fluorescent lamp. Due to the new EU energy directive, this luminaire may only be used as a replacement in existing installations, but no longer for new installations. LI-2064</p> <p>With decorative cover glass, outside matt, inside textured. Sheet steel housing white. incl. 2x lamp PL-C / G24d2 18 Watt Voltage: 220 - 240V 50Hz The magnetic ballast with cable and plug connector is included in delivery.</p> <p>Dimensions: Outside Ø 254mm Installation Ø 235mm D 200mm Weight: 3 kg</p>
	<p>Recessed Fluorescent Downlight 2x 18W 26W Decorative</p> <p>Recessed ceiling luminaire 230mm with electronic ballast for compact fluorescent lamp PL-C / G24q2. With decorative matt anti-glare ring. An additional decorative glass pane with frosted edge is mounted a few centimetres away. Suitable for 2x lamp PL-C / G24q2 18 or 26 Watt. The lamps must be ordered separately. Voltage: 220 - 240V 50Hz The electronic, flicker-free ballast is included in delivery. Protection class: IP20 Dimensions: Outside Ø 230mm, recessed Ø 215mm, depth 100mm. LI-2065E</p>
<p>Recessed Fluorescent Downlight 2x 26W asym.</p>	<p>Wallwasher for PLC for uniform wall lighting or for wide-area floor lighting at the side. LI-2075-K</p>

Recessed Light Fixtures Rectangular



Recessed downlight Angular Micro TC-D ECG



Square recessed ceiling luminaire with PAR-S anti-glare louvre 2x 18W LI-2080

Discontinued item, remaining stock

Wide-beam luminaire made of rectangular steel profile, white. Highly effective PAR-S anti-glare louvre of pure aluminium. Beam angle 60

Operating voltage 220V - 240V 50 /60Hz

The integrated electronic ballast ensures flicker-free light and extended lamp life.

The ballast switches off automatically in case of overload or lamp failure.

The matching fluorescent lamps must be ordered separately.

Protection class IP20

Dimensions:

W 234mm x 234mm,

depth 90mm

Installation cut-out 200mm x 200mm.

Weight: 1,7 kg

Surface mounted lights & spotlights



Surface mounted LED Downlight IP65



Round LED surface-mounted ceiling luminaire 12W for indoor and outdoor use, e.g. canopy, passage, entrance hall LI-2103

Flickerfree, electronic gear.

Power 12W

Casing: Steel sheet, black or white.

Protection grade IP65

Dimensions:

Ø 120mm

height 115mm

Weight: 2,2 kg

Recessed Light Fixtures Rectangular



Recessed LED Downlight rectangular 30W

Angular recessed ceiling spotlight downlight with bright COB LED, white, For salesroom, shop, museum. Comparable with 300W halogen. LI-2130

No UV radiation, no heat radiation.

Less insect attraction.

Ideal for lighting sensitive goods, food, clothing, pictures.

Swivel range 45 deg

Incl. Samsung SMD LED

Radiation: 90° wide

Light colour: 4000K natural white (on special order also 3000K ww or 6000K daylight)

Luminous flux: 2450 Lm

Colour rendering quality Ra: > 80

Service life: approx. 50000 h

Bulb and ballast (driver) are included in the price.

The luminaire is not dimmable

Power consumption: 28W

Power factor: 0,94

Voltage: 220 - 230V

Protection class: IP20

Metal housing white

Dimensions: Length 235mm, width 145mm, depth 120mm

Installation cut-out: 220mm x 128mm

Minimum order quantity: 2 pcs.

Weight: 1 kg

	<p>Recessed LED Downlight rectangular 40W</p>	<p>Angular recessed ceiling downlight with bright COB LED, white, for salesroom, shop, museum. Comparable with 400W halogen. Minimum order quantity: 8 pcs. LI-2131</p> <p>No UV radiation, no heat radiation. Less insect attraction. Ideal for lighting sensitive goods, food, clothing, pictures.</p> <p>Swivel range 45 Radiation: approx. 90° wide Light colour: 4000K natural white (on special order also 3000K ww or 6000K daylight) Luminous flux: 3750 Lm Colour rendering quality Ra: > 80 Service life: approx. 50000 h Bulb and ballast (driver) are included in the price. The luminaire is not dimmable Voltage: 220 - 230V Protection class: IP20 Metal housing white. Length 235mm, width 145mm, depth 120mm Recessed cut-out: 210mm x 128mm Minimum order quantity: 8 pcs. Weight: 1,3 kg</p>
---	--	--



Recessed Fixtures Round		
	<p>Bright recessed downlight swivelling Orto for HQI-T</p>	<p>Adjustable spotlight for recessed ceiling mounting for gallery or salesroom. For metal halide lamp HQI 35W, 70W or 150W energy-saving. LI-2240</p> <p>Width of light beam 88 Rotates 355°, swivels 60°. Suitable for HQI-T 35W, 70W or 150W lamps. Please order lamp and ballast separately from the accessories. Body made of die-cast aluminium. Diameter Ø 183mm, installation depth 170mm, installation opening Ø 170mm. Available in white Cover glass Protection class: IP20 Weight: 2 kg</p>
	<p>Recessed Downlight Bend MH-70W, Adjustable</p>	<p>MH spotlight for false ceiling 70 watt, adjustable Beam spread: 30° narrow Rotated 355°, 60° swivel Suitable for lamp HQI-TS 70W. Please order extra ballast and lamp. Ø 240mm, depth 249mm, 230mm mounting hole Body made of die-cast aluminum Available in white or silver gray LI-2241</p>



	<p>Recessed LED Downlight Adjustable Round 35W</p>	<p>Round, adjustable recessed spotlight for ceiling installation. For shop, office, boutique, museum ... LI-2250</p> <p>No UV radiation, no heat radiation. Ideal for illuminating sensitive goods, food, clothing, paintings. By the round reflector, the light is bundled and the beam focused on the desired area. The light is more intense, and sets the tone. No lenses are used, therefore there are no color distortions at the edges. Rotates 355°, swivel 60°. Beam spread: 25° medium closely (on order 45° or 60°) Available in the light colors: 4000K pure white (on order 3000K ww or 6000K daylight). Luminous flux: 3450 Lm Color rendering: CRI > 80 Life time: about 50000 hours Including driver. The lamp is not dimmable Power: 35W Voltage: 200 - 240V Protection: IP20 Housing aluminum, white. Diffuser: Clear PC Diameter: Ø 180mm Cut-out hole: Ø 170mm, depth 128mm Weight: 1 kg</p>
	<p>Recessed LED Panel Downlight 17cm round silver</p>	<p>Bright LED recessed luminaire with 175 mm diameter and 15W power. LI-2309</p> <p>Space-saving and attractive LED panel for living areas, offices, hallways, stairwells ... High efficiency and long service life. LED panel with white SMD LEDs Power max. 15W Light colour: warm white 3000K or cool white 6000K Light intensity: 1350 lumen Beam angle very wide 120 Instant start, no flickering 100 - 240V, 50-60 Hz Protection class 2, IP20 Material: aluminium, plastic suitable for recessed ceiling mounting incl. LED ballast also dimmable at extra charge Permanently installed LEDs (not replaceable) Operating temperature -25°C ... +45°C Installation Ø 153 mm Installation depth 10 mm External Ø 167 mm Weight: kg</p>
	<p>Recessed LED Panel Downlight 17cm round white</p>	<p>Bright LED recessed luminaire with 17cm diameter and 15W power. LI-2309W</p> <p>Space-saving and attractive LED panel for living areas, offices, hallways, stairwells ... High efficiency and long service life. LED panel with white SMD LEDs Power max. 15W Light colour: warm white 3000K or cool white 6000K Light intensity: 1350 lumen Beam angle very wide 120 Instant start, no flickering 100 - 240V, 50-60 Hz Protection class 2, IP20 Material: aluminium, plastic suitable for recessed ceiling mounting incl. LED ballast also dimmable at extra charge Permanently installed LEDs (not replaceable) Operating temperature -25°C ... +45°C Installation Ø 153 mm Installation depth 10 mm External Ø 167 mm Weight: kg</p>



**Recessed LED Panel Downlight
18W Round**



Bright LED recessed luminaire with 22cm diameter.
LI-2321

Space-saving and attractive LED panel for living areas, offices, hallways, stairwells ...
High efficiency and long service life.
LED panel with white SMD LEDs
Power max. 18W
Light colour: warm white 3000K or cool white 6000K
Light intensity: 1260 lumen
Beam angle very wide 120
Instant start, no flickering
100 - 240V, 50-60 Hz
Protection class 2, IP20
Material: aluminium, plastic
suitable for recessed ceiling mounting
incl. LED ballast
also dimmable at extra charge
Permanently installed LEDs (not replaceable)
Operating temperature -25°C ... +45°C
Installation Ø 205 mm
Installation depth 20 mm
External Ø 223 mm
Weight: kg

Recessed Light Fixtures Rectangular



**LED downlight recessed
spotlight angular 6W swivelling
aluminium**



Square LED recessed ceiling luminaire 6W made of aluminium. For recessed mounting.
LI-2356

Solid recessed spotlight for installation in walls or ceilings with a material thickness of max. 30 mm
swivels through 30 degrees
Light colour: warm white 3000K
Luminous flux: 540 lumen
not dimmable
Material: Brushed die-cast aluminium
Power: 6 Watt
LED recessed spotlight and transformer included in delivery.
Voltage: 230V - with transformer
Illuminant: 3 x 2W LED
Illuminant included in delivery.
Service life: approx. 50000 hrs.
Outer diameter: 92 x 92 mm
Installation depth: 55 mm
Installation cut-out: 75 x 75 mm
Weight: 0,3 kg

Recessed Fixtures Round



**Power LED Recessed Light 6W
COB adjustable**



Round recessed spotlight / downlight with COB LED for soft light emission, shallow recess depth.
LI-2357

Swivelling, bright spotlight with low energy consumption.
Very low heat emission.
Power LED bulb from Epistar included.
Light intensity comparable with 50 Watt halogen light.
Light colour 3000K warm white (4000K neutral white can also be ordered for orders of 10 or more).
Light distribution: 100°.
Operating current: 350mA
Please order LED power supply or dimmable driver 350mA separately.
Power consumption: 6 Watt
For brightness control we recommend a dimmable driver VS-LED354 and a phase cut-off dimmer
or up to 2 luminaires can be operated via a dimmable VS-LED707 driver with momentary-action switch.
Housing made of solid metal
Colour white
Dimensions: Diameter 90mm, depth 60mm, mounting hole Ø 80mm
Weight: 0,24 kg



**Round LED Recessed Light 18W
COB adjustable**



Recessed ceiling spotlight / downlight with COB LED with 38° light distribution for shops and galleries.
LI-2358

Swivel, bright spotlight with low energy consumption.
Low heat emission.
Very long life time
Including Power COB LED Lamp.
Light intensity comparable to 120W halogen light.

Light color:	4000K nature white (at 5pcs. also in 3000K warm white on order)
Beam shape:	38°
Luminous flux:	1500 lm
Operating voltage:	230V
Power:	18 Watt

LED power supply driver is included.
Case made of solid metal
color white
Diameter: 135mm
Dimensions: cut-out Ø 110mm
Weight: 0,4 kg



**Round Downlight LED Recessed
6W IP44**



Recessed ceiling luminaire 6W made of aluminium. Splash-proof, for bathrooms, damp rooms or outdoors.
Remaining stock.
LI-2361

Downlight for installation in walls or ceilings with a max. material thickness of 30 mm.

Light colour: Warm white 3000K
Material: aluminium
Colour: anodised aluminium
Power: 6 Watt
Protection class: IP 44
Illuminant: 6 Power LED's 1 Watt
Illuminant included in delivery.
An LED driver with 350 mA is required for operation.
Diameter Ø: 88 mm
Installation depth: 44 mm
Cut-out Ø: 76 mm
Weight: 0,3 kg

	<p>Recessed Halogen Fixture Waterproof IP65</p>	<p>Recessed luminaire for bathrooms, terraces and outdoors. Moisture-protected. LI-2450 Remaining stock: 4 pieces</p> <p>Protective glass satin finish. Aluminium cover in white. For halogen cold light lamps MR16 up to 35W. (Please order lamp separately). A 12V transformer is required for operation.</p> <p>Dimensions: Outside Ø 80mm, recessed Ø 70mm, depth 85mm. Weight: 0,21 kg</p>
	<p>Cool Beam Spot Recessed Massive</p>	<p>High-quality halogen spotlight / recessed halogen spotlight made of cast aluminium. LI-2460 Stock: 7 pcs. white, 10 pcs. matt chrome</p> <p>Suitable for cold mirror lamp 50mm 12V, 20W - 50W. Please order suitable lamps in various wattages and beam angles separately. A 12V transformer is required for operation. Outside Ø 83mm, recessed Ø 68mm, depth 26mm. Weight: 0,1 kg</p>
	<p>Round halogen recessed spotlight 12V cold light, white</p>	<p>Halogen spotlight for low-voltage dichroic mirror lamps MR16 50mm. White Metal cover. For multi-mirror lamp GU5.3 / GX5.3 12V. Please order transformer and MR16 bulb max. 50W separately. The luminaire is held by 2 spring clips.</p> <p>Dimensions: Outside Ø 81mm, recessed Ø 65 - 68mm LI-2466-W</p>
	<p>Recessed Cool Beam Spot, Eyeball adjustable</p>	<p>Round halogen spotlight white for 50mm low voltage multi-mirror lamps MR16. Remaining stock: 3 pieces LI-2470-G Swivelling 40 Rotatable 360</p> <p>Please order 12V transformer and reflector lamp MR16 max. 50W separately.</p> <p>Housing: Metal Colour: white Dimensions: Ø 110mm, shallow depth 50mm, Installation Ø 92mm. Weight: 0,1 kg</p>
<p>Recessed Cool Beam Spot, adjustable, black</p>	<p>Recessed luminaire for cold-light mirror lamp MR16 Cool-Beam 50mm up to 50W. LI-2476-S</p>	
<p>Recessed Cool Beam Spot, adjustable, white</p>	<p>Halogen spot for dichroic mirror lamp MR16 Cool-Beam 50mm. LI-2476-W</p>	
	<p>Recessed Cool Beam Spot MR16 Mäander adjustable</p>	<p>Decorative recessed luminaire of cast metal for dichroic mirror lamp 50W 12V 50mm. LI-2477 Solid metal housing, gold, with matte silver cut-outs. Required halogen bulb MR 16, 51mm max 50 watts. Operating Voltage 12V - a halogen transformer is required IP20 / 850 ° C Outside diameter 92mm, mounting Ø 80 mm, depth 60 mm Weight: 0,15 kg</p>

 	<p>Halogen Furniture Recessed Light, 20W, brass</p>	<p>Recessed luminaire for 12V G4 halogen lamps up to 20W - without protective glass. LI-2480-G Remaining stock: 2 pieces</p> <p>With protective glass Metal cover Light range up to approx. 2.5m. Connecting cable length 10cm with open ends. A 12V halogen transformer is required for operation. Please order a suitable halogen lamp 12V G4 max. 20W separately. Several lamps can be operated with one transformer. Please note that the transformer power must be at least as strong as the total power of all luminaires.</p> <p>Dimensions: Outside Ø 77mm, recessed Ø 62mm, small depth 20mm. Weight: 0,05 kg</p>
	<p>Halogen Recessed Furniture Light, 20W with glass</p>	<p>Flat recessed spotlight for 12V G4 halogen lamp up to 20 Watt - white or brass. LI-2482 Remaining stock: 3 pieces</p> <p>The glass is frosted so that the light is widely diffused. A 12V halogen transformer is required for operation, as well as a 12V G4 bulb max. 20W. Several luminaires can also be operated via one transformer. Please note that the transformer power must be at least as strong as the total power of all luminaires.</p> <p>Dimensions: External Ø 70mm, recessed Ø 60mm, shallow depth 16mm. Weight: 0,05 kg</p>

Waterproof Lighting Fixtures

 	<p>Bulkhead Ceiling Light Fixture 60W</p>	<p>Small oval surface-mounted luminaire with wire basket for cellars, warehouses, corridors, technical rooms. LI-250-306</p> <p>For incandescent lamp or energy-saving lamp E27 Max. Power 60 W Housing made of grey plastic On special order also available in white, black, brown, red or blue. Cover of clear glass, prismatic With wire guard Lamps can be changed without tools Impact resistance IK06 Length 185mm, width 125mm, height 110mm Weight: 0,52 kg</p>																				
 	<p>LED damp proof oval luminaire marine fitting IP44</p>	<p>Small oval surface-mounted luminaire with wire basket for cellars, warehouses, corridors, technical rooms. Lamps can be changed without tools. LI-250-307</p> <p>Including LED lamp</p> <table border="0"> <tr> <td>Power:</td> <td>4.0W comparable to 50W incandescent light</td> </tr> <tr> <td>Luminous flux:</td> <td>360 Lm</td> </tr> <tr> <td>Light color:</td> <td>4000K nature white.</td> </tr> <tr> <td>Voltage:</td> <td>230V</td> </tr> <tr> <td>Diffusor:</td> <td>Clear glass, prismatic.</td> </tr> <tr> <td>With steel guard basket.</td> <td></td> </tr> <tr> <td>Housing:</td> <td>Plastic</td> </tr> <tr> <td>Protection class:</td> <td>IP44</td> </tr> <tr> <td>Protection class</td> <td>II, fully insulated.</td> </tr> <tr> <td>Dimensions:</td> <td>Length 165mm, width 115mm, height 70mm</td> </tr> </table> <p>Lamp replacement can be done without tools For feed thru wiring Weight: 0,52 kg</p>	Power:	4.0W comparable to 50W incandescent light	Luminous flux:	360 Lm	Light color:	4000K nature white.	Voltage:	230V	Diffusor:	Clear glass, prismatic.	With steel guard basket.		Housing:	Plastic	Protection class:	IP44	Protection class	II, fully insulated.	Dimensions:	Length 165mm, width 115mm, height 70mm
Power:	4.0W comparable to 50W incandescent light																					
Luminous flux:	360 Lm																					
Light color:	4000K nature white.																					
Voltage:	230V																					
Diffusor:	Clear glass, prismatic.																					
With steel guard basket.																						
Housing:	Plastic																					
Protection class:	IP44																					
Protection class	II, fully insulated.																					
Dimensions:	Length 165mm, width 115mm, height 70mm																					

	<h3>Bulkhead Ceiling LED Light Fixture IP44</h3>	<p>Small LED surface-mounted luminaire 4W marine fitting for cellars, passageways, stairwells, industry, car parks or outdoors. Energy-saving and very stable. LI-250-310</p> <p>LED bulb included.</p> <p>Power: 4W comparable with 50W incandescent light. Luminous flux: 360 Lm Light colour: 4000K (natural white) Voltage: 230V Cover: clear glass, prismatic Housing PP plastic white Impact resistance IK10 Protection class: IP44 Protection class II, fully insulated Dimensions: Length 185mm, width 125mm, height 110mm</p> <p>Suitable for through-wiring Weight: 0,12 kg</p>
	<h3>Outdoor wall lighting fixture Drop Matte IP55</h3>	<p>Outdoor luminaire / damp-proof luminaire made of plastic vandal-proof, max. 75W. LI-250-322D</p> <p>Housing plastic white (on special order also black or silver-grey). Cover made of impact-resistant polycarbonate opal. For bulb E27, max. 42 Watt (please order separately) Protection class IP 55 Very high impact resistance IK10 Dimensions: Ø 300mm, H 108mm Weight: 1,12 kg</p>
	<h3>Waterproof LED Wall Luminaire Square IP54</h3>	<p>Rectangular wall-mount fixture for bathroom, indoor or outdoor. LI-250-324E</p> <p>Casing polycarbonat white Diffuser cover, shockproof polycarbonate opal Power: 18 Watt Light color: 4000K Not dimmable Voltage 220V - 240V 50Hz Protection degree IP 54 Hi impact resistance IK08 Width 280mm, height 280mm, depth 60mm Weight: 0,36 kg</p>
	<h3>Triproof LED On Mount Light Round 10W with Sensor IP54</h3>	<p>Round LED outdoor luminaire 21cm / damp-proof luminaire with motion detector IP54. LED 10W. Wall or ceiling mounted. LI-250-340</p> <p>Housing glass fibre reinforced plastic Colour: white Cover: opal matt cover With high-intensity LED not replaceable. Beam angle 120 Light colour: 4000K natural white Luminous flux 800 Lm The brightness is comparable with a 75W incandescent lamp With PIR sensor Angle of detection 90 Range 8 m Time and brightness are fixed Lighting time: Adjustable Voltage: 220V - 240V Frequency: 50-60Hz Protection class: IP 54 Dimensions: Ø 215mm, H 80mm Weight: 1,02 kg</p>

	<p>Triproof LED On Mount Light Round 12W with Sensor IP54</p>	<p>Round LED outdoor luminaire 21cm / damp-proof luminaire with motion detector IP54. LED 12W. Wall or ceiling mounted. LI-250-341</p> <p>Housing: plastic Colour: white Cover: Opal matt cover With high-intensity LED, not replaceable. Beam angle 120 Light colour: 3000K warm white Luminous flux 800 Lm The brightness is comparable with a 75W incandescent lamp With PIR sensor Angle of detection 90 Range 8 m Time and brightness are fixed Lighting time: Adjustable Voltage: 220V - 240V Frequency: 50-60Hz Protection class: IP 54 Dimensions: Ø 215mm, H 80mm Weight: 1,02 kg</p>
	<p>Wall Lighting Fixture Omega Dome Down IP54</p>	<p>Outdoor luminaire / moisture-proof luminaire aluminium and glass with partial dimming, max. 100W. LI-250-402</p> <p>Luminaire for damp rooms, swimming pools, toilets, public areas or outdoors. Housing of white cast aluminium (special order also black). Cover of opal matt glass Protection class IP 54 For bulb E27, max. 100 Watt (please order separately) Dimensions: Ø 260mm, H 120mm Weight: 1,38 kg</p>

Lighting for container and accomodations

	<p>LED Wall lighting fixture Dome IP65</p>	<p>Weatherproof lamp aluminium / glass, max. 100w. 1650 lm LI-250-442</p> <p>For indoor use in wet rooms, bath, public areas or stair case. Including LED lamp Light color: 4500K nature white Power: 16W Luminous flux: 1300 Lm Ambient temperature: -25 ~50°C Voltage: 220- 240V Housing: Resistant plastic, white (on special oder also black or grey) Diffusor: opal matte plastic Hit proof: IK10 Heat proof: 850°C (hot wire test) Protection degree: IP 65 Dimensions: Ø 425mm, H 140mm Weight: 1,26 kg</p>
---	---	--

Wall Mount Light Fixtures

	<p>Ceiling Dome Light IP44 Cama 60W E27</p>	<p>Surface-mounted luminaire vandalism-proof for indoors and outdoors. For incandescent lamp 75 Watt, LED or energy-saving lamp E27. LI-2501W</p> <p>Humidity-proof IP 44 Available in white (also on order silver or black). E27 max. 75W, or LED or energy-saving bulbs max. 11W. Pls. order the bulb extra. Vandalism proof IK10 Dimensions: Ø 290mm, depth 95mm. Weight: 1,2 kg</p>
---	--	---

	<p>Ceiling Dome Light LED IP44 Cama 9W</p>	<p>Surface-mounted luminaire vandal-proof for indoors and outdoors. With LED 9W - comparable to 75 Watt incandescent light. LI-2502-1W</p> <p>Humidity-proof IP 44 Available in white (also on order silver or black). Including LED Power 11W Light color: 4000K nature white Vandalism proof IK10 Dimensions: Ø 290mm, depth 95mm. Weight: 1,2 kg</p>
		

Waterproof Lighting Fixtures

	<p>Surface-Mount Light IP44 Luna Dome 100W</p>	<p>Splash-proof damp-proof luminaire for indoor and outdoor use. Vandal-proof. E27 Max 100 Watt. LI-2503E</p> <p>Fixture for indoor use in wet rooms, bath, public areas or outdoor. For incandescent lamp max. 100 watt or energy saver lamp E27. The lamp must be ordered extra. Diffusor prismatic glass Base polycarbonate. Available in white (also black on order). Humidity-proof IP 44 Vandalism proof IK08 Dimensions: Ø 240mm, depth 85mm MOQ: 2 pcs. Weight: 0,9 kg</p>
		

Wall Mount Light Fixtures

	<p>LED Wall and ceiling light 30cm with motion detector</p>	<p>Round LED surface-mounted luminaire 30cm with HF sensor. LI-2508</p> <p>Elegant ceiling light with high quality microwave motion and shapely UV resistant casing with elegant matte cover and white outer ring. 100 SMD LEDs Luminous flux: 1200 Lm Color temperature 4200K (pleasant white) Consumption in operation 16W, 0.9W in standby additional switching output max. 300W Power 16W Operating at 230V / 50Hz Installation height 2-4m Coverage and illumination time adjustable Detection range: 360 °, radius 1-8m Lighting period: 10sec - 12min Light sensitivity adjustable: 3-2000 LUX for indoor and outdoor use IP44 Outer diameter: 300mm Height: 115mm Weight: kg</p>
---	--	--

	<p>LED Wall and ceiling light 35cm with motion detector</p>	<p>Round decorative LED surface-mounted luminaire 35cm with HF sensor. LI-2509</p> <p>Elegant ceiling light with high quality microwave motion and shapely UV resistant casing with elegant matte cover and white outer ring. 100 SMD LEDs Luminous flux: 1200 Lm Color temperature 3000K (warm white) Consumption in operation 15W, 0.9W in standby additional switching output max. 300W Power 15W Operating at 230V / 50Hz Installation height 2-4m Coverage and illumination time adjustable Detection range: 360 °, radius 1-8m Lighting period: 10sec - 12min Light sensitivity adjustable: 3-2000 LUX for indoor and outdoor use IP20 Outer diameter: 350mm Height: 100mm Weight: kg</p>
	<p>Surface-Mount Light Proxim Fluoro 2* 18W IP65</p>	<p>Wall-ceiling luminaire with high degree of protection for 2 compact fluorescent lamps 18W. LI-2513</p> <p>Waterproof IP 65 Polycarbonate white (on special order silver grey). Shockproof IK10 With electronic ballast For 2x compact fluorescent lamp 18W G11 (please order separately). Dimensions: Ø 387mm, depth 96 mm Weight: 1,4 kg</p>
	<p>Wall Light Fixture Alpha</p>	<p>Direct and indirect beam halogen luminaire 100W. Roman-Greek wall bowl in white. LI-2517</p> <p>Minimum order quantity 2 pcs.</p> <p>The main part of the light is emitted indirectly upwards. The real glass insert emits a soft light downwards. For lamp R7s 78mm, max. 100 Watt. Please order bulbs separately. Dimmable via optional dimmer. Dimensions: W 270 mm, H 65 mm, D 145 mm Minimum order quantity 2 pcs. Weight: 0,6 kg</p>
	<p>Fluorescent Wall Light Fixture Zenith</p>	<p>Direct-indirect distribution, energy-saving surface-mounted luminaire made of glass and aluminium. LI-2520</p> <p>Soft light distribution, forward and backwards by the satinized glass reflector. Built-in low-losses ballast. For lamp G24d-2 18W - please order extra. As bright as a 100W halogen lamp. The fixture is not dimmable. Dimensions: w 295mm, h 250 mm, d 140mm Weight: 1,8 kg</p>
	<p>Wall Lighting Fixture Window K</p>	<p>Conveys the feeling of a window. With ECG energy-saving, direct and indirect lighting. LI-2526</p> <p>Available for 2x 18W or 2x 26W compact fluorescent lamp. With a flicker-free, electronic ballast. Decorative aluminum frame Diffusor: frosted acrylic Dimensions 235mm x 235mm, depth 76mm Weight: 1,3 kg</p>



Duet Tube LED Wall Bracket Light Fixture



Delicate LED luminaire 2 x 3 Watt made of satinised acrylic glass with metal surround.

Discontinued model - can no longer be reordered.
LI-2528

Application area: bathroom mirror, wardrobe, wall lamp, hallway, walk-in wardrobe, living room.

Metal lamp with acrylic glass insert.

Intensive upward and downward light.

Diffuse light to the side.

Lamp life 50000 hours.

The luminous intensity of the LEDs corresponds to about 60 watts of incandescent light.

Light colour: natural white 4000K

Supply voltage 230V

Power consumption 8 Watt

Protection class: IP40

Height 156mm, diameter 50mm

Weight: 0,9 kg

Recessed Wall Fixtures



Recessed Wall Light Flat Curve



Halogen or LED recessed wall luminaire with shallow recess depth. For decorative lighting.
LI-2530H

With this recessed wall spotlight, you can set decorative accents in your home,

or to mark stumbling hazards or steps.

Use only in dry rooms.

Suitable for halogen lamp 12V G4 max. 20W or for LED.

(Please order bulb and transformer separately).

Material: anodised aluminium.

Dimensions: W 90 mm, H 90 mm, D 31 mm, hole cut-out: 75 x75 mm.

With clamping springs for direct snap-in into sheetrock walls.

Optionally available:

Flush-mounted frame, recessed box, LED insert.

Weight: 0,15 kg

Accessories for indoor lights



Recessed Frame for false wall
LI-2531-E

Recessed Wall Fixtures



Recessed Wall Light Fixture Downunder II

Stylish recessed aluminium wall luminaire for compact fluorescent lamp TC-D
LI-2535

Energy-saving recessed luminaire for a harmonious atmosphere in rooms.

The frame of the luminaire is made of natural aluminium.

A clear plastic cover glass prevents dusting.

Visible dimension: W 221mm, H 305 mm

Wall cut-out: W 210mm, H 285mm, D 90mm

Suitable for bulb TC-DG 24d1 2-pin 13 Watt. (Please order separately.)

Including VVG ballast.

With clamping springs for direct snap-in into sheetrock walls.

Accessories:

Coloured glass blue

Flush-mounted frame (wall mounting)

Weight: 2,45 kg

Accessories for indoor lights



Recessed Frame for Downunder II
LI-2536-U

Recessed Wall Fixtures



Frame Basic Recessed Halogen Fixture

Quadratic wall light for halogen lamp max. 20w.
LI-2544



Decorative lamp in satin-finished aluminum enclosure with protective glass.
With protective cover for hollow walls and ceilings.
Fixing by 2 spring clips.
Dimmable with appropriate dimming.
The halogen lamp G4 12V max. must be ordered extra.
Operating voltage 12V (For 230V operation, an additional halogen transformer required).
Dimensions: 90x 90mm, depth 31mm
Panel cutout: 75 x 75mm
Weight: 0,3 kg

Accessories for indoor lights



Recessed Frame for deep Frame lights
LI-2544-U

Recessed Wall Lights Outdoor



Wall Recessed Light Wall-Led 18

LED recessed luminaire for wall or stairs, with 18 LEDs and silver surround.
Comparable to 30 Watt incandescent light.
LI-2550




Fixture for stair or wall-mount. For indoor or outdoor, IP65,
Available with LEDs in white or blue colour.
For operation is a 24 volt LED supply required
Power consumption 3 watt
(max. 7 lamps can be driven over 1 power supply).
2 cable glands allow a simple wiring in series.
Housing: Extreme rigid polycarbonat, screws out of stainless steel,
scratchproof silvergry coated, screen made of highly resistant plastic.
Dimensions: w 155 mm, h 80 mm, d 46 mm. Cut-out hole 146,5 mm x 71 mm
Weight: 0,25 kg

Recessed Wall Fixtures



Recessed Wall Light Fitting Baleo LED B

Decorative recessed luminaire with 14 LEDs, energy-saving.
LI-2552



Supply voltage 230V / 0,8W
Aluminium, silver powder coated.
Protection IP65 - for indoor and outdoor use.
Dimensions: w 126mm, h 126mm, d 66mm, required hole Ø 124mm
Weight: 0,4 kg

Recessed Wall Lights Outdoor



Recessed LED Wall Light Fitting Bileo Brick



LI-2555

Decorative luminaire with 27 LEDs, energy-saving for indoor and outdoor use IP65.
LI-2555

As orientation light or step lighting.
Supply voltage 230V / 1.8W
The brightness corresponds to a 25W incandescent lamp.
Housing: aluminium, silver powder-coated
2 brass screw connections, therefore suitable for through-wiring.
With plastic mounting frame.
Protection class IP65 (for indoor and outdoor use).
Dimensions: W 180mm, H 135mm, D 85mm
Installation cut-out: 176mm wide, 130mm high
Weight: 0,7 kg



Recessed Wall Fluorescent Fixture IP65

Recessed luminaire with front grill and glare shield. For compact fluorescent lamp TC-D13W
Discontinued item - only 4 left in stock
Protection class IP65 for wet rooms or outdoor areas.
With low-loss ballast.
Suitable for fluorescent lamp TC-D /G24d-1 13 Watt.
Please order lamp separately.

Exterior dimensions: W 233mm, H 79mm, D 98mm.
Included in delivery is a plastic recessed pot
Internal dimensions without mounting cup: width 195mm, height 60mm, depth 76mm
LI-2567C-F



Recessed Wall Fluorescent Fixture IP65



GEO-Technik

Recessed luminaire for compact fluorescent lamp PL-C 13W for indoor and outdoor use
LI-2567D-F

Rigid fixture for indoor and outdoor.
With low-loss ballast
Please order extra: fluorescent lamp PL-C /G24d-1 13 Watt.
Aluminium casing, with satined diffusor.
Protection degree IP65 splashing water proof.
Available white or black.
Dimensions: L 233mm, H 79mm
Cut-out: L 225mm, H 60mm, Tiefe 98mm
Weight: 1,3 kg

Recessed Fixtures Round



Recessed Ceiling Light Micro GX53 Energy Saving



www.dimmer.de

Very flat recessed spotlight for installation in hollow ceilings in bathrooms, kitchens, corridors, walk-in wardrobes or as bedside reading lighting.
White or chrome-plated. 5 - 7W, long life.
LI-2570

Very low heat emission.
Suitable for energy-saving bulbs with GX53 base.
Please order bulbs separately.
Light intensity comparable with 20 / 35 Watt halogen light.
Light colour warm tone 3000K.
Power consumption 7W
Voltage 230V
Housing: UV-resistant plastic.
White or chrome-plated.

Dimensions
Ø 90mm
Installation Ø 80mm
low installation depth 30mm.

Discontinued model: small number in stock
Weight: 0,1 kg

	<p>3 pcs. Recessed Downlights Fluorescent 7W Energy Saving</p> 	<p>3 energy-saving recessed spotlights chrome or gold. With longlife lamp GU10 7W, pleasant warm light. LI-2574</p> <p>Very low heat emission. Energy-saving bulbs with GU10 base are included in the price. Light colour: 2700K warm white - comparable with halogen bulbs. The light intensity is comparable with 20 / 35 Watt halogen light. Connection voltage 230V Sheet steel: gold-coloured or chrome-plated. Dimensions: Ø 80mm, recessed Ø 55 - 68mm, depth 80mm. Weight: 0,55 kg</p>
	<p>3 pieces recessed spotlights swivelling downlight 100mm gold</p>	<p>3 moveable spotlights with compact fluorescent lamp GU10 7W. LI-2575</p>
	<p>Recessed LED Downlight 27W adjustable</p> 	<p>Round recessed ceiling spotlight, shallow recess depth. Made of aluminium with power LEDs. White or black. LI-2579-2</p> <p>Swivelling, bright spotlight with low energy consumption. Light colour: 4000K natural white (also warm white 3000K on order). Wide light distribution 36° (24° or 60° also available to order) Luminous flux: 2500 Lm Colour rendering: Ra 90 Voltage: 230V AC Power: 27W Aluminium housing Colour: white (black on request) Protection class: IP20 Diameter 140mm Installation cut-out Ø 125mm Depth 85mm Weight: 0,24 kg</p>
	<p>Recessed LED Downlight 42W adjustable</p> 	<p>Round recessed ceiling spotlight, shallow mounting depth. Made of aluminium with power LEDs. White or black. LI-2579-4</p> <p>Swivelling, bright spotlight with low energy consumption. Light colour: 4000K natural white (also warm white 3000K on order). Wide light distribution 36° (24° or 50° also available to order) Luminous flux: 4800 Lm Colour rendering: Ra 90 Voltage: 230V AC Power: 42W Aluminium housing Colour: white (black on request) Protection class: IP20 Diameter 165mm Recessed cut-out Ø 155mm Depth 110mm Weight: 0,24 kg</p>

Recessed Light Fixtures Rectangular



Frame For Modena LED

Square frame for small, round spotlights. Brushed aluminium.
LI-2581



Square versions:
1-fold 80x 80mm,
2-fold 80x 142mm (in stock)
3-fold 80x 204mm
4-fold 80x 266mm

Installation depth 30mm
With 2 spring clips for hanging in hollow ceiling.

Cut-out diameter 44.5 mm
Weight: 0,1 kg

Recessed Fixtures Round



Power LED Recessed Light 5W adjustable

Round recessed spotlight / downlight with 5 power LEDs and prismatic glass cover, shallow recess depth.
LI-2583-99

Swivel, bright spotlight with low energy consumption.
Very low heat output.
Including Power LED Lamp Epistar.
Light intensity comparable to 50W halogen light.
Light color: 4500K nature white (from 20 pcs warm white 3000K also can be ordered)
Operating voltage: 100 - 260 volt
No extra driver required
Not dimmable
Case made of solid metal
color silver
Dimensions: Diameter Ø 110mm, cut-out Ø 90mm, depth 45mm
Weight: 0,24 kg

Recessed Light Fixtures Rectangular



Small LED recessed spotlight set of 3 Dimel, with transformer IP44



3 pcs. Stainless steel power LED recessed luminaire for indoor and outdoor use. Ready for use with cables.
LI-2587

With high-power LEDs 3 x 0.5W in white or blue.
With round or angular steel cover.
The set includes:
3 spotlights with cables (2m each) and plugs,
1 distributor,
1 mains transformer with plug.
Supply voltage 230V / 2,5W.
Dimensions of the lamps 40mm x 40mm, depth 57mm.
Protection class IP44 (also for damp rooms).
Weight: 0,5 kg

Recessed Fixtures Round



LED Downlight 9W adjustable



LED recessed luminaire with 3 x 3W Power LED and ballast.
LI-2589

Bright luminaire with low energy consumption.
Adjustable recessed LED light fixture.
CREE LED 3x3W
Beam shape: 30° Spot
Light distribution: symmetric
Light colour warmwhite 3000K
With driver and cables
Voltage: 220V - 240V
Dimensions:
Cut out: 90 mm
Max diameter: 102 mm
Protection: IP20 , class III
Brandschutz "F"
Casing material: Aluminium dye-cast
Colour: aluminium matte (on request also white)
Weight: kg

Recessed Wall Fixtures



**Small LED recessed spotlight
Siena Nautik flat IP43**



Small LED recessed luminaire 40mm round with low installation depth for bathroom, kitchen, step, hallway etc.
LI-2590

Luminaire for step or wall mounting for indoor use,
Available with LEDs in white or blue.
A 12 V DC LED supply is required for operation.
Power consumption 0.3 W
(Please order power supply separately. Several luminaires can be operated via one power supply).
Housing: Shatterproof polycarbonate, scratch-resistant silver-grey coating, lens of highly stable plastic.
Protection class IP43
Dimensions:
Ø 40mm,
D 35mm,
Installation Ø 25mm
Weight: 0,1 kg



**Small LED Recessed Light Strip
260mm Ginovra**

LED recessed wall luminaire, rectangular, with 20 LEDs and silver surround.
Light strip, shallow recess depth. IP43
LI-2592

Luminaire for step or wall mounting for indoor use,
Available with LEDs in white, blue, red, yellow or green.
A 12 volt DC LED supply is required for operation. (Please order separately)
Power consumption: 1.6 W
Several luminaires can be operated via one power supply
Housing: Shatterproof polycarbonate, scratch-resistant silver-grey coated, lens made of highly stable plastic.
Mounting frame included in delivery.
Protection class IP43
Impact resistance: IK08

Dimensions:
L 260mm
W 35mm
D 35mm
Mounting cut-out 260mm x 29mm
Weight: 0,35 kg

	<p>LED Recessed Light Roma coloured</p>	<p>LED luminaire round and super flat only 4mm, with 19 LEDs white or coloured. LI-2593</p> <p>Luminaire for step or wall mounting for indoor use, Available with LEDs in red, yellow or blue. A 12 V DC LED supply is required for operation. Power: 1.0 W (Please order power supply separately. Several luminaires can be operated via one power supply). Housing: Polycarbonate, scratch-resistant. With connecting cable 100cm and plug. Protection class IP40</p> <p>Dimensions: Ø 50mm small installation depth 4 mm. Weight: 0,15 kg</p>
---	--	--

Recessed Fixtures Round


	<p>Recessed LED Downlight dimmable 8 Watt</p>	<p>LED downlight round, made of aluminium for recessed ceiling mounting. Pleasant, bright light. LI-2594</p> <p>Very low heat emission. Power LED bulb 8W from Epistar included. Light intensity comparable with 35 Watt halogen light. Light colour 2700K warm white (also 4000K neutral white on order). Beam angle 60° very wide Connected current: 350mA Please order LED power supply or dimmable driver 350mA separately. For brightness control we recommend a dimmable driver VS-LED354 and a phase cut-off dimmer or up to 2 luminaires can be operated via a dimmable VS-LED707 driver with momentary-action switch. Brushed aluminium surface. Dimensions: Ø 78mm, recessed Ø 68mm, depth 45mm Weight: 0,17 kg</p>
	<p>LED Downlight Kit 3 x 5 Watt adjustable</p>	<p>3 energy saver recessed LED spotlights, with adjustable LED lamps 5W. Bright light. LI-2595-3</p> <p>Very low heat emission. 3 Power LED bulbs 5W with MR16 base are included in the price. Light intensity comparable with 20 / 25 Watt halogen light. Electronic LED transformer included. Connection voltage 230V Surface matt silver, gold-plated or chrome-plated. Dimensions: Ø 85mm, recessed Ø 80mm, depth 50mm. Weight: kg</p>
	<p>LED Downlight Kit 5 x 5 Watt adjustable</p>	<p>5 energy-saving spotlights, swivelling with LED lamps 5W. Pleasant, bright light. LI-2595-5</p>
	<p>LED Downlight adjustable 3 Watt</p>	<p>Energy saver spotlight, adjustable, with power LED lamp 3W. Bright and pleasant light. LI-2597</p> <p>Very low heat emission. Power LED bulb 3W with MR16 base is included in the price. Light intensity comparable with 20 Watt halogen light. LED driver included. Connection voltage 230V Surface matt silver, gold-plated or chrome-plated. Dimensions: Ø 85mm, recessed Ø 80mm, depth 50mm. Weight: kg</p>

	<h3>LED Downlight 3W adjustable</h3>	<p>Round recessed spotlight 3 x 1W Power LED made of solid aluminium, low installation depth. Available - only while stocks last ! LI-2598</p> <p>Swivelling, bright spotlight with low energy consumption. Operating voltage 12V / 350mA Light colour bright white or warm white Housing made of solid metal Colour matt silver Protection class IP23 Dimensions: Diameter 90mm, depth 34mm, mounting hole Ø 80mm Weight: 0,24 kg</p>
		

Recessed Wall Lights Outdoor

	<h3>Belkis Round 6 LED Recessed Wall Light</h3>	<p>Small LED recessed wall luminaire. Available in yellow, blue or white. Waterproof LI-25Bel-R1</p> <p>Robust luminaire made of die-cast aluminum, light gray. With 6 yellow, blue or white LEDs. Operating voltage 230 Volt ac (opt. 12 or 24V) Power consumption approx. 2 watts With 5 m connection cable Protection: IP67 Moisture-proof Outside 54 mm, hole 36 mm, depth 23mm. Weight: 0,3 kg</p>
		

	<h3>Belkis Round 12 LED Recessed Wall Light</h3>	<p>LED fixture with horizontal light distribution. Available with yellow, blue or white leds. Robust luminaire made of die-cast aluminium, light grey. With 12 yellow, blue or white LEDs. Operating voltage 230 volts ac (opt. 12 or 24V). Power consumption approx. 3 watts With 5 m connecting cable Moisture-proof IP67 Outside 78 mm, hole 55 mm, depth 28mm. LI-25Bel-R2</p>
---	--	--

	<h3>Belkis Square LED Recessed Wall Light</h3>	<p>LED fixture with horizontal light distribution. Available with yellow or white leds. Robust luminaire made of die-cast aluminium, light grey. With 12 yellow or white LEDs. Operating voltage 230 volts ac (opt. 12 or 24V). Power consumption approx. 3 Watt With 5 m connecting cable Outside 80 x 80mm, hole 70 x 54mm, depth 30mm. Moisture-proof IP67</p> <p>Minimum order quantity: Yellow 1 pc, White 4 pcs. LI-25Bel-S1G</p>
---	--	---

Recessed LED In-Ground Lights

	<h3>LED Ground Light Belkis 2 Round IP67</h3>	<p>Solid aluminium surface mounted spotlight 90mm diameter, radiating to 2 sides. Waterproof LI-25Bel22</p> <p>Rugged cast aluminum die casting, light gray. With 4 LEDs. Operating voltage: 24V dc (230 volts ac only reminder items) Power consumption 1.5 watts With 5 m cable Humidity-proof IP67 Hit proof: IK10 Dimensions: Ø 90 mm, installation height 45mm Weight: 0,9 kg</p>
		

	<h3>LED Recessed Ground Light Belkis 2 Round IP67</h3>	<p>Flat aluminium surface mounted spotlight 90mm diameter, radiating to 2 sides. Waterproof LI-25Bel30</p> <p>Rugged cast aluminum die casting, light gray. With 4 LEDs. Operating voltage: 24V dc or 230 volts ac Power consumption 1.5 watts With 5 m cable Humidity-proof IP67 Hit proof: IK10 Dimensions: Ø 90 mm, installation height 20mm Weight: 0,9 kg</p>
		

Recessed Wall Fixtures

	<h3>LED Recessed Wall Light Vizir</h3>	<p>The light beam is deflected downwards by an aperture. White or coloured light. LI-25VIZWS</p> <p>With 4 LEDs white, yellow, red or blue. Operates with 12V 0.4W. A transformer is required and must be ordered separately. Outer dimensions 120 x 86mm. Delivery incl. flush-mounted installation frame. Material aluminium matt silver. Installation 95 x 60mm, depth 35mm. Remaining stock 1 piece - can no longer be reordered ! Weight: 0,25 kg</p>
		

Pendant Fixtures Office and Shop

	<h3>Office Pendant Light Fixture 515 Direct Indirect</h3>	<p>Elegant, floating lighting with lots of light for modern offices. LI-2612</p> <p>Workplace-oriented general lighting for large desks, CAD workstations, but also for reception counters, meeting tables and conference rooms. With decorative micro-perforation for low direct light component. The main light is emitted indirectly, towards the ceiling. Ideal for room heights between 2.5 and 3 metres. With electronic ballast for flicker-free light with reduced power consumption. Dimensions: L 1160mm, W 307mm, H 94mm. Colour: silver-grey. With steel cable suspension, infinitely height adjustable up to 110 cm. Pendant lamp is delivered incl. illuminant (4x 55Watt TC-L). This item can only be shipped as bulky goods - the surcharge is 17 euros once or by collection. Weight: 6 kg</p>
		

Track spotlights for metal halide lamps

	<h3>MH Flood Light MHL-Design 70W</h3>	<p>Bright, wide-beam floodlight for metal vapour discharge lamp. Energy-saving - HQI 70W = 300W halogen light. For trade fair, shop, foyer, product presentation. Single item from our showroom LI-3150</p> <p>With 3-phase track adapter and heavy-duty anchor. Incl. ballast for use of metal halide lamp HQI-TS 70W lamp Rx7s. Please order the HIT lamp 70W with double-sided base separately. The spotlight must not be dimmed. Housing: Die-cast aluminium Colour: silver Weight: 3,85 kg</p>
		

Accessories for indoor lights

	<p>Barndoor for MHL Floodlight LI-3155</p>
---	--

Halogen Spotlights for Track

	<h3>Halogen Spot Shadow</h3>	<p>Mains-voltage halogen spot made of cast aluminium for 3-circuit track. For PAR30 lamp up to 75W. Dimmable LI-3200</p> <p>Decorative high-voltage halogen light fixture. Suitable for standard 3-phase lighting tracks. The reflector lamp PAR 30 max. 75 W. must be ordered extra. High quality metal housing available in white or aluminum silver Weight: 0,45 kg</p>
		
	<h3>Halogen Spot Base</h3>	<p>Highvolt halogen spotlight with 3 phase track-adaptor. For lamp PAR30 max. 75 W. LI-3201</p> <p>Decorative halogen high-voltage spotlight. Fits all standard 3-phase tracks. Can be fitted with reflector lamp PAR 30 up to max. 75 W. Please order lamp separately. High-quality metal housing available in white or aluminium silver. Remaining stock Weight: 0,5 kg</p>
		
	<h3>Halogen Spot Bima 2</h3>	<p>Dainty halogen spotlight for 3-phase track, 2-beam with 50Watt each. Dimmable LI-3207-2</p> <p>2-beam halogen spotlight with 50 W each. Only suitable for indoor use. Fits all standard 3-circuit tracks.</p> <p>The spotlight can be dimmed when using halogen lamps. Please order bulbs separately. Suitable for GU10 230V bulbs up to 50W. Connection voltage 230V Aluminium housing, colour: silver-grey length: 78 mm Ø 130 mm Height: 255 mm Weight: 0,5 kg</p>
		
	<h3>Low-Volt Halogen Spotlight Eurospot 75W</h3>	<p>LED or halogen spotlight with focused light for object illumination. Long-life low-voltage system with transformer. For 3-phase track. LI-3211</p> <p>Incl. transformer for halogen lamp QR-111 50W - 75W. Fits all standard 3-circuit tracks. The bright spotlight may be dimmed. The beam angle is determined by the choice of lamp (8°, 24°, 45°).</p> <p>Please order the QR-111 halogen lamp separately. Alternatively, an LED lamp can be used (not dimmable).</p> <p>Connection voltage 230V Aluminium housing silver-grey (optionally white). Length 28 cm, width 16.5 cm. Weight: 2,3 kg</p>
		

 	<p>Eurospot Low-Volt Halogen Spotlight MR16</p>	<p>Attractive low-voltage halogen spotlight with transformer for dichroic mirror lamps up to 50W for 3-phase track. Remaining stock. LI-3270</p> <p>Euro Spot MR16 Fits all standard 3-circuit tracks. Suitable for light source type: MR16 (halogen reflector lamp). Socket: pin base G5.3 / GX5.3 Please order suitable halogen lamp separately. Operating voltage 230V AC Lamp voltage 12V , max. 50 Watt Built-in electronic transformer. Low-voltage halogen lamps have a much longer life expectancy than high-voltage halogen lamps. In addition, the filament is smaller and the light is brighter and more uniform than with mains voltage lamps. Housing material: aluminium Colours: White or black. Only limited availability in black. Dimensions: Length 22.5 cm, height 21 cm, diameter 8 cm Weight: 0,92 kg</p>
---	--	---

Surface mounted lights & spotlights

 	<p>Metal Halide Spot Light Nice 70W</p>	<p>Bright, pure white light for illuminating objects. Only 70W HQI power, as bright as 300W halogen light. LI-3324</p> <p>Energy-saving discharge lamp spotlight. Light distribution narrowly focused 15°. Light range up to approx. 6m. Built-in ballast and igniter. The luminaire is not dimmable. Please order the HQI-T 70W lamp (8,000h life) separately. Solid housing made of die-cast aluminium. Dimensions: 32x19x14 cm Silver-grey Weight: 3,5 kg</p>
 	<p>LED Power Spotlight Nice</p>	<p>Bright LED luminaire for illuminating objects in shop windows, boutiques, galleries. Energy-saving, as bright as 100W / 150W halogen light. LI-3328</p> <p>Energy-saving spot with very long-life LEDs. For shop windows, exhibition stands, galleries, etc. Light range up to max. 4 - 5m. Built-in ballast. The luminaire is not dimmable. Including LED bulb 890 Lm Light colour: 3500K neutral white Light distribution: 40 Power consumption: 18W Voltage: 230V Solid housing made of die-cast aluminium. Dimensions: 32 x 19 x 14 cm Silver-grey (on special order also white or black). Weight: 2,7 kg</p>

LED Lights for track lighting



COB LED Track Light 20W



Swivelling LED spot with bright 20 Watt LED lamp, suitable for all standard 3-phase tracks.
Only small quantity left in stock !
LI-3336

Gimbal-mounted swivelling to all sides.
Beam angle 50° spot for product illumination or accent lighting.
Incl. 3-phase track adapter and ECG driver, flicker-free.
Only suitable for indoor use.
The spotlight must not be dimmed.
Incl. high-intensity LED insert.
Luminous flux: 1850 Lm
Light colour: 3000K warm white or 5000K cool white
Supply voltage 230V / 50- 60Hz / 20 Watt
Housing: aluminium and plastic.
Colour: black.
Dimensions: L 220 mm, W 40 mm, H 185 mm.
Weight: 0,88 kg



LED Track Light 18W Triphase



Bright LED spot for 3-phase track for shop windows, trade fairs, shops or living rooms. Solid aluminium.
LI-3338-3

Adjustable track spot with good colour reproduction.
Complete with 18 watt power LED light.
Beam angle: 45 deg
Lumen output: 1600 lm
Light color 4000K (neutral white)
The light intensity is equivalent to 150W halogen light.
With 3 phases universal track adaptor for common current rails.
Supply voltage: 220 - 230V 50 / 60Hz
Valued aluminum housing, black or aluminium silver surfaced
Dimensions: Length 140mm,
diameter 125mm
Weight: 1,05 kg

Surface mounted lights & spotlights



LED Spotlight adjustable focus 27W for Track

LED luminaire, adjustable beam angle 10° - 60° for 3-phase track. For shop windows, trade fairs, picture galleries or shops.
LI-3339

With adjustable mounting bracket.
Complete with 27 watt power LED lamp.
Adjustable beam angle: 10° - 60° deg
Light color 3000K (warm white) or 6000K daylight white
The light intensity is equivalent to 150W halogen light.
With 3 phase universal track adaptor for common current rails.
Supply voltage: 220 - 230V
Valued aluminum housing, silver anodized.
Dimensions: Length 215mm, diameter 100mm
Weight: 2 kg

LED Lights for track lighting



LED Spotlight Shadow for Track

Bright LED luminaire for 3-phase track. Energy-saving and durable. LI-3340



Decorative high-voltage LED lamp.
Suitable for standard 3-phase lighting tracks.
Including LED reflector lamp PAR30 10 W.
Beam spread: 45°
Light color: 3000K warm white (on order also 5000K daylight white)
Operating voltage: 220 - 230V 50 / 60Hz
Power: max. 11W
High quality metal housing available in aluminum silver
Weight: 0,5 kg



Power LED Track Light Cyclos 75W

With 9900 lumens, this spot is as bright as a 150W HQI spotlight. Futuristic adjustable floodlight for shop, house, exhibition and fair. For all common 3-phase lighting tracks. LI-3344



Cardanic adjustable.
Beam angle: 25°
Light color: 3000K warm white (at 2 pcs. also in 4000K neutral white on order)
Nominal LED Lumens: 9900 lm
Incl. track adaptor for most common 3 phase tracks
LED driver flickerfree
This spotlight is not dimmable.
Incl. powerful LED lamp.
Operating voltage: 220 - 240V 50 / 60Hz
Power: 75W
Material aluminium
Only for indoor use.
Colour: silver grey or white (at 5 pcs. also in black on order)
Dimensions: l 277 mm, w 160 mm, h 292 mm
Weight: 3,5 kg



COB LED Track Light 9W

Spot LED orientable con LED brillante de 800 Lm, para vías trifásicas. CRI 90 para la iluminación de productos o de acento. Sustituye a un foco halógeno de 35W LI-3350S



Rotatable 300
Beam angle: 35° (from 10 pcs. also available in 15° or 25°)
Incl. 3-circuit track adapter
LED driver: Tridonic
Fits all standard 3-phase tracks
The spotlight must not be dimmed
Incl. COB LED Philips
Service life L70/B50/C10: 50,000 hrs. (according to IEC 62717 standard)
Light colour: 3000K warm white
Excellent colour rendering quality: CRI 90
Luminous flux of luminaire: 800 lm
Voltage: 220-230V / 50- 60Hz
Power: 9 Watt
Power factor (PF): >0.95
Material: Aluminium
Colour: Black (from 10 pcs. also available in white)
Dimensions: L 207 mm, H 233 mm
Head diameter: 95mm
Protection class: IP20
Only suitable for indoor use.
Weight: 0,88 kg

 	<p>COB LED Track Light 27W black</p>	<p>Swivelling LED spot with very bright LED 2500 Lm, for 3-phase tracks. CRI 90 for product lighting or accent lighting.comparable with 35W HQI luminaires. LI-3353S</p> <p>Adjustable 300° Beam angle: 35° (at 10 pcs. also 15°, 25°, 35° or 60°) Incl. 3 phase track adaptor and electronic ballast. This spotlight is not dimmable. Incl. COB LED Citizen (CLU038) Lifetime L70/B50/C10: 50.000 hours (according to IEC 62717 norm) Available light colours: 4000K nature white (on order 3000K warm white) Very good colour rendering quality: CRI 90 Fixture/LED flux: 2500 lm Voltage: 220-230V / 50- 60Hz Power: 27 Watt power factor (PF): > 0,95 Casing: Aluminium Casing colour: Black (at 10 pcs also white) Dimensions: l 224 mm, h 273 mm Head diameter: 95mm Protection: IP20 Only for indoor use Weight: 0,88 kg</p>
 	<p>COB LED Track Light 27W white</p>	<p>Swivelling LED spot with very bright LED 2500 Lm, for 3-phase tracks. CRI 90 for product lighting or accent lighting.comparable with 35W HQI luminaires. LI-3353W</p> <p>Adjustable 300° Beam angle: 35° (at 10 pcs. also 15°, 25°, 35° or 60°) Incl. 3 phase track adaptor and electronic ballast. This spotlight is not dimmable. Incl. COB LED Citizen (CLU038) Lifetime L70/B50/C10: 50.000 hours (according to IEC 62717 norm) Available light colours: 4000K nature white (on order 3000K warm white) Very good colour rendering quality: CRI 90 Fixture/LED flux: 2500 lm Voltage: 220-230V / 50- 60Hz Power: 27 Watt power factor (PF): > 0,95 Casing: Aluminium Casing colour: White Dimensions: l 224 mm, h 273 mm Head diameter: 95mm Protection: IP20 Only for indoor use Weight: 0,88 kg</p>
 	<p>COB LED Track Light 40W black</p>	<p>Swivelling LED spot with very bright LED 3800 Lm, for 3 phase track. CRI 90 for product lighting or accent lighting. Replaces 35W HQI luminaires LI-3354S</p> <p>Adjustable 300° Beam angle: 35° (at 10 pcs. also 15°, 25°, 35° or 60°) Incl. 3 phase track adaptor and electronic ballast. This spotlight is not dimmable. Incl. COB LED Citizen (CLU038) Lifetime L70/B50/C10: 50.000 hours (according to IEC 62717 norm) Available light colours: 4000K nature white (on order 3000K warm white) Very good colour rendering quality: CRI 90 Fixture/LED flux: 3800 lm Voltage: 220-230V / 50- 60Hz Power: 40 Watt power factor (PF): > 0,95 Casing: Aluminium Casing colour: Black (at 10 pcs also white) Dimensions: l 224 mm, h 273 mm Head diameter: 95mm Protection: IP20 Only for indoor use Weight: 0,88 kg</p>

	<h3>COB LED Track Light 40W white</h3>	<p>Swivelling LED spot with very bright LED 3800 Lm, for 3 phase track. CRI 90 for product lighting or accent lighting. Replaces 35W HQI luminaires LI-3354W</p> <p>Adjustable: 300° Beam angle: 35° (at 10 pcs. also 15°, 25°, 35° or 60°) Incl. 3 phase track adaptor and electronic ballast. This spotlight is not dimmable. Incl. COB LED Citizen (CLU038) Lifetime L70/B50/C10: 50.000 hours (according to IEC 62717 norm) Available light colours: 4000K nature white (on order 3000K warm white) Very good colour rendering quality: CRI 90 Fixture/LED flux: 3800 lm Voltage: 220-230V / 50- 60Hz Power: 40 Watt power factor (PF): > 0,95 Casing: Aluminium Casing colour: Black (at 10 pcs also white) Dimensions: 1 224 mm, h 273 mm Head diameter: 95mm Protection: IP20 Only for indoor use Weight: 0,88 kg</p>
		

Surface mounted lights & spotlights

	<h3>Punto Low-Volt Halogen Light 75W-100W</h3>	<p>Professional aluminium spotlight, halogen spotlight in studio design from Italian production. Dimmable spotlight with transformer for illuminating goods, plants or art objects. LI-3405</p> <p>For illuminating goods, pictures, restaurant, plant lighting, shop lighting. With swivel mounting bracket. Directional light for object lighting. With 12V transformer for longer service life and lower energy requirements. For low-voltage halogen lamp R111 12V AC G53 (75W and 100W) Please order the lamp separately. Good colour rendering quality: CRI 100 With mains cable 120cm and plug. Connection voltage 230V AC Professional housing made of anodised aluminum profile with black decorative ring. Optionally also available with 3-phase adapter for power rails. Length 212mm, Ø 130mm Weight: 2,95 kg</p>
		

	<h3>Punto Spotlight 35W HID</h3>	<p>Bright aluminium discharge lamp spotlight in studio design. For 35W HID lamps from Italian production. For displaying goods or for sculptures indoors. LI-3410</p> <p>Bright discharge lamp spotlight made of aluminium. For bulbs 35W HID from Italian production. For displaying goods or sculptures indoors.</p> <p>With built-in ballast and igniter. Lamp wattage 35W - The brightness corresponds to about 200W halogen light. Suitable for ES111 35W HID discharge lamp base GX10. Please order lamp separately.</p> <p>With mains cable and plug. Connection voltage 230V AC Professional housing made of aluminium profile matt anodised with black trim ring and swivelling mounting bracket. Length 280mm, Ø 130mm Weight: 2 kg</p>
		



Punto LED Spotlight 7W



Compact LED spotlight made of aluminium. Directional illumination of objects and images. Italian manufacturing.
LI-3414

With adjustable mounting bracket.
Available on request in different colors.
Complete with 7 watt power LED bulb.
Light distribution: 35°
Light color: CCT 4500K (cool white)
The light intensity equivalent to 50W halogen light.
With 120cm power cord and plug.
Supply voltage 230V
Professional profile anodized aluminum housing with matte black trim ring.
Length 130mm, diameter 140mm
Weight: 1,1 kg

Track spotlights for metal halide lamps



MH Spotlight Seven 70W TD for Track



Directional light for object illumination - HQI corresponds to 300W halogen light. For mounting on 3-circuit track. Italian production.
Remaining stock - only 1 piece in stock
LI-3520

Beam angle 32°. (Light circle Ø 150cm at 2.5m distance).
High luminous intensity, for illuminating showcases, pictures, smaller objects.
Incl. electronic ballast for the Longlife metal halide lamp HQI-TS 70W.

With 3-phase track adapter and heavy-duty anchor for all commercially available tracks.
The spotlight must not be dimmed.
Please order HQI-TS 70W lamp separately (available in daylight, neutral white and warm white).

Housing: cast aluminium.
Colour: white.
Dimensions: L 243 mm, W 180 mm, H 260 mm.
Weight: 2,65 kg



Seven Spot-Light MH 70W HF for Track



Tightly focused light for highlights in your exhibition. For HQI lamp. For 3-phase track.
LI-3522

This spotlight projects a uniform, tightly focused circle of light 24°.
Incl. flicker-free electronic ballast.
The light intensity is comparable to 300W halogen.
Suitable for the long-life and very bright metal vapour discharge lamp HQI-T 70W.
Please order the lamp separately (available in daylight, neutral white or warm white).

The luminaire is NOT dimmable.
It is suitable for continuous operation.
Housing cast aluminium,
colour white or silver.
With 3-phase adapter and heavy-duty anchor for commercially available tracks.
Dimensions: L 300mm, W 140 mm, H 225 mm.

Remaining stock - only 1 piece in stock.
Weight: 2,3 kg

Surface mounted lights & spotlights

	<p>Halogen Spotlight Astro 1 GU10</p>	<p>Swivel ceiling spotlight with square mounting plate, up to 50 W LI-4455</p> <p>Modern halogen spotlight for ceiling mount. Massive appearance of thick aluminum components. Matte brushed aluminum. Suitable for GU10 lamps 50W. Lamp to be ordered separately. Supply voltage 230V Dimensions: L 120mm, W 65mm, H 100mm Weight: 0,25 kg</p>
	<p>LED Spotlight Astro 1 GU10</p>	<p>Swivelling aluminium ceiling spot with square mounting plate with GU10 LED lamp LI-4455L</p> <p>Modern halogen spotlight for ceiling mount. Massive appearance of thick aluminum components. Matte brushed aluminum. Including LED lamp GU10 5W. Light color 3000K warm white Comparable to 50w halogen light. Supply voltage 230V Dimensions: L 120mm, W 65mm, H 100mm Weight: 0,25 kg</p>

Track spotlights for metal halide lamps

	<p>Track Spot Lival Power 70-T MH, silver</p>	<p>Bright HID metal halide Lival track spotlight for HQI, energy-saving. Light range up to 7m Discontinued item - only 1 left in silver. LI-6084C</p> <p>Spotlight for bright shop lighting, for foyers and ideal for exhibition stands.</p> <p>Built-in, low-loss ballast and igniter with thermal switch + short-circuit protection. The luminous efficacy corresponds to about 300 Watt halogen. Light distribution 22° (7° or 30° on special request), Light range up to max. 7m. Please order the metal vapour lamp HQI-T 70W with one-sided base G12 separately. The luminaire is not dimmable.</p> <p>With track adapter for snapping onto standard 3-phase tracks.</p> <p>Protection class IP20, class I. Toughened UV-protective glass. Housing metal, silver RAL 9006. Dimensions: W 220mm, L 190mm, H max. 260mm. Weight: 2,9 kg</p>
	<p>Track Spot Lival Power 70-T MH, black</p>	<p>Bright HID discharge lamp spotlight for track, energy-saving. Light range up to 7m Discontinued item - only 1 left in black from our showroom. LI-6084S</p>
	<p>Spot Lival Power 150-T MH, white</p>	<p>Bright discharge lamp spotlight for HQI lamp, energy-saving. Light range up to 9m Discontinued item - only small quantities available. LI-6085-W</p>
	<p>Track Spot Power Sodium-T 100W Lival</p>	<p>White track spotlight for illuminating goods with a slightly reddish-yellowish hue. Pleasant light for baked goods or jeans shop. Bright sodium vapour lamp spotlight with 3-phase adapter for product presentation, energy-saving. Article is only available for a limited time !</p> <p>LI-6087AC</p>



Shop-Master CDM-T 70 Light



Decorative spotlight, energysaving. With light source and electronic gear. LI-6265

For snapping onto all commercially available 3-phase tracks.
 With electronic ballast, flicker-free.
 Light distribution 24°.
 Lamp and ballast unit are completely separated for better heat distribution. Including lamp CDM-T 70W -830 (15.000h).
 Electronic ballasts with switch-off in case of defective or used lamps and absolutely flicker-free operation.
 Lamps can be changed without tools !
 Housing made of thermoplastic material.
 Colour: silver-grey (optionally white or black).
 Discontinued item. Only small quantities are available.
 Weight: 0,85 kg

Wall Mount Light Fixtures



Bed-head LED Light Fixture for Hospital



Multifunctional lighting for wall mounting behind the patient's bed in the hospital room.
 Minimum order quantity 2 pieces
 LI-6339

Lighting and distribution unit for headboards. Intended for sickrooms, but can also be used in laboratories or in the production of or in the production of precision equipment.
 The unit ensures direct and indirect lighting.
 It consists of three completely separate compartments, two of which are for lighting and additional components. The third chamber is separate with dual function, as a channel for medical gases and glare protection. Both components have a PC diffuser for soft, direct and indirect lighting.
 Housing made of extruded aluminium profile anodised with polyester powder coating.
 Total luminaire power: 61.0W
 Bright colour temperature 4000 K
 Colour rendering index of (CRI) >80
 LED lifetime is 54000 hours, with flux after 50000 hours does not fall below 80% of the original flux. (L80B10).
 The initial luminous flux of the luminaires is 8328lm.
 Efficiency of the luminaires not less than 137lm/W.
 Light colour deviation (SDCM) less than 3. Emissivity is UGR < 16.
 Dimensions of luminaires 1200/220/150 A/B/H [mm].
 Mechanical protection degree IP20.
 The luminaire fitting can be maintained as the LEDs and drivers of the luminaire are replaceable due to the ZHAGA standard.
 The manufacturer has valid certificates: ISO 9001: 2015, ISO 27001: 2013, ISO 14001: 2015, ISO 45001: 2018, ISO

Additional equipment, such as safety plugs, telephone socket, etc., is possible at an extra charge:

- 1 x 2P+E-SOCKEL WHITE 30 €/pce.
 - 1 x 2P+E-SOCKEL RED 42 €/pce.
 - 1 x RJ11-SOCKEL 48 €/pc.
 - 1 x LAN RJ45 BOCK 48 €/pc.
 - 1 x TV/RD/SAT-SOCKEL 48 €/pc.
 - 1 x SISTER CALL SWITCH 42 €/pc.
 - 2 x SINGLE-POLE SWITCH 24 €/pc.
- Weight: 1,5 kg

Floor and Stand Lights



Indirect Stand Light Office 515

Flexible and energy-saving lighting for the modern office in a contemporary design.

For glare-free illumination of a double workstation, but also for foyers, reception areas, meeting and conference rooms.
 Strong upward light distribution and dimmed downward light distribution (glare-free).
 With integrated 2-position switch on the luminaire head for either 50% or 100% light output.
 Energy-saving and bright due to 4 compact fluorescent lamps 55 Watt (included in delivery).
 Luminaire head can be swivelled by 180°.
 Decorative micro-perforation for small direct light component.
 With clip-in cover as standard.
 Ideal for room heights between 2.5 and 3 metres.
 Height: 190 cm
 Colour: alutech-silver
 LI-7030



Indirect Stand Light Office 515

Flexible and energy-saving lighting for the modern office in a contemporary design.

For glare-free illumination of a double working place, but also for foyers, Reception areas, meeting and conference rooms.
 Strong light emitted upwards and subdued light downward (low glare).
 With an integrated 2-stage switch on the lamp head for either 50% or 100% light output.
 Energy efficient and bright light from four 55 watt compact fluorescent lamps (included).
 180° swivel head.
 Decorative microperforated for small direct light component.
 With tool-free clip-on cover plate.
 Ideal for room heights of between 2.5 and 3 meters.
 Voltage: 220 - 230V, energy-saving.
 Height: 190 cm
 Color: silver-alutech
 LI-7032

Work Lights



Desk lamp with articulated arm design energy-saving 11W



Energy-saving desk lamp and bright aluminium articulated lamp with table base or clamp. Incl. fluorescent lamp PL 11W.
 LI-7620
 Flexible metal lamp with 3 joints.
 The lamp head is made of plastic, with power switch.
 With clamp fastening for table top (on special order with stable table base).
 With low-loss ballast.
 Including compact fluorescent lamp G23 11W.
 With 150cm connection cable and mains plug.
 Colour silver
 (from 40 pcs. also available in other versions)
 Weight: 2 kg

Industrial Lights for direct Canopy Mounting



Heat-resistant Luminaire max. +160° C



Bright heatproof luminaire HID 70W / 150W for extreme ambient temperatures in climatic chambers, ovens, Industrial furnace and other applications.
LI-7900

Lighting temperature-resistant for strong temperature fluctuations. Included in delivery is a pressure compensation container with 0.5m metal flex connection cable for mounting outside the temperature range. (other lengths available on request). The matching ballast is also mounted outside the chamber (please order separately). This way, only the luminaire is directly exposed to extreme temperature fluctuations and humidity.

Heat-resistant glass: Max. 180°C
 Temperature change: Up to 150°C per minute.
 Temperature range tested in long-term operation -50°C ... +135°C (with 70W lamp)
 Calculated range: -70°C...+160°C
 Aluminium reflector for symmetrical light emission 60° angle.
 Luminous flux: 7000Lm (70W) / 12500 Lm (150W)
 Colour rendering quality: CRI 92 excellent
 Lamp life: approx. 15000 h
 Energy-saving: 70W ceramic corresponds to approx. 300W halogen light.

150W ceramic = 550W luminous intensity.

Please order ceramic lamp HCI-TS 70W or 150W separately.

Efficiency: 58 %
 Heat output: 29.4 W (70W) / 63.0 W (150W)

Housing: Die-cast aluminium, all screws are stainless steel.
 Swivelling mounting bracket.
 Both seals in the spotlight: silicone foamed, temperature resistant in the range -50 °C to 200 °C
 Protection class: IP65
 Dimensions: Width 280, height 210, depth 165 mm

Minimum order quantity 2 pcs.

* On request, we can manufacture luminaires for other applications *
 Weight: 4 kg



Heat-resistant LED Floodlight +100 C degree



Bright heatproof luminaire for extreme ambient temperatures in sauna, ovens, Industrial furnace and other applications.
LI-7910

Luminaire for high ambient temperatures.

Constructed temperature range: -70°C ... +100°C
 Temperature alternation: Max 100°C deg per minute.
 Light distribution: symmetrical 60° angle.
 Lamp life: approx. 30000 hours
 Energy saving: 25W LED, equivalent to 300W halogen light.
 Voltage: 205V - 265V / 50 Hz

Case: aluminum gray.
 Protection class: IP65
 Dimensions: Width 280, height 210, depth 165 mm

* On request we manufacture for other lighting applications *
 Weight: 2,5 kg

LED Sticks and Bars



RGB LED Strip board 25cm

Flexible ribbon with 24 LED in red, green and blue colour for free colour mixing.
 Smooth color change and color blends in millions of colors are possible absolutely in sync at any speed.
 For operation a power supply and a control unit are required.
 With these additional components can also be operated more LED strips. The connection of the strips is available via the connection cable with connectors.
 Length 25 cm,
 power 2.65 W.
 LI-8000

Colour Light Controllers



LED Controller RGB + Driver 12V / 24V

For colour mixing and control of RGB LED light 12V or 24V.
 8 different programmes for automatic colour change or fixed colour setting.
 Connection for external buttons.
 An LED power supply unit 12V or 24 V DC is required for operation.
 3 output channels 12/24V with max. 2A
 Maximum connectable power: 120 Watt LED power / 24V
 or 60 Watt / 12V
 LI-8009



RGB Controller with Remote Control

For colour mixing and control of RGB LED light 12V or 24V.
 LI-8011

3 outputs: 12/24V
 Max. Current carrying capacity 5A per channel.
 Operation only with an external power supply of 12V or 24V DC.
 4 automatic programme sequences, as well as 15 static colour settings are selectable.
 Brightness can be selected in 3 dimming levels.
 Maximum distance to remote control 7m.
 Synchronisation with other RGB controls is possible.
 The programmes can be called up with the enclosed IR remote control.
 If a radio remote control is required so that the control unit can also be mounted invisibly behind panelling, we recommend our RGB Controller LI-8017.
 Dimensions 102mm x 40mm x 18mm
 Weight: 0,19 kg



DMX Colour Scene Controller

Control unit with 30 programmes and colour change with DMX 512 output for RGB LED luminaires.
 Demonstration unit at reduced price
 LI-8025



For controlling RGB LED spotlights or other luminaires that can be controlled via DMX.
 There are 30 colour programmes available, which can be called up with the enclosed radio remote control.
 The programmes can be called up via the buttons on the unit or via the hand-held transmitter.
 Power consumption: 5W
 DMX output: XLR-3 socket
 PC interface: RJ45 connector
 Dimensions: 175 x 45 x 35mm
 Weight: 0,3 kg



3 Channel LED Driver PWM RGB 12 - 24V

To regulate LED with 12 / 24V by 10V analog input.
 External supply voltage 12V or 24V DC required depending on LEDs.
 LED voltage: 12V/24V
 3 control channels with max. 1.3A load capacity each.
 3 analogue inputs 0 - 10V or 1 - 10V
 Length 167mm, W 38mm, H 30mm
 LI-8030



3 Channel LED Driver PWM RGB 24V

To regulate LED with 24V by 10V analog input.
 External supply voltage 24V DC required depending on LEDs.
 LED voltage: 24V
 3 control channels with max. 2A load capacity each.
 3 analogue inputs 0 - 10V or 1 - 10V
 Length 167mm, W 38mm, H 30mm
 LI-8031

LED Sticks and Bars



LED Aluminium-Profile Light 0.5m warm white



Delicate, bright LED bar to display case lighting, interior or exterior, with connectors for 12V.
 LI-8039

Ideal for exhibition stands, shop window lighting, display lighting, display cases, shelves, kitchen base ...

Light color: warm white 3000K with 30 LEDs, high brightness

Very wide 120 ° viewing angle

Operating voltage 12 Volt DC / 600mA

Up to 10 bars can be connected via the connector.

A 12V power supply must be ordered extra.

IP65

Dimensions 500mm x 11mm x 9mm

Weight: 0,12 kg

Flexible LED Stripes



Flexible Power LED Strip Light SMD per Meter



Flexible LED strip with 120 bright LEDs in white or various light colours. Strip can be shortened.

LI-8042

Voltage: 12V DC

Power: 10W / m

120 SMD LEDs per m

Can be cut with scissors each 6 Leds (45mm)

Backside with strong self-adhesive tape to stick on plain and clean surfaces.

We cut this strip in full meter length to your specification, up to 10 meters.

The wires have to be soldered on one end.

Only for dry ambient.

Length: 1m, 2m, 3m, 4m, 5m, 6m, 7m, 8m, 9m or 10m

Dimensions: width 8mm, thickness 2.5 mm

Weight: kg

Flexible LED Strip Light 24V SMD 1m

Flexible LED ribbon tape in several colours. Can be cut with scissors.
 LI-8045

LED Sticks and Bars



LED Stripe Rigid 30 LED 37,5cm



GEO-Technik

Thin light strip with 30 LEDs in white, red, yellow, green or blue. For 12V. Special offer - remaining stock - can no longer be reordered.
 LI-8050

For direct or indirect lighting and decoration.

(e.g. as lighting behind the TV or under shelves and cupboards), on the vehicle (observe traffic regulations!) or e.g. in model making.

A 12V power supply is required for operation.

Power consumption 200mA

Power 2.4 W

Light colour white 5500K or warm white 3000K or coloured.

Several LED strips can be operated from one power supply.

At both ends of the LED strip are short connecting cables with connectors for connection to the power supply or for additional LED strips.

Please order the power supply separately.

The LED strips are not moisture-proof and are only suitable for indoor use.

Length 375 mm, width 10 mm, height 8mm.

Weight: kg

	<p>LED Bar 63cm waterproof, warm white</p>	<p>Rigid LED bar with 36 LED for indoor and outdoor. With connectors for 12V. LI-8051-6</p>
		<p>Fully encapsulated and waterproof (IP67) LED Strip with 36 warm white LEDs Piranha (3000 K). With two connection cables (one side with socket, one end with plug, Length approx 18 cm) for connecting several bars and an extra cable for the AC adapter connector (AC adapter not included). Includes 3 mounting clips for installation. Length about 63 cm (without connecting cable). Ideal for direct or indirect lighting in the home (eg as lighting behind the TV or under shelves and cupboards), On the vehicle (note StVO!) or for example, in model building. Operating voltage 12 V DC / 300 mA. A maximum. 8 pieces of LED strips can be connected in series. Power LEDs are characterized by high luminous efficiency, wide projection angle and the special design with 4 solder terminals, which guarantees optimum heat dissipation. Dimensions about 18 x 13 mm. Weight: kg</p>

Flexible LED Stripes

	<p>LED Strip Light Flexible 12V 8mm SMD 0.5m</p>	<p>Flexible, self-adhesive LED strip, 50cm long. LED strip with 30 x SMD 3528 white or coloured. LI-8052</p> <p>Voltage: 12V DC Power: 5.28W / m 33 SMD LEDs Can be cut with scissors each 3 Leds (45mm) Backside with strong self-adhesive tape to stick on plain and clean surfaces. The wires have to be soldered on one end. Only for dry ambient. Length: 500mm Dimensions: width 8mm, thickness 2.5 mm Weight: kg</p>
	<p>LED Strip Light Flexible 12V 8mm white, per Meter</p>	<p>Flexible, self-adhesive LED strip, length as required. LED strip with 60 x SMD 3528 white per metre. LI-8053</p>
	<p>RGB LED strip waterproof, flexible per metre</p>	<p>Selfadhesive LED tape ribbon splashproof, multi-coloured for 12V controllers. LI-8060-3</p> <p>For decorations, backlighting, bathrooms, advertising banners and for pulling into aluminium profiles. Connecting voltage 12V DC Power: 7 Watt /m Bright SMD 5050 RGB LEDs Each chip contains 3 coloured LEDs to produce pure mixed colours. Radiation angle: 110°. LED spacing 33mm. The ribbon can be cut at 10cm intervals. The connection is made by soldering points. Width 12mm. There is a strong self-adhesive tape on the back. A 12V DC power supply and an RGB control unit are required for operation. Protection class IP65 (splash-proof) Weight: kg</p>
		



LED Light Strip IP65 Flexible Outdoor white per m

12V LED strip moisture-protected for outdoor use, self-adhesive, with SMD LEDs. 3.6W per metre.
 For decorations, backlighting, bathroom, kitchen and for pulling into aluminium profiles.
 Connected voltage 12V DC
 Power: 3,6 Watt
 Powerful SMD LEDs with 120° beam angle.
 Light colour 4500K neutral white (on request also warm white, red, green or blue)
 LED spacing 20mm
 The strip can be cut at 10cm intervals.
 At the end there are 10cm short connection strands.
 Width 8,5mm, length 100cm
 There is a strong self-adhesive tape on the back.
 A 12V DC power supply is required for operation.
 Protection class IP65 (rainproof)
 LI-8061-1

Colour Light Controllers



LED Controller RGB Driver 350 mA Chromoflex



For colour mixing and control of RGB LED light 350 mA.
 LI-8100

8 automatic programmes.
 Connection for external buttons.
 3 LED outputs 350mA
 An LED power supply unit 12 V or 24 V DC is required for operation.
 One or more RGB LED lamps can be operated in series.
 A maximum of 3 RGB luminaires (with 12V supply voltage) or 6 RGB luminaires (with 24V supply voltage) can be connected.
 Dimensions: L95mm, W 50mm, H 38mm
 Weight: kg

Emergency Lights



Emergency Exit Light LED Aluminium + Flag



Safety light with LED lamp, batteries, straight flag and exit pictographs.
 LI-9050

Universal escape light fixture for wall or ceiling surface mount.
 For recessed wall / ceiling mount or for pendant installation are accessory adapters available.
 With straight flag / diffuser for the illuminated pictograph.
 Visibility distance: 22m according to DIN EN 60598 T2.22
 With LED lamp 3W and NiMH battery 4.8V
 The lamp is continuous lighted und switches automatically to battery power, if power line fails.
 With LED function indicator, test button, deep discharge protection and electronic switching.
 Autarkic operating time: 3 hours with the battery.
 3 pictographs EXIT direction are included.
 Top part aluminium profile, white coated.
 Acrylic flag
 Protection grade IP40
 Length 250mm, height 198mm, max. depth 50mm.
 Weight: 0,8 kg

	<p>Emergency Exit Light LED Aluminium + Flag</p>	<p>Emergency Exit Light LED + Flag LI-9051</p> <p>Escape route luminaire for wall, ceiling or surface mounting. With large illuminated lens to accommodate the illuminated pictogram. Large recognition range up to 24m according to DIN EN 60598 T2.22. With LED lamp 4W and NiMH battery 4.8V. The emergency luminaire shines continuously and switches to battery operation in the event of a power failure. Illumination time 3 hours via built-in rechargeable battery. With LED function display, test button, deep discharge protection and electronic switching device. 4 pictograms FLIGHT DIRECTION are included. Upper part made of plastic, white Acrylic lens Protection class IP40 Length 240mm, width 175mm, max. depth 50mm</p> <p>Frames for ceiling or wall installation or pendants for suspension are available as accessories. Weight: 0,8 kg</p>
	<p>Emergency Exit Light Flag IP65</p>	<p>Escape route luminaire with fluorescent lamp 8W, vertical lens and escape route symbols for indoor and outdoor use. Discontinued item - 1 pc. Remaining stock LI-9060</p> <p>Escape route luminaire for surface ceiling mounting or recessed mounting. With vertically projecting diffuser for affixing one of the escape route symbols supplied. The luminaire also emits light to the surroundings for better orientation. With fluorescent lamp 8W T5 and NiCd battery 3.6V. The light is always on and switches to battery operation in the event of a power failure. Light duration 3 hours via built-in rechargeable battery. A small red LED indicates when mains power is available. 3 pictograms FLIGHT DIRECTION are included. White housing Splashproof IP65 Length 365mm, width 170mm, depth 200mm. Discontinued item - 1 pc. Remaining stock Weight: kg</p>
	<p>Emergency Exit Light with Battery</p>	<p>Escape sign luminaire with long-life fluorescent lamp 8W, emergency luminaire. LI-9070</p> <p>Emergency exit luminaire for wall or ceiling mounting. Light duration in case of power failure 1 hr. or 3 hrs. Detection distance approx. 21m. With fluorescent lamp 8W T16 and NiCd battery 3.6V. Protection class IP20. Housing colour white, with escape sign "below" Width 335mm, height 130mm, depth 80mm. Weight: 0,5 kg</p>
	<p>LED Emergency Exit Light with Battery</p>	<p>Escape sign luminaire with battery and maintenance-free, bright LED lamp, emergency luminaire. LI-9072</p> <p>Emergency exit luminaire for wall or ceiling mounting. Light duration in case of power failure 1 hr. Detection distance approx. 21m. With LED lamp 3W and NiCd battery 3.6V. Protection class IP65 moisture-proof. Housing colour white, with escape sign "down" Width 357mm, height 110mm, depth 57mm. Weight: 0,5 kg</p>

	<h3>Emergency Exit Light LED with Battery</h3>	<p>Emergency light with battery, LED lamp 4W and escape symbols. IP54 for wet environment LI-9075</p> <p>Universal fixture for wall / ceiling surface mount or pendant mounting. Large illuminated surface for the pictograph. Large viewing distance: 24m according to DIN EN 60598 T2.22 With LED lamp 4W and NiMH accu 3.6V The security light stays continuous on and switches automatically to battery, if power line fails. A small red LED indicates if AC power line is present. Autarkic operating time: 3 hours with the battery. With LED function indicator, test button, deep discharge protection and electronic switching. 4 pictograms ESCAPE DIRECTION BGV A8 are included. White plastic housing Protection class IP54 Dimensions: Length 250mm, width 174mm, depth 34mm. Weight: 0,2 kg</p>
		

Accessories for indoor lights

	<p>Vertical Glass Diffusor for Emergency Light Stair LI-9083</p>
---	--

Emergency Lights

	<h3>Emergency Light Secur</h3>	<p>Emergency lighting with fluorescent lamp 8W for wall mounting or installation. 3 h battery operation. Discontinued item - 1 pc. Remaining stock LI-9091</p> <p>Emergency luminaire for surface wall mounting or recessed mounting. With fluorescent lamp 8W T5 and NiCd battery 3.6V. In the event of a power failure, the fluorescent tube is automatically switched on for 3 hours via the built-in rechargeable battery. A small red LED indicates when mains power is available.</p> <p>The light can be operated in several modes: 1) Standby mode - the light switches on automatically only in the event of a power failure, 2) Permanent circuit - the light is always on, 3) Stand-by mode - in addition, the light can be switched on remotely via a control connection.</p> <p>White housing made of sturdy plastic, water-protected IP65 Width 350mm, height 117mm, depth 76mm</p> <p>Discontinued item - 1 pc. Remaining stock Weight: 1,1 kg</p>
		


Accessories for indoor lights

	<p>Vertical Wall mounting bracket for Emergency Light STAIR LI-9095</p>
	<p>Horiz. Wall-Mount Bracket f. Emergency Light STAIR LI-9096</p>
	<p>Pictograph left for Emergency Exit Light LI-9097L</p>
	<p>Pictograph right for Emergency Exit Light LI-9097R</p>
	<p>Pictograph down for Emergency Exit Light LI-9097U</p>

Industrial Lights for direct Canopy Mounting



LED Floodlight warehouse and fuel station 100W IP66



Energy-saving floodlight and spotlight for hall ceilings, tunnels, petrol stations, sports halls and high-bay warehouses.
Luminous flux 14120 Lm, dimmable 100 Watt power LED luminaire on request - as bright as 1500W halogen light.
LI-D110

Bright lighting for ceiling mounting.
Light distribution: Symmetrical 90° (from 4 units can be ordered in 120° or asymmetrical AS55°).

With built-in LED driver and stabilisation for uniform brightness even with voltage fluctuations.

Low power consumption, no maintenance costs, very long service life.

Completely ready for operation, incl. LED illuminant.

The large number of power LEDs results in better heat distribution in the luminaire and a longer service life.

Colour rendering index: Ra 80

Operating voltage 100V - 277V / 50 - 60Hz

Luminous flux: 14120 lm

Power factor 0.9

Ambient temperature during operation: -35° C ... +45° C

Power consumption: 99W

Humidity: 10% - 90%

LED lifetime > 74000 hrs.

Colour temperature 4000 K (daylight)

Very stable aluminium die-cast housing

Painting: Anthracite RAL 7039

Protection class IP66 splash-proof and dust-proof.

Dimensions: L 360mm, W 291mm, H 73 mm.

On special order:

also dimmable via DALI

99W or 184W

3000K or 6000K

Rotatable ceiling fixture


Ball-impact grille

Emergency power battery 1h

Weight: 7,18 kg



LED Floodlight warehouse and fuel station 138W IP66



Bright, energy-saving floodlight and lighting for hall ceilings, tunnels, petrol stations, sports halls and high-bay warehouses.

Luminous flux 21455 Lm, dimmable 138 Watt power LED luminaire on request - as bright as 2000W halogen light.
LI-D111

Bright lighting for ceiling mounting.

Light emission: Symmetrical 90° (from 4 units can be ordered in 120° or asymmetrical AS55°).

With built-in LED driver and stabilisation for uniform brightness even with voltage fluctuations.

Low power consumption, no maintenance costs, very long service life.

Completely ready for operation, incl. LED illuminant.

The large number of power LEDs results in better heat distribution in the luminaire and a longer service life.

Colour rendering index: Ra 80

Operating voltage 100V - 277V / 50 - 60Hz

Luminous flux: 21455 lm

Power factor 0.9

Ambient temperature during operation: -35° C ... +45° C

Power consumption: 138W

Humidity: 10% - 90%

LED lifetime > 74000 hrs.

Colour temperature 4000 K (daylight)

Very stable aluminium die-cast housing

Painting: Anthracite RAL 7039

Protection class IP66 splash-proof and dust-proof.

Dimensions: L 360mm, W 291mm, H 73 mm.

On special order:

also dimmable via DALI

99W or 184W

3000K or 6000K

Rotatable ceiling fixture


Ball-impact grille

Emergency power battery 1h

Weight: 7,18 kg



LED Floodlight warehouse + fuel station 184W IP66



Bright, energy-saving floodlight and lighting for hall ceilings, tunnels, petrol stations, sports halls and high-bay warehouses.

Luminous flux 24400 Lm, dimmable 184 Watt power LED luminaire on request - as bright as 2800W halogen light.
LI-D112

Bright lighting for ceiling mounting.

Light distribution: Symmetrical 90° (from 4 units can be ordered in 120° or asymmetrical AS55°).

With built-in LED driver and stabilisation for uniform brightness even with voltage fluctuations.

Low power consumption, no maintenance costs, very long service life.

Completely ready for operation, incl. LED illuminant.

The large number of power LEDs results in better heat distribution in the luminaire and a longer service life.

Colour rendering index: Ra 80

Operating voltage 100V - 277V / 50 - 60Hz

Luminous flux: 24400 lm

Power factor 0.9

Ambient temperature during operation: -35° C ... +45° C

Power consumption: 184W

Humidity: 10% - 90%

LED lifetime > 74000 hrs.

Colour temperature 4000 K (daylight)

Very stable aluminium die-cast housing

Painting: Anthracite RAL 7039

Protection class: IP66 splash-proof and dust-proof.

Dimensions: L 360mm, W 291mm, H 73 mm.

On special order:

also dimmable via DALI

99W or 138W

3000K or 6000K

Rotatable ceiling fixture

Ball-impact grille

Emergency power battery 1h

Weight: 7,18 kg

Linear Trunking Light Systems for Office and Hall



**Linear LED Light Lane 115cm
70W IP43**



Energy-saving glare-free batten luminaire 11160 Lm for hall ceilings, sports halls, multi-purpose halls, halls and high-bay warehouses.
With dimming function.
LI-D140

Bright lighting for ceiling mounting.
This surface-mounted luminaire replaces the conventional 150W HID HQI luminaires.

Built-in LED driver and stabilisation for uniform brightness even with voltage fluctuations.

Low power consumption, no maintenance costs, very long life.

Completely ready for operation, incl. LED bulbs.

The large number of power LEDs results in better heat distribution in the luminaire and a longer service life.

With internal through-connection - The continuous row only needs to be connected electrically at one end.

A maximum of 20 luminaires can be connected in a row.

Colour rendering index: Ra 80

UGR: 16

Operating voltage 220V - 240V / 50 - 60Hz

Light emission: Symmetrical 90° (alternatively 60°)

Luminous flux: 11160 lm

Power factor: 0.97

Ambient temperature: -35° C ... +45° C during operation

Total power consumption: 70W

Humidity: 10% - 90%

LED lifetime > 70000 hrs.

Colour temperature 4000 K (daylight)

Very stable aluminium die-cast housing, black anodised (white on request)

Protection class: IP43 splash-proof

Impact resistance: IK05

Dimensions: L 1150mm, W 50mm, H 65 mm

On special order:

also dimmable via DALI, wireless or 1-10V,

Photosensor for automatic daylight-dependent dimming,

Light colour 3000K or 6000K

Ceiling spacer

Ball-impact grille

Chain suspension 1m or 2m

Overvoltage protection 12kV

Weight: 2,8 kg



Lighting strip LED hall lighting Lane 171cm 105W IP43



Energy-saving glare-free batten luminaire 16740 Lm for hall ceilings, sports halls, multi-purpose halls, halls and high-bay warehouses.
With dimming function.
LI-D141

Bright lighting for ceiling mounting.
This surface-mounted luminaire replaces the conventional 250W HID HQI luminaires.

Built-in LED driver and stabilisation for uniform brightness even with voltage fluctuations.
Low power consumption, no maintenance costs, very long life.
Completely ready for operation, incl. LED bulbs.
The large number of power LEDs results in better heat distribution in the luminaire and a longer service life.
With internal through-connection - The continuous row only needs to be connected electrically at one end.
A maximum of 20 luminaires can be connected in a row.

Colour rendering index: Ra 80
UGR: 16
Operating voltage 220V - 240V / 50 - 60Hz
Light emission: Symmetrical 90° (alternatively 60°)
Luminous flux: 16740 lm
Power factor 0.97
Ambient temperature: -35° C ... +45° C during operation
Total power consumption: 105W
Humidity: 10% - 90%
LED lifetime > 70000 hrs.
Colour temperature 4000 K (daylight)
Very stable aluminium die-cast housing, black anodised (white on request)
Protection class: IP43 splash-proof
Impact resistance: IK05
Dimensions: L 1710mm, W 50mm, H 65 mm

On special order:
also dimmable via DALI, wireless or 1-10V,
Photosensor for automatic daylight-dependent dimming,
Light colour 3000K or 6000K
Ceiling spacer
Ball-impact grille
Chain suspension 1m or 2m
Overvoltage protection 12kV
Weight: 4 kg

Pendant Fixtures Office and Shop



Pendant Louver Fixture Trier T5 2x 28W

Decorative office pendant luminaire with super-flat design and glare-free louvre, radiating upwards and downwards. With electronic ballast
Only a few available.
Incl. ropes for ceiling suspension.
The electronic ballast ensures flicker-free light and extended lamp life.
With glare-free aluminium louvre.
Please order 2 x bulbs T5 28W separately.

Dimensions:
Length 1220 mm, width 220mm, height only 70 mm.
LI-L1051

Accessories for indoor lights



System Vega Ceiling Suspension
LI-L1244

LED onmount lights for furnitures	
 LED Fixture T8 with diffuser 60cm 2x T8	<p>Decorative light fitting IP40 with prismatic cover. LI-L2033</p> <p>With prismatic cover - diffuses the light and makes the lamp glare-free. This is especially important at low ceiling heights, such as Counter lighting, kitchen, dressing rooms or dry cellar rooms. The brightness corresponds to about 180W incandescent light. Suitable for office, workplace, corridor, fitness center. (2 matching LED tubes T8 please order separately) Light color: 4000K natural white Voltage: 220-240V Power: 8W or 2x 8W Housing: sheet steel white Cover: PVC Protection class IP40 Length 650mm, height 66mm, width 152mm, white Weight: 2,8 kg</p>
 LED Fixture T8 with diffuser 120cm 2x T8	<p>Energy-saving LED 1200mm T8 with cover. Increased protection class IP40. LI-L2035</p>
LED Fixture T8 24V with diffuser 120cm 18W	<p>Energy-saving luminaire 24 Volt 120cm T8 with cover and electronic ballast. Increased protection class IP40. Minimum order quantity: 6 pcs. LI-L2044</p>
LED Fixture T8 24V with diffuser 120cm 36W	<p>Energy-saving luminaire 24 Volt 120cm 2x T8 with cover and electronic ballast. Increased protection class IP40. Minimum order quantity: 6 pcs. LI-L2045</p>
 LED Fixture flat with diffuser 120cm	<p>Energy-saving LED surface mounted luminaire 1200mm with cover. Increased protection class IP40. LI-L2050</p> <p>With prismatic cover - diffuses the light and makes the lamp glare-free. This is especially important at low ceiling heights, such as Counter lighting, kitchen, dressing rooms or dry cellar rooms. The brightness corresponds to about 300W incandescent light. Suitable for office, workplace, corridor, fitness center. With LEDs - non exchangeable</p> <p>Luminous flux: 3200 Lm Light color: 4000K natural white Lighting angle [°]: 120 Voltage: 220-240V Power: 32W Temperature range [°C]: -20/+40 Short connection wire 30cm on the backside Housing: Plastic white Cover: PVC Protection class: IP20 Dimensions: Length 1200mm, height 25mm, width 74mm Marking: CE Weight: 1 kg</p>
Linear LED Light Fixture Waterproof Slim 60cm IP65	<p>LED damp-proof diffuser luminaire 19W LED (replaces 2x 18W T8). For surface-mounting or suspension for indoors. LI-L2052</p>

 	<p>Fluorescent Lighting Fixture flat, with diffuser 18W T8 IP40</p>	<p>Energy-saving under-cabinet luminaire fluorescent lamp T8 with diffuser cover and electronic ballast. Protection class IP40. LI-L2070E</p> <p>Versions for 1 or 2 fluorescent tubes T8 18W. The brightness corresponds to about 90W or 180W incandescent light. With prismatic cover - scatters the light and makes the luminaire glare-free. This is particularly important with low ceiling height, e.g. Counters, kitchen, dressing rooms or dry cellar rooms. Electronic ballast EVG flicker-free and for extended lamp life. (Please order fluorescent tubes T8 separately)</p> <p>Protection class IP40 Length 622mm, height 35mm, width 120mm, Casing: Plastic, white Weight: 0,7 kg</p>
 	<p>Fluorescent Fixture T8 with diffuser 2x 36W</p>	<p>Energy-saving under-cabinet luminaire fluorescent lamp T8 with cover and electronic ballast. Increased protection class IP40. LI-L2075</p> <p>With prismatic cover - diffuses the light and makes the luminaire more glare-free. This is particularly important for low ceiling heights, such as counter lighting, kitchens, changing rooms or dry basement rooms. The brightness is equivalent to about 360W incandescent light. Sufficient for a small office or workplace. Electronic ballast EVG flicker-free and for extended lamp life. (Please order matching T8 fluorescent tubes separately). Protection class IP40 Length 1256mm, height 68mm, width 165mm Weight: 2,8 kg</p>
<p>Fluorescent Fixture T8 with diffuser 2x 58W</p>		<p>Energy-saving under-cabinet luminaire Surface-mounted luminaire T8 with diffuser and electronic ballast. Increased protection class IP40. LI-L2076</p>
 	<p>Fluorescent Fixture T5 with diffuser 14W</p>	<p>Under-cabinet luminaire 600mm fluorescent luminaire with cover and electronic ballast. Increased protection class IP44 e.g. for kitchen LI-L2081</p> <p>With prismatic cover. Applications: Areas with higher protection requirements: Hospitals, laboratories, passageways, offices. Available for 1 or 2 fluorescent tubes T5 14W. (Lamps must be ordered extra). With flicker-free electronic ballast for low energy consumption and extended lamp life. Protection class IP44 Chassis sheet steel, white. Length 630mm, height 64mm, width 173mm. Optionally: 12V, 24V supply voltage or with emergency lighting supply. Weight: 1,55 kg</p>
<p>Fluorescent Fixture T5 with diffuser 28W</p>		<p>Decorative lighting batten with plastic cover for T5 tube 28 watt. Protection IP40. LI-L2083</p>
 	<p>Flat Fluorescent Fixture T5 with diffuser 54W</p>	<p>Bright, energy-saving fluorescent luminaire with diffuser and electronic ballast. Increased protection class IP44. For kitchen, cellar, warehouse, corridor. LI-L2086</p> <p>With prismatic cover. Use: places with increased protection: hospitals, laboratories, passages, kitchens, offices. Versions for 1 or 2 fluorescent tubes T5 54W. (Please order lamps separately). With electronic ballast flicker-free and for extended lamp life. Protection class IP44 Support plate made of sheet steel, white. Length 1230mm, height 64mm, width 173mm.</p> <p>As accessory: For larger quantities 24V supply or with emergency power supply. Weight: 2,7 kg</p>

Louvre Lighting Fixtures Surface-Mount

	<p>Louvre Fixture Torino T8 2x36W</p>	<p>Glare-free ceiling louvre surface-mounted luminaire with SLA aluminium anti-glare louvre. For office and workplace LI-L2430E</p> <p>For 2 x fluorescent tube T8 36W (please order separately) Optionally: with white anti-glare louvre and magnetic ballast low-loss, or with SLA aluminium louvre and flicker-free ECG.</p> <p>Dimensions: Model Torino: L 1233mm, W 310mm, H 90mm (ECG). Model Kastor: L 1233mm, W 240mm, H 70mm (magnetic) Weight: 5,1 kg</p>
	<p>LED Louvre Light Onmount 120cm T8 120cm</p> <p>Louvre Light Monza Onmount 2x36W T8 Electronic</p>	<p>Bright ceiling louvre luminaire with LED and glare-free PAR specular louvre. For office and workplace LI-L2524</p> <p>Bright ceiling louvre luminaire for workplaces with glare-free PAR specular louvre. For office and workplace LI-L2530E</p>
	<p>Louvre Light Monza On-Mount 2x58W T8 darklight ECG</p>	<p>Bright ceiling luminaire for two T8 fluorescent tubes 58 Watt. For workshop, office, lounge, practice, warehouse, workplace. For 2 x 58W T8 fluorescent tube (Please order extra)</p> <p><u>Available with following reflectors:</u> PAR-Raster with highly polished aluminium reflector grid is optically dark, the light stays discreetly hidden and pleasant. The emitted light is ideal for computer workstations, and wherever incurred demanding visual tasks. Or aluminium reflector silver polished for standard lighting, or with white painted sheet steel reflector - the cheapest variation with wide and equal light distribution.</p> <p><u>Available with following ballast:</u> KVG (low-loss, magnetic ballast) or EVG (No flickering light and gentle start, automatic shutdown at tube defect - no lamp flashing. energy saving, improved light output and longer lamp life expectancy.)</p> <p>Operating voltage 230V 50 / 60Hz Casing sheet steel, white painted. Dimensions: L 1525mm, W 310mm, H 95mm Dieser Artikel kann nur als Sperrgut versendet werden - Der Aufpreis beträgt einmalig 17 Euro oder durch Abholung. LI-L2560E</p>
	<p>Louvre Light Monza On-Mount 2x58W T8 darklight ECG</p>	<p>Bright ceiling luminaire, glare-free, with 2x LED tube - as bright as two T8 fluorescent tubes 58 Watt. For workshop, office, lounge, practice, warehouse, workplace. Remaining stock from old inventory - still a few in stock. with white sheet steel reflector - the particularly low-priced version with good light distribution. Energy-saving LED included. Power consumption 46W Instant lamp start. Lower power consumption, improved luminous flux and much longer lamp life. Luminous flux: 2x 2200 lm Light colour 4500K white (on special order from 5 pcs. also 6000K daylight) Operating voltage 230V 50 / 60Hz Housing made of sheet steel, painted white. Dimensions: L 1525mm, W 310mm, H 95mm.</p> <p>This item can only be shipped as bulky goods - the surcharge is 17 Euro once or by collection. LI-L2560LED</p>



Louvre Light Monza On-Mount 2x58W T8 150cm

Bright ceiling luminaire with white reflector for two T8 fluorescent tubes 58 Watt. For workshop, office, lounge, practice, warehouse, workplace.
Remaining stock from old inventory - still 7 pcs. in stock.
For 2 x fluorescent tube T8 58W (please order tubes separately).

with white sheet steel reflector - the particularly low-priced version with good light distribution.
With CCG (low-loss, magnetic ballast).

Operating voltage 230V 50 / 60Hz
Sheet steel housing, painted white.
Dimensions: L 1525mm, W 310mm, H 95mm.

This item can only be shipped as bulky goods - the surcharge is 17 Euro once or by collection.
LI-L2560V



LED Louvre Light Monza On-Mount 150cm T8 darklight

Bright ceiling luminaire, glare-free, with 2x LED tube - as bright as two T8 fluorescent tubes 58 Watt.
For workshop, office, lounge, practice, warehouse, workplace.
with white sheet steel reflector - the particularly low-priced version with good light distribution.
Includes energy-saving LED - replaceable.
Immediate lamp start.
The light emitted is ideal for VDU workstations and wherever demanding visual tasks are involved.
Flicker-free and gentle lamp start.
Improved luminous flux and longer lamp life expectancy due to LED technology.

Including 2 LED tubes T8 23W longlife
Life expectancy: 26000 hrs - corresponds to about 11 years, during which you save a lot of electricity and do not need to change lamps
Luminous flux: 4400 lm
Light colour: 4500K white (on special order from 10 pcs. also 3000K warm white or 6000K daylight)
Wide beam angle: 125
Operating voltage: 85V - 230V AC
Power consumption: 46 Watt
Energy efficiency: C (A - G)
Base: T8, G13 - like standard fluorescent lamps
Approvals: TÜV, CE, EMC and RoHS, CEI EN 62776

Material: Body like louvre made of powder-coated sheet steel.
Dimensions: L 1600 mm, W 400 mm, H89 mm
Protection class: IP 20

This item can only be shipped as bulky goods - the surcharge is 17 Euro once or by collection.
LI-L2565



Surface-Mount Louvre Light T5 Monza 2x28W

Surface-mounted louvre luminaire for suspension or ceiling mounting for 2 fluorescent tubes T 5, 28 W.
For office and workplace
The highly polished louvre reflector remains optically dark, the luminaire does not dazzle unpleasantly.
The emitted light is optimal for VDU workstations and wherever demanding visual tasks are involved.
Flicker-free, electronic ballast.
Flicker-free and gentle lamp start. Shuts off if a tube is defective.
For 2 x fluorescent tube T5 28W (please order separately).
Improved luminous flux and longer lamp life expectancy due to the low-loss electronic ballast.
Light emission: direct.
Operating voltage 230V 50 / 60Hz
Decorative luminaire in white powder-coated sheet steel housing.
Dimensions: L 1225 mm, W 216 mm, H57 mm
LI-L2570

Surface-Mount Louvre Light T5 Monza 2x54W

Bright fluo louvre luminaire for suspension or ceiling mounting for 2x fluorescent tube T 5, 54 Watt.
For office and workplace
LI-L2576


<p>Surface-Mount Louvre Light T5 Beghelli 2x54W</p>	<p>Glare-free fluo louvre luminaire for hanging or ceiling mounting for office, school, workplace. For 2 tubes T5 54W LI-L2576B</p>
	<p>Louvre Light T8 Monza 4x18W Darklight electronic</p> <p>Square surface-mounted louvre luminaire with electronic ballast and glare-free reflector. For office and workplace LI-L2580E</p> <p>The wide range of optical accessories allows the luminaire to be used in any space. Material: Body and louvre made of powder-coated sheet steel. IP 20 Supplied with electronic ballast for flicker-free and flicker-free light. For 4 x fluorescent tube T8 18W (please order separately). Dimensions: 638 x 638 x 85 mm Optionally available: frame with inserted opal pane or prismatic pane. This increases the protection class to IP 40. Weight: 5,2 kg</p>
 	<p>Louvre Light Fixture Solar T5 2x 54W, darklight electronic</p> <p>Super-flat, bright T5 specular louvre luminaires for pleasant working. Electronic ballast and glare-free PAR reflector. Remaining stock LI-L2610</p> <p>The highly polished louvre reflector remains optically dark, the luminaire does not dazzle unpleasantly. The emitted light is optimal for VDU workstations and wherever demanding visual tasks are involved. Flicker-free and gentle lamp start. Shuts off if a tube is defective. Improved luminous flux and longer lamp life expectancy thanks to the low-loss electronic ballast.</p> <p>For 2 x fluorescent tube T5 54W (please order separately) Operating voltage: 230V 50 / 60Hz Flat housing: white sheet steel Dimensions: L 1220mm, W 310mm, H 60mm Weight: 6 kg</p>

Ceiling Recessed Fluorescent Lighting Fixtures

<p>Louvre Light Troffer T8 Frankfurt 4x18W, BAP dark</p>	<p>Bright T8 recessed luminaire 625x625 mm with glare-free Darklight reflector, for grid ceiling. With electronic ballast For office and workplace LI-L3019D</p>
 	<p>Recessed Troffer IMOLA 2x36W Softlight</p> <p>Glare-free louvre luminaire with soft light. For 2x36W for installation in ceilings with 600mm or 625mm panels. For direct + indirect lighting in cinema, conference room, foyer. LI-L3021WE-D</p> <p>Recessed luminaire for 2x 36 Watt fluorescent lamp TC-L / 2G11. (Please order illuminant separately). Direct and indirect light distribution, with glare shield / perforated plate. Including electronic ballast for flicker- and flicker-free light. For insertion into Odenwald ceiling 62 x 62cm (optionally grid ceiling 60 x 60cm). Material: powder-coated sheet steel, glare protection through mains grid. Protection class IP 20</p> <p>Dimensions: Model 625: 625mm x 625mm x 100 mm Model 600: 595mm x 595mm x 100 mm. Weight: 5,35 kg</p>
	<p>Louvre Fixture Milano 4x 18W aluminium electronic</p> <p>Square T8 recessed luminaire 600mm / 595 mm with glare-free aluminium reflector. Low-loss electronic ballast. Recessed luminaire for 4x T8 fluorescent tubes 18W. (Please order fluorescent tubes separately). With aluminium reflector and anti-glare grill. With flicker-free electronic ballast for longer lamp life. For insertion into hollow ceilings with 600 mm x 600mm grid dimensions. Voltage: 230V AC</p> <p>Dimensions: 595 mm x 595mm, depth 95mm. LI-L3023S</p>



**Louwer Light Fixture Mainz T5
4x14W, BAP darklight**



Louvre luminaire T5 for 625x625mm grid ceilings. Energy-saving recessed luminaire with glare-free darklight reflector.
For office and workplace
LI-L3060

Recessed luminaire for 4x T5 fluorescent tubes 14W or 24W. (Please order fluorescent tubes separately).
The luminaire requires less energy than the usual 4x 18W luminaires, has the same luminous intensity and a longer lamp life.
Glare-free PAR darklight reflector and anti-glare grill for fatigue-free work.
Flicker-free electronic ballast for longer lamp life.
With the 4x 18W version, the tubes are arranged in pairs at the edge, with the 4x 24W luminaire, the tubes are close together in the centre.
For insertion into hollow ceilings with 625 mm x 625mm grid dimensions (Odenwald ceiling).
Depth 60mm
Weight: 5,6 kg

Recessed Light Fixtures Rectangular



**Recessed Wall Washer
Fluorescent 120cm T5**



Asymmetrical batten luminaire with laterally inclined light emission for wall lighting, corridor, shop, gallery. Installation in hollow ceilings, for 1x fluorescent lamp 54W. With aluminium reflector, electronic ballast.
LI-L3110

Recessed luminaire with asymmetrical light distribution for wall illumination. Please order separately: 1 pc. T5 fluorescent tube 54W.
High-gloss aluminium reflector.
Flicker-free electronic ballast for longer lamp life.
For installation in false ceilings.
Sheet steel housing, white powder-coated.
Dimensions: 1197 mm x 150 mm, H 77 mm
Recessed cut-out: 1187 mm x 140 mm
Protection class IP20
This item can only be shipped as bulky goods - the surcharge is a one-time fee of 17 euros or by collection.
Weight: 2,5 kg

Ceiling LED Panel Modules



**Recessed LED Panel for False
Ceiling 62cm 33W**



LED panel louvre insert luminaire for Odenwald ceilings 62.5cm, super flat. Minimum order quantity: 2 pcs.
LI-L3200

LED power:	33W
Luminous flux:	3300 lumens
Light color:	4000K pure white (from 10 pcs. also available in 3000K or 5000K)
Light distribution:	Very wide 140°
Color rendering:	CRI > 80
Glare factor UGR:	< 19 very low
Service life:	> 30000 h
For extra charge:	DALI dimmable or with emergency lighting function 3h
Connection voltage:	230V AC
Power consumption:	36 watt
Power factor:	> 0.9
Acrylic diffuser cover:	matt opaque
Frame:	Aluminum white powder coated
Dimensions:	620mm x 620mm x 10mm
Protection degree:	IP20 (for indoor use only)
Minimum order quantity:	2 pcs.

Driver (dimmable or normal) please order separately.
Weight: 4,8 kg

Ceiling Recessed Fluorescent Lighting Fixtures



Recessed LED Troffer for False Ceiling 62.5cm 40W



Glare-free, energy-saving LED module recessed luminaire 625x625 mm specular louvre luminaire corresponds to T8 4x18W. Made in Europe
Minimum order quantity: 4 pieces
LI-L3201

For low-glare, directional light at workplaces.

For insertion into Odenwald louvre ceilings.

With efficient SMD power LEDs

Luminous flux: 3880 Lm

Light colour: 4500K neutral white

Light distribution wide 100

Service life > 50000 h

Not dimmable

Supply voltage 230V AC

Power consumption 40 W

Also available with matt, prismatic or clear acrylic cover for humid environments.

Reflector: polished aluminium

Housing: sheet steel, painted white

Dimensions: 615mm x 615mm x 90mm

Protection class: IP 20 (with cover IP40)

Weight: 4,8 kg

Ceiling LED Panel Modules



LED Panel Ceiling Plate 60x60 cm 3600 Lm



Highly efficient LED panel louvre recessed luminaire for suspended ceilings 60cm, shallow recess depth. Very good colour rendering.
Minimum order quantity: 4 pcs.
LI-L3202

From EU production

LED: Samsung

LED Power: 36W

Luminous flux: 3600 lumens

Light color: 4000K pure white (with larger quantities also in 3000K, 5000K or 6000K available for purchase)

Light distribution: very wide 140°

Colour rendering: Ra > 80

Uniformity: UGR > 19

Lifetime: > 50000 h

Extra: On request, dimmable DALI or emergency lighting with function 3h.

Supply voltage: 220V - 240V AC

Frequency: 50Hz - 60Hz

Power consumption: 36 Watt

Acrylic diffuser cover matt opaque

Aluminum frame white powder coated (optionally in any RAL color)

Dimensions: 595mm x 595mm x 10mm

Protection: IP20 (only for interiors)

Weight: 4,8 kg

	<p>Recessed LED Panel for False Ceiling 120 x 60cm 62W</p>	<p>LED louvre ceiling panel 62 Watt for Odenwald ceilings 600 mm Minimum order quantity: 2 pcs. LI-L3235 336 LEDs Luminous flux: 7600 lumen Light colour 4500K neutral white or 6000K cool white Light distribution 120 Colour rendering Ra > 70 Service life > 50000 h Dimmable at extra charge via remote control unit available as accessory. Supply voltage 120 - 240V AC Frequency 50 - 60Hz Power consumption: 72 Watt Dimensions 1197mm x 597mm x 12mm Protection class IP 40 (for indoor use only) Weight: 8 kg</p>
---	---	--



	<p>Round LED Panel for False Ceiling 60cm</p>	<p>Flat, round LED recessed luminaire for hollow ceilings or for suspension with cables. LI-L3250 Power consumption: 36 watt Luminous flux: 2630 Lm Light color: warm white 2700-3500K , nature white 4000K, cool white 6000-7000K LEDs: Epistar Lifetime: 50,000hrs Please order driver 45w extra (dimmable or non dimmable) Operating voltage with driver: 220-230V AC Material : PMMA+Aluminum Frame color: white Dimensions: Ø 600 x 20mm Cut-hole dimension: Ø 585mm Protection degree IP 30 (only for indoor use) MOQ 10 pcs. Weight: 4,8 kg</p>
---	--	---



Fluorescent Batten Lights

<p>Fluorescent Fitting PT T8 36W with Protecting Tube</p>	<p>Surface-mounted luminaire 1x36W for fluorescent tube T8, 36 Watt for lift shaft, workshop, machine room, garage. Discontinued item - remaining stock - can no longer be reordered. LI-L4003</p>
<p>Fluorescent Light Fitting PT T8 2x 36W with Protecting Tube</p>	<p>Surface mounted luminaire 2x36W for 2 fluorescent tubes T8, 36 Watt for lift shaft, workshop, machine room, garage. Discontinued item - remaining stock LI-L4005</p>

Linear Trunking Light Systems for Office and Hall

<p>Fluorescent Trunking Lighting Reflector 1x 58W</p>	<p>Industrial luminaire / line luminaire 150cm, T8 with energy-saving electronic ballast 1x 58 Watt for supermarket, warehouse or workshop. Remaining stock: 9 pcs. LI-L4024</p>
<p>Fluorescent Trunking Light Poker SL 2x 58W ECG</p>	<p>Industrial luminaire for trunking system T8 with low-loss electronic ballast 2x 58 W for supermarket, warehouse or workshop. LI-L4028</p>

Accessories for indoor lights

	<p>Diffusor Cover for Poker 58W LI-L402AB5</p>
	<p>Hang-Up Bracket for Poker Fluro Line LI-L402AT</p>



Mechanical Joint For Poker SL Line
LI-L402MV



S-Hook for Poker SL Line
LI-L402SV



Masking Cover For Poker SL Line
LI-L402VA

Linear Trunking Light Systems for Office and Hall



Continuous row luminaire Connect light rail T8 150cm



ECG strip lighting system for 2x 58W T8 fluorescent tubes for warehouse or workshop.

Stock: 1 piece
LI-L4030

Bayable continuous row luminaire for suspension.
Quick mounting with mechanical connectors.

No additional mounting rails are required.

Incl. 5-core through-wiring with connectors,

Load capacity max. 16 A.

Only the first luminaire, at the beginning of the continuous row, is electrically connected.

All other luminaires are simply plugged together.

With flicker-free and long-life electronic ballast for reduced power consumption.

Can be fitted with 2 x fluorescent tubes T8 58W.

Protection class IP20 (optionally IP40 with cover glass).

Housing made of white powder-coated sheet steel.

With integrated white reflector.

Dimensions: L 1540 mm,
W 130 mm,
H 80 mm

Available as accessories:

Mechanical connector, straight end cap, suspension attachment, S-hook for chain connection, chain

Weight: 3,98 kg



LED Trunking Light Line Compact 170cm IP66



LED strip light system for hanging. Brighter than a 2x 58W T8 fluorescent tube. For warehouse or large workshop.

LI-L4035

Bayable continuous row luminaire for suspension.

Quick mounting with mechanical connectors.

No additional mounting rails are required.

Incl. through-wiring with connectors, max. load 10 A.

Up to 10 luminaires can be interconnected.

Only the first luminaire, at the beginning of the continuous row, is electrically connected. All other luminaires are simply plugged together.

With flicker-free and long-life electronic driver for reduced power consumption.

Complete with light sources.

Luminous flux: 8400 Lm

Power: 60W (also 45W at 5850 Lm on order)

Protection class IP66 for damp rooms

Housing made of white powder-coated sheet steel

dimensions: L 1700 mm, W 80 mm, H 80 mm

This article can only be shipped as bulky goods - the surcharge is 17 Euro or by collection.

Weight: 3,98 kg

LED onmount lights for furnitures

LED Light Batten T5-Design Slim 60cm

LED kitchen surface-mounted luminaire with switch and cable. Can be plugged together.

LI-L4075

	<p>Light Batten Fluorescent T5 Linear Slim 6W ECG</p>	<p>Delicate, slim furniture surface-mounted luminaire with fluorescent lamp T5 6W with electronic ballast flicker-free. Remaining stock: 1 piece LI-L4080</p> <p>Lamp for mirror or furniture lighting. Protection grade IP20 With electronic ballast for flicker-free lighting. On-off switch Including fluorescent tube T5, length 212mm, Ø 16mm, 6 Watt 4000K. Voltage: 220-230V 50Hz (on request other voltages) Approvals: CE, F With pluggable connection cable 1,8m White plastic housing. Dimensions: l 270 mm, w 22 mm, h 42 mm Weight: 0,7 kg</p>
		

<p style="background-color: #0070C0; color: white; padding: 5px; text-align: center;">Fluorescent Batten Lights</p>	
<p>Fluorescent Batten Fitting T8 2x36W</p>	<p>Surface-mounted lampholder for fluorescent lamp with low-loss CCG. LI-L4106</p>
<p>LED Batten Fitting T8 120cm 1x18W (36W)</p>	<p>Surface mounted light with LED tube 120cm. Energy-saving: 18W = 36W LI-L4125</p>
<p>LED Batten Fitting T8 150cm 23W (58W)</p>	<p>Surface mounted light with LED tube 150cm. Energy-saving: 23W = 58W LI-L4127</p>
<p>LED Batten Light Aluminium Proxa 57cm</p>	<p>Rigid surface mounted industrial luminaire. LI-L42-03</p>
<p>LED Batten Light Aluminium Proxa 120cm</p>	<p>Rigid surface mounted industrial luminaire. LI-L42-05</p>

Waterproof Lighting Fixtures



**Waterproof LED Light Batten
Steel 128cm 55W IP66**



Bright damp-proof luminaire with LED instead of fluorescent tubes 2x58W T8. Diffuser luminaire for industry and production. As pendant luminaire or for ceiling mounting.
LI-L5000

Flicker-free, bright light for indoors and outdoors.

Housing made of galvanised sheet steel with caps made of plastic and lens made of tempered glass, microprismatic.

Caps and lens are firmly attached to the housing.

Light directed by segmented, parabolically shaped reflector of highly specular aluminium, deep wide beam.

Extremely resistant to mechanical and chemical stress.

Linear LED module. Electronic LED driver as SmartDriver, dimmable from 1% to 100%, with integrated interfaces for optional modules for decentralised or centralised dimming, control and monitoring.

At extra charge: explosion-proof for zone 2 (II 3G Ex nA IIB T4) and 22 (II 3D Ex tD A22 T100) with accessories.

Light colour 4000K neutral white

Luminous flux: 5200 Lm

UGR: < 25

This luminaire is not dimmable.

Supply voltage: 220-230V 50Hz (from 50 units also available in other voltages)

Total power consumption: 55 Watt

Power factor: 0.96

Lifetime: 60000 hours

The ballast unit is built into the luminaire.

Cable connection 3x 1,5² via brass gland

Housing made of galvanised sheet steel, grey powder-coated RAL7035

Cover caps polycarbonate grey

Protective screen of tempered glass with silicone seals.

Ambient temperature: -20°C to +40°C

Luminaire dust-tight and jet-water protected to IP66.

High impact resistance IK 09

Length: 1280 mm, width: 170 mm, height: 89 mm

Energy class: C

This item can only be shipped as bulky goods - the surcharge is 17 euros once or by collection.

Weight: 5,1 kg



**Waterproof LED Light Batten
Steel dimmable 58W IP66**



Bright sheet steel moisture-proof luminaire with LED instead of fluorescent tubes 2x58W T8. For industry and production. As pendant luminaire or for ceiling mounting.
LI-L5001-3

Flicker-free, bright light for indoors and outdoors.
Housing made of galvanised sheet steel with caps made of plastic and lens made of tempered glass, microprismatic.
Caps and lens are firmly attached to the housing.
Light directed by segmented, parabolically shaped reflector of highly specular aluminium, deep wide beam.
Extremely resistant to mechanical and chemical stress.
Linear LED module. Electronic LED driver as SmartDriver, dimmable from 1% to 100%, with integrated interfaces for optional modules for decentralised or centralised dimming, control and monitoring.
At extra charge: explosion-proof for zone 2 (II 3G Ex nA IIB T4) and 22 (II 3D Ex tD A22 T100) with accessories.
Light colour 4000K neutral white
Luminous flux 4000 Lm
UGR: < 25
Dimmable 1% - 100% with suitable control unit
Optionally for 1-10V control or for DALI
Connection voltage: 93V - 265V AC
or for battery supply: 176V - 276V
Total power consumption: 55 Watt
Power factor: 0.96
Lifetime: 60000 hours
The ballast unit is built into the luminaire.
Cable connection 3x 1,5² via brass gland
Housing made of galvanised sheet steel, grey powder-coated RAL7035
Cover caps polycarbonate grey
Protective screen of tempered glass with silicone seals.
Ambient temperature: -20°C to +40°C
Luminaire dust-tight and jet-water protected to IP66.
High impact resistance IK 09
Length: 1280 mm, width: 170 mm, height: 89 mm
Energy class: C

This item can only be shipped as bulky goods - the surcharge is 17 euros once or by collection.
Weight: 5,1 kg



Waterproof LED Light Batten Steel EX 58W IP66



Bright LED sheet steel damp-proof luminaire with Ex II protection. For industry and production. As pendant luminaire or for ceiling mounting.
LI-L5002-3

Flicker-free, bright light for indoors and outdoors.
Housing made of galvanised sheet steel with caps made of plastic and lens made of tempered glass, microprismatic.
Caps and lens are firmly attached to the housing.
Light directed by segmented, parabolically shaped reflector of highly specular aluminium, deep wide beam.
Extremely resistant to mechanical and chemical stress.
Linear LED module. Electronic LED driver as SmartDriver, dimmable from 1% to 100%, with integrated interfaces for optional modules for decentralised or centralised dimming, control and monitoring.
At extra charge: explosion-proof for zone 2 (II 3G Ex nA IIB T4) and 22 (II 3D Ex tD A22 T100) with accessories.

Light colour 4000K neutral white

Luminous flux 4000 Lm

UGR: < 25

Dimmable at extra charge.

Supply voltage: 93V - 265V AC

or for battery supply: 176V - 276V

Total power consumption: 55 Watt

Power factor: 0.96

Lifetime: 60000 hrs.

The ballast unit is built into the luminaire.

Cable connection 3x 1,5² via brass gland

Housing made of galvanised sheet steel, grey powder-coated RAL7035

Cover caps polycarbonate grey

Protective pane of tempered glass with silicone seals.

Ambient temperature: -20°C to +40°C

Luminaire dust-tight and jet-water protected to IP66.

High impact resistance IK 09

Length: 1280 mm, width: 170 mm, height: 89 mm

Energy class: C

This item can only be shipped as bulky goods - the surcharge is 17 euros once or by collection.

Weight: 5,1 kg



Waterproof LED Light Batten Stainless Steel 125cm IP66 60 Celsius



Bright sheet steel LED damp-proof luminaire for high ambient temperatures. For industry and production. As pendant luminaire or for ceiling mounting.
LI-L5003-4

Flicker-free, bright light for indoors and outdoors.
Housing made of galvanised sheet steel with caps made of plastic and lens made of tempered glass, microprismatic.
Caps and lens are firmly attached to the housing.
Light directed by segmented, parabolically shaped reflector of highly specular aluminium, deep wide beam.
Extremely resistant to mechanical and chemical stress.

Linear LED module. Electronic LED driver.

Light colour 4000K neutral white

Luminous flux 4800 Lm

UGR: < 25

This luminaire is not dimmable.

Supply voltage: 220-230V 50Hz (from 50 units also available in other voltages)

Total power consumption: 40 Watt

Power factor: 0.96

Lifetime: 60000 hours

The ballast unit is built into the luminaire.

Cable connection 3x 1,5² via brass gland

Housing made of galvanised sheet steel, grey powder-coated RAL7035

Cover caps polycarbonate grey

Protective screen of tempered glass with silicone seals.

Ambient temperature: -20°C to +60°C

Luminaire dust-tight and jet-water protected to IP66.

High impact resistance IK 09

Length: 1250 mm, width: 170 mm, height: 89 mm

Energy class: B

This item can only be shipped as bulky goods - the surcharge is 17 euros once or by collection.

Weight: 5,1 kg

 <p>Waterproof Fluorescent Light Fixture Single 18W IP65</p> 		<p>Damp-proof luminaire made in EU with electronic ballast or electronic ballast for 1x18W fluorescent tube T8, high protection class IP65. LI-L5011-1</p> <p>Housing and cover made of impact-resistant polycarbonate for wall or ceiling wall or ceiling surface mounting or for pendant mounting. Impact-resistant, vandal-proof, resistant to dilute acids, many oils and greases, as well as ethanol, but to ethanol, but not resistant to bases, aromatic and halogenated hydrocarbons, as well as ketones and esters. Suitable for underground car parks, kitchens, bakeries, indoor areas.</p> <p>Temperature range: -20°C to + 50C°. Lamp dust-tight and jet-proof to IP65. Quick-release clips for easy lamp replacement. Suitable for through-wiring Suitable for 1x tube T8 18W 60cm length. Please order the fluorescent tube separately. Built-in, low-loss ballast with reactive current compensation + starter Or energy-saving electronic ballast for longer lamp life. Dimensions: L 660 mm, W 100 mm, H 106 mm Weight: 1,7 kg</p>
	<p>Fluorescent Light Fixture Waterproof 58W Twin IP65</p>	<p>Damp-proof luminaire made in EU with electronic ballast or electronic ballast for 2 fluorescent tubes T8 58 Watt, high protection class IP65. LI-L5015-2</p>
 <p>Waterproof Fluorescent Light Fixture T5 14W IP65</p> 		<p>Damp-proof fluorescent luminaire 60cm with electronic ballast for 1x 14W or 2x 14W fluorescent tube T5, high protection class. LI-L5031</p> <p>Housing and cover made of impact-resistant polycarbonate for wall or ceiling surface mounting or for pendant mounting. Impact-resistant, vandal-proof, resistant to dilute acids, many oils and fats as well as ethanol, but unresistant to bases, aromatic and halogenated hydrocarbons as well as ketones and esters. Suitable for underground car parks, kitchens, bakeries, indoor areas. Temperature range: -20°C to + 50C°. Luminaire dust-tight and jet-proof to IP65. Quick-release clips for easy lamp replacement. Built-in electronic ballast for very long lamp life and reduced power consumption. Single or double flame, suitable for fluorescent tubes T5 14W, 549 mm length. Please order fluorescent tubes separately. Operating voltage 230V 50Hz Dimensions: L 658 mm, W 115 mm, H 115 mm. Optionally with emergency light function. Weight: 1,45 kg</p>
	<p>Waterproof Fluorescent Light Fixture T5 28W ECG IP65</p> <p>Waterproof Fluorescent Light Fitting T5 49W IP65</p> <p>Fluorescent Light Fixture Waterproof T5 54W IP65</p>	<p>Damp-proof fluorescent luminaire 120cm with electronic ballast for 1x28W or 2x28W fluorescent tube T5, high protection class IP65. LI-L5033</p> <p>Damp-proof fluorescent luminaire 150cm with electronic ballast for 1x49W or 2x49W fluorescent tube T5, high protection class IP65. LI-L5034</p> <p>Damp-proof fluorescent luminaire 120cm with electronic ballast for 1x54W or 2x54W fluorescent tube T5, high protection class IP65. LI-L5037</p>

	<p>Waterproof Batten Light Fixture 60cm IP65</p> 	<p>LED moisture-proof diffuser luminaire 10W LED (replaces 1x 18W T8). For surface-mounting or suspension for indoors or outdoors, high protection class. LI-L5049-1</p> <p>Housing and cover of impact-resistant polycarbonate for wall or ceiling surface-mounting or for pendant mounting.</p> <p>Impact-resistant, vandal-proof, resistant to dilute acids, many oils and greases as well as ethanol, but ethanol, but not resistant to alkalis, aromatic and halogenated hydrocarbons hydrocarbons as well as ketones and esters.</p> <p>Suitable for underground car parks, kitchens, bakeries, indoor areas.</p> <p>Power consumption: 10W Voltage: 180 - 240V 50Hz (as special version 12V DC) Luminous flux: 970 lm Light colour: 4500K white Temperature range: -20°C to + 50°C. Lamp dustproof and jet-proof according to IP65. Quick-release clips for easy lamp replacement. Suitable for through-wiring Includes 1x LED tube replaceable. Dimensions: L 670 mm, W 60 mm, H 62 mm Weight: 1,7 kg</p>
	<p>Linear LED Light Fixture Waterproof IP65 120cm 18W</p> <p>Linear LED Light Fixture Waterproof IP65 1200mm</p> <p>Linear LED Light Fixture Waterproof IP65 1500 22W</p> <p>Linear LED Light Fixture Waterproof IP65 1500 2x22W</p>	<p>Tri-proof LED Fitting 1200mm for on-mount or suspending. 18W LED replace single 36W fluorescent. With polycarbonate diffuser IP65 rating. LI-L5050-1</p> <p>Tri-proof LED Fitting for on-mount or suspending. 36W LED replace 2x 36W fluorescent. With polycarbonate diffuser IP65 rating. LI-L5050-2</p> <p>LED damp-proof diffuser luminaire (replaces 1x 58W T8). For surface mounting or suspension for indoor or outdoor use, high protection class. LI-L5053</p> <p>LED damp-proof diffuser luminaire (replaces 2x58W T8). For surface mounting or suspension for indoor or outdoor use, high protection class. LI-L5053-2</p>
	<p>Waterproof Batten Light Fixture 12V-24V 60cm IP65</p> 	<p>LED damp-proof diffuser luminaire 10W LED (replaces 1x 18W T8) for 12-24 Volt DC battery voltage. For swimming pool, industry, manufacturing, ship, railway or vehicle. High protection class, also for dusty or damp environments. LI-L5054-1</p> <p>Housing and cover of impact-resistant polycarbonate for wall or ceiling surface-mounting or for pendant mounting.</p> <p>Impact-resistant, vandal-proof, resistant to dilute acids, many oils and greases as well as ethanol, but ethanol, but not resistant to bases, aromatic and halogenated hydrocarbons hydrocarbons as well as ketones and esters.</p> <p>Suitable for underground car parks, kitchens, bakeries, indoor areas.</p> <p>Average life: 30000 h Power consumption: 10W Operating voltage: 12V and 24V DC (10V - 28V) - not for mains voltage ! Luminous flux: 1000 lm Light colour: 4000K natural white Temperature range: -20°C to + 40°C Lamp dustproof and jet-proof according to IP65. Quick-release clips for easy lamp replacement. Suitable for through-wiring Includes 1x LED tube replaceable. Dimensions: L 670 mm, W 60 mm, H 62 mm Weight: 1,7 kg</p>
	<p>Triproof LED Light Fixture 12V-24V IP65 120cm 18W</p>	<p>LED damp-proof diffuser luminaire 18W LED (replaces 1x 36W T8) for 12-24 Volt DC battery voltage. For swimming pool, industry, manufacturing, ship, railway or vehicle. High protection class, also for dusty or damp environments. LI-L5055-1</p>

<p>Triproof LED Light Fixture 12V-24V IP65 120cm 2x18W</p>	<p>LED damp-proof diffuser luminaire 36W (replaces 2x36W T8) for 12-24 volts DC battery voltage. For swimming pool, industry, manufacturing, ship, railway or vehicle. High protection class, also for dusty or damp environments. LI-L5055-2</p>
<p>LED Tri Proof Light Fixture IP65 120cm Heat</p>	<p>LED damp-proof diffuser luminaire 24W LED (replaces 1x 36W T8). For surface-mounting or suspension for indoors or outdoors, for high ambient temperature. LI-L5060</p>
<p>LED Tri Proof Light Fixture 24V DC IP65 120cm Heat</p>	<p>waterproof LED Fitting 1200mm for high ambient temperatures. 24W LED replace single 36W fluorescent. With polycarbonate diffuser IP65 rating. LI-L5060-24</p>
<p>LED Tri Proof Light Fixture 48V DC 120cm longlife IP65</p>	<p>LED damp-proof luminaire 48 Volt LED (replaces T8). LI-L5060-48</p>
<p>LED Tri Proof Light Fixture 24VDC IP66 120cm longlife</p>	<p>LED damp-proof diffuser luminaire 26W LED (comparable with a 2x 36W T8 luminaire). For operation on 12V - 24V battery voltage. Particularly long-lasting. Also for higher ambient temperatures, as industry, mining, machine rooms. LI-L5060T24</p>
<p>LED Tri Proof Light Fixture IP66 120cm longlife</p>	<p>LED damp-proof diffuser luminaire 25W LED (comparable with a 2x 36W T8 luminaire). Particularly long-lasting. LI-L5060T90</p>
<p>LED Tri Proof Light IP65 120cm Heat</p>	<p>LED damp-proof diffuser luminaire 66W LED (replaces 2x 58W T8). For surface-mounting or suspension for indoors or outdoors, for high ambient temperature. LI-L5061-6</p>
<p>LED Tri Proof Light Fixture IP65 60cm longlife</p>	<p>LED damp-proof diffuser luminaire 20W LED (comparable with a 2x 18W T8 luminaire). Particularly long-lasting. LI-L5063T20</p>
<p>Linear LED Light Fixture Waterproof Slim 120cm IP65</p>	<p>LED damp-proof diffuser luminaire 36W LED (replaces 1x 58W T8). For surface-mounting or suspension for indoors or outdoors. LI-L5085</p>
<p>Linear LED Light Fixture 60cm Strong 20W Waterproof IP66 Outdoor</p>	<p>LED damp-proof diffuser luminaire 60cm, impact-resistant IK08 LI-L5093-1</p>
<p>Tri Proof LED Light Fixture 48W Strong IP65 Outdoor</p>	<p>LED damp-proof diffuser luminaire 120cm, waterproof , impact-resistant IK08 LI-L5093-3</p>
<p>Linear LED Light Fixture 150cm 59W Strong Waterproof IP65 Outdoor</p>	<p>LED damp-proof luminaire 150cm, impact-resistant IK08 LI-L5095</p>

	EX-protected diffuser luminaire EX-II Luminaire 36W T8	Explosion-proof damp-proof luminaire IP65 for fluorescent lamp T8. EX Zone 2. LI-L5114
		For areas with dust, such as bakeries, carpentry workshops, cement works, mills and for areas with gases and vapours, such as refineries, paint shops, petrol stations, etc. Housing and cover made of impact-resistant polycarbonate for wall or ceiling surface mounting or pendant mounting. Quick-release clips for easy lamp replacement.
		Suitable for tube T8 36W G13 with 120cm length. Available: Only 2-lamp version. Please order fluorescent tubes separately.
		Flicker-free, electronic ballast EVG Dust-tight and splash-proof according to IP65. Explosion protection according to EN 50 021 and EN 50 281 Approved for gas and dust, for zone 2 (normal safety), 21(high safety dust) and 22 (normal safety dust). Dimensions: L 1270 mm, W 100 mm, H 106 mm.
		This item can only be shipped as bulky goods - The surcharge is 17 Euro once or by collection. Weight: 3,2 kg
	EX Proof Lighting Fixture 58W T8 IP65	Explosion-proof luminaire / damp-proof luminaire for fluorescent lamp 1x or 2x58W T8. EX Zone 2. Availability: We only have a few items in stock. Attention - there are different versions at different prices. If reordering is necessary, this can only be done for quantities of 10 or more quantity. Please contact us for availability or send us a "request" via the shopping cart. LI-L5115
	Tri-Proof LED Light Fixture 150cm 72W IP66 Emergency	Damp-proof diffuser luminaire with emergency lighting function. Made in EU with driver and LED, high protection class. LI-L5211N
	Tri-Proof LED Light Fixture 150cm 72W IP66 Emergency	PMMA damp-proof diffuser luminaire with emergency lighting function. Made in EU with driver and LED, high protection class. LI-L5213
	Industrial luminaire LED diffuser luminaire 150cm IP66 Emergency lighting	Damp-proof diffuser luminaire made of PMMA with high chemical resistance. With emergency lighting function. Made in EU with driver and LED, high protection class. LI-L5213N
	Linear LED Light Fixture Watertight IP69K Outdoor	LED damp-proof industrial luminaire 60cm impact-resistant IK10 for flooding, car wash etc. Minimum order quantity: 10 pcs. LI-L5302
	LED Tube Light Fixture 24VDC 120cm IP65	LED industrial luminaire 1200mm 24 volt with long connecting cable for industry, car, boat or truck battery etc. Minimum order quantity: 2 pcs. LI-L5308

Lighting Tracks 3 Circuit Model D

	3 Phase Track Adapter	For connecting spotlights to 3-phase track Erco, Global, Eutrac, SLV, Staff. LI-SCH01
---	------------------------------	--

Accessories for indoor lights

	Thread for 3 phase adaptor + nut LI-SCH02
---	--

Lighting Tracks ASS and other manufacturers

	3 Phase Track Adapter incl. assembling	Conversion of a luminaire to universal adapter incl. material and working time. LI-SCH03
--	--	--

Lighting Tracks 3 Circuit Model D

	Fix-Point for ceiling-mount of 3-phase lights	Fix-Point rosette for direct ceiling mounting of luminaires with 3-phase adapter, without track. LI-SCH09-S
--	---	---

Lighting Tracks ASS and other manufacturers

	Schuko Socket for 3 phase lighting track 6.3A	GLOBAL, with 3-phase adapter and fine-wire fuse 6.3A Fits on 3-phase tracks from Nokia, Erco, Staff, Eutrac, Global, Lival and ASS. Max. power: 1400 watt / 230 volt LI-SCH42
	3-phase track ASS 2m long silver - exhibit	Power rail 3-phase, 2 metres. Very good condition - hardly any visible signs of use. LI-SCHA06R
	3-circuit track ASS 3m silver - exhibit	Rail 3-phase, 3 metres. Very good condition - hardly any visible signs of use. LI-SCHA07R
		Steel Line for pendant tracks LI-SCHA30

Lighting Tracks 3 Circuit Model D

	3 Phase Lighting Track D 1m	Light track 3-phase, angular design, 1 metre. Available in black, white or silver. LI-SCHD05
		For horizontal mounting. Lights can be plugged with a 3-phase adapter manufacturer of all commercially available. With the right supply up to 3 circuits can be connected to 230 volts. The lamps can be arbitrarily into 3 groups on and switched off. With optional dimming the light can be controlled (only with dimmable lights). Material: aluminum with copper conductors. Power: 230 volts, 3 x 16 Amp Weight: 1,2 kg
	3 Phase Lighting Track D 2m	3 circuit track 16 amp, available in black, white or silver. LI-SCHD06
	3 Phase Lighting Track D 3m	3 phase track, angular design, 3 metres. Available in black, white or silvergrey. LI-SCHD07
		Live End for D-Track 3 phase left LI-SCHD11
		Live End for D-Track 3 phase right LI-SCHD12

-  Straight Connector for D Track 3 phase
LI-SCHD13
-  Flexible Connector for D Track 3 phase
LI-SCHD14
-  End Cap for D-Track 3
LI-SCHD15
-  T-Connector left D-Track 3 phase
LI-SCHD16
-  T-Connector right D-Track 3 phase
LI-SCHD17
-  Feed-in Connector for D-Track 3 phase
LI-SCHD18
-  Corner Connector D-Track 3 Inner Side
LI-SCHD19
-  Corner Connector D-Track 3 Outside
LI-SCHD20
-  Cross Connector for D-Track 3 + Electr.
LI-SCHD21
-  Anchor for 3-Phase Track
LI-SCHD35

Lighting Tracks ASS and other manufacturers

	3-Phase Track Eutrac 2m, White	Eutrac track 3-phase, light track 2 metres long Only a few available. LI-SCHE06W Power track for 3 lighting circuits. Can be used with all commercially available track spotlights. Weight: 2,1 kg
	Global 3 Phase Track Feed-In right, black	Electrical connection for Global 3 phase rail. LI-SCHG11-S
	Current Track 3 Coupler Global black	Electrical connection for Global 3 phase rail. LI-SCHG13S
	Current Track 3 Coupler Global white	Connector for Global 3 phase rail. LI-SCHG13W
	Global Track End Cover black	End cap for Global 3 phase rail. XTS 41-2 Manufacturer: Nordic Aluminium LI-SCHG15-S
	Global Track 3 T-Coupler Right Black	T-connector for Global 3 phase track. LI-SCHG17S