

Globe Post Lights

		<p>Pole Light Globe Norm</p> <p>Decorative and blindfree post top lantern in different heights.</p>	<p>Globe in acrylic UV stabilized with 400 mm diameter. The globe is available in transparent or top black mirrored. (At higher quantities optionally polycarbonate or 250 or 300mm or opal or smoked finish available.) E27 porcelain lamp holder. For incandescent lamps up to 100W and for self-ballasted compact fluorescent lamps. For pole mount 60mm diameter. (Please order lamp and pole extra) Protection class IP44, insulation class II Please see also our LT-2000 Park Reflex for higher light outputs with discharge lamps or the LED model. LT-2001</p>
	<p>Pole Light LED Globe</p>	<p>Decorative post top lantern in different heights. LT-2001L</p>	

Straight Steel Poles

	<p>Lantern Light Post Aluminium Lightweight 3m LT-2004</p>
---	--

Round Street Lamps Lanterns



LED Urban Park Light Lantern Sylt 32W



Round, decorative, energy-saving LED pole luminaire for car parks, pedestrian zones, marketplaces, parks. As bright as 300W halogen light. LT-2110-3

Economical and decorative LED street light and post luminaire. Luminaire made of cast aluminium
 UV-stabilised acrylic glass, transparent (polycarbonate on request). Glare protection according to the relevant standards against light pollution of the night sky.
 Power SMD LED bulb 30W included.
 LED mushroom luminaires do not emit UV light and therefore hardly attract insects. The luminaire stays clean and free of cobwebs for longer.
 The LED mushroom lamps are almost maintenance-free, have a very long service life and require only a quarter of the electricity of conventional mercury vapour lamps.
 The light is pleasantly warm, illuminates evenly and does not glare into the surrounding windows.
 Dimmable at extra cost: 1-10V (10% to 100% light output via extra control lead) or time-controlled automatic dimming.

For pole mounting on 60 - 76mm poles.
 Recommended mast height 3-5 m
 Please order a suitable pole separately.

Luminous flux 4000 Lm
 Light colour 4000K neutral white (from 10 pcs. also 3000K warm white)
 Light distribution: 360 degrees all around
 Particularly economical - high efficiency lamp -
 The brightness is comparable with 125W HQL mercury vapour lamp or a 70W sodium vapour lamp.
 Service life: > 100000 hrs.
 LED supply unit included.
 Operating voltage 230V (85 ... 265V AC) 50 / 60Hz
 Power consumption: 32 Watt
 Built-in power stabilisation that ensures constant luminous intensity even with fluctuating mains voltage.
 Protection class: IP65
 Protection class II
 Permissible ambient temperature: -40°C ... +50°C
 Colour: RAL 7021 anthracite (alternatively in RAL 7005 grey).
 Dimensions: Diameter 481mm, height 418mm
 Wind load: 0.023 m²
 Weight: 7,63 kg



LED Urban Park Light Lantern Sylt 80W

Round, decorative, energy-saving LED post luminaire with 10000 lumens. For car parks, pedestrian zone, market place, park. As bright as 1000W halogen light. LT-2110-8

Decorative Pole Lights for pedestrian precincts



LED Street Pole Light Unique Lantern



Decorative LED post-top luminaire - Made in Germany. For service roads, paths, parks or as a replacement for mushroom luminaires. LT-9300

Very rigid and worthy construction. Timeless design that fits into the old town, as well as in modern pedestrian zones, parks and footpaths. Use: Riding lane lighting, footpath, park, driveway, pedestrian precinct, bicycle path, etc. Without any pollution, Unique lights are energy saving and environmental protective, and they are very suitable to illuminate streets, schools, parks, villas, courtyards, gardens, and so on. Hand welded, corrosion-protected with two-component primer and scratch resistant, provide multi-component truck paint. With durable acrylic glass.

The light distribution is 360 degree round, to all directions.
 Enlighted area aprx. 15m - 25m Ø
 Feeds the light slightly downwards and protects against blinding.
 With high efficient power LED 15W or 20W
 Light output 950 / 2000 Lumen - as bright as 50W / 125W HQL HPL mercury
 Light colour 3500K warm white
 Functions well under low temperature - 25° ... + 60° C.
 Maintenance-free - Lifetime of the lamp aprx. 10 years.
 Easily exchange of the LED light.
 Operating voltage 200V - 240V 50 / 60Hz
 Protection IP44, class II
 Dimensions: Tiefe 300mm, Breite 450mm, Höhe 400mm
 For poles with 60mm top diameter.
 The steel pole 3, 4 or 5 meter height has to be ordered extra.
 12 years spareparts availability.
 Weight: 5 kg



LED Street Pole Light Old Style Lantern 3m



Decorative and bright 30W LED post luminaire for street lighting for residential streets, pedestrian zones, parks or as a replacement for mushroom luminaires. LT-9302

Very rigid and worthy construction. Timeless design that fits into the old town, as well as in modern pedestrian zones, parks and footpaths. Use: Riding lane lighting, footpath, park, driveway, pedestrian precinct, bicycle path, etc. Without any pollution, energy saving and environmental protective, and they are very suitable to illuminate streets, schools, parks, villas, courtyards, gardens, and so on. Corrosion-protected with two-component primer and scratch resistant, provide multi-component paint truck. The light distribution is 360 degree round, to all directions. Lighted area aprx. 25m - 30m Ø The LED optics feeds the light slightly downwards and protects against blinding. With high efficient power LED 30W
 Light output: 3000 Lumen - as bright as 70W sodium / 80W HQL HPL mercury
 Light colour 4000K nature white
 Wide ambient temperature range: - 20°C ... + 40°C
 Maintenance-free - Lifetime of the lamp aprx. 10 years.
 Operating voltage 200V - 240V 50 / 60Hz
 Power factor: > 0,95
 Protection IP65, class II
 Shock proof: IK08
 Wind load surface: 0,37m²
 Dimensions: Width 420mm, depth 420mm, height 800mm
 For poles with 60mm top diameter.
 The steel pole 4, 5 or 6 meters height has to be ordered extra.
 Minimum ordering quantity 2 pcs. Preparing time aprx. 3 weeks
 Weight: 7,5 kg



**LED Street Pole Light Old Style
Lantern 40W**



Decorative and bright 40W LED post-top luminaire for street lighting for residential streets, pedestrian zones, parks or as a replacement for mushroom luminaires. LT-9304

High-quality and stable luminaire made of aluminium. Classic design that blends into the old town as well as modern residential streets, footpaths, cycle path lighting, park, cycle path etc. Top-mounted luminaire without UV radiation - hardly any insects are attracted. No upward light emission - to protect the night sky.

- Light distribution: radial 360° in all directions.
- Beam width 120°.
- Light range Ø approx. 25 - 30m
- Thanks to the lens optics, the light is better directed, glare-free and more evenly distributed.
- LED power 40W and highest energy efficiency.
- Luminous intensity: 4800 lumen - corresponds to approx. 70W sodium vapour or 100W HQL HPL lamps
- Light colour: 4000K natural white or 3000K warm white
- Ambient temperature range: - 20°C ... + 40°C
- Maintenance-free - service life of the LED lamp approx. 12 years.
- Operating voltage: 200V - 240V 50 / 60Hz
- Power factor: > 0.95
- Protection class IP65, class II
- Impact resistance: IK08
- Wind area: 0.37m²
- Dimensions: Depth 440mm, Width 440mm, Height 766mm

Please order steel mast separately. We recommend a height of 4m - 6m with a spigot dimension of Ø 60mm.
Weight: 7,5 kg

Classic Lighting Posts for Gardens and Pedestrian Precinct



**Post Light
Candelabra
Trumpet LED 2
Flames 250cm**

Versatile, classic pole lantern with two lights. For lighting gardens, parks, old town and much more.

- Pole height 2.50m
- For energy-saving lamp E27 or LED.
- Please order bulbs separately.
- Pole: 250 cm
- Material: die-cast aluminium
- Lamp head made of aluminium
- Diffuser made of glass
- Available colours: white, black, black/copper.
- Protection class: IP43
- LT-9331

Decorative Pole Lights for pedestrian precincts



LED Park Light Pole 4m Moritz P



Decorative lantern pole light with LED lamp and 4 metres pole for park, paths or grounds. German manufacture.
Minimum order quantity: 2 pieces
LT-9338-4

Bell light - elegant in design and reliable in operation - low power consumption.
Usage: Cycle path lighting, footpaths, car park, driveway, pedestrian area, cycle lanes etc.
Environmentally friendly.
The brightness is equivalent to a 150W halogen lamp

General technical data:
Illuminated area: All-round optics approx. 6 x 6m
or with street light optics (following the course of the path)
18 x 4m
Recommended mast spacing: Approx. 6 - 19 metres
Ambient temperature: -20°C ~ +50°C (extension -35°C ~ +65°C possible on request)
Material: Brackets: Hot-dip galvanised steel (UV-resistant paint available at extra cost). Screws: VA stainless steel.
Energy efficiency class: B
Marks of conformity: CE, RoHS, WEEE
20-year availability guarantee for spare parts.

Luminaire head specification:
Robust LED luminaire head made of die-cast aluminium
LED lamp: SMD chipset Osram
LED power: 18W
Light colour: 4000K neutral white (also available in 3000K warm white)
No UV radiation for reduced insect attraction
LED efficiency: > 160 lm/w
Luminaire efficiency: > 142 lm/w
Luminous flux lumen: 2500 lm
Central illuminance: > 22 Lux (4m height)
Average luminous intensity: > 12 Lux (4m)
LED life: approx. 50,000 hours
Protection class: IP66 (water and storm protected)
Impact resistance: IK10
Warranty: 5 years

Steel pole
Steel pole, hot-dip galvanised
(additionally scratch-resistant powder-coated at an extra charge).
Visible height: 4 m
Pigtail Ø: 60mm galvanised
Ground section: 60 cm for setting in concrete (on request also 3m - 8m height)
For easier erection, we also offer installation sleeves into which the mast can be inserted.
Lockable mast door, for easy access to the connection area.

Operating conditions:
Ambient temperature: -25°C ~ +45°C deg
Weight: 62 kg



LED Park Light Pole 5m Moritz P

Decorative lantern pole light with LED lamp and 5 metre pole for park, paths or grounds. German manufacture.
Minimum order quantity: 2 pieces
LT-9338-5