











Low Bay Fixtures 20 - 35cm



	<p>Pendant Light 32cm PC E27</p>	<p>With acrylic reflector. For lamp max. 100 watt. LP-12PC-AC</p>
		<p>Lamp shade 320 mm, transparent structurized polycarbonate. Hanging light with ceiling cap made of silver PVC plastic. Adjustable height max. 220 cm. Light distribution: 94° To use with E27 lamp max. 100 watt. Protection degree IP20 Weight: 0,9 kg</p>
	<p>Pendant LED Light 32cm PC</p>	<p>With acrylic reflector and LED. As bright as 200 watt incandescent lamp. LP-12PC-AL</p>
		<p>Lamp shade 320 mm, transparent structurized polycarbonate. Hanging light with ceiling cap made of silver PVC plastic. Adjustable height max. 220 cm. Light distribution: 94° Including LED lamp E27 Light colour: 4000K nature white Luminous flux: 2020 Lm Voltage: 230V Power: 20W Protection degree IP20 Weight: 0,9 kg</p>
	<p>Pendant Light Reflector 32cm, MH E27 150W, PC</p>	<p>Energy saving, with polycarbonate reflector. 150 W metal halide = as bright as 550 w halogen light. LP-12PC-B-H1</p>
		<p>Lampshade 320 mm, light-transparent. Integrated ballast for metal halide lamp 150W E27. Since the screen is open at the bottom, bulbs must be used with splinter protection (sold separately) Gray with 165cm cable and ceiling canopy. Weight: 4,5 kg</p>
	<p>Acrylic Low Bay Fixture 310mm E27</p>	<p>LP-12PC-C</p>
		<p>Available without cover plate. Suitable for illuminant E27 Max. Power 150W Screen Diameter: 315mm Overall height: 360mm Top made of aluminum: height 168mm Weight: 2,3 kg</p>
	<p>Acrylic Low Bay Fixture 300mm E27</p>	<p>LP-12PC-LED</p>
		<p>Diameter: 315mm Height: 360mm Power 9W (comparable to 90W incandescent lamp) Dimmable with LED dimmer or phase section dimmer suitable for 9W power. Weight: 2,3 kg</p>

Accessories for indoor lights







Acrylic Diffusor Glass for pendant light 32 cm
LP-12Z-01

Low-Bay Fixtures

	<p>LED High Bay Light Mini UFO 100W</p> <p>LED High Bay Light Mini UFO 150W</p>	<p>Waterproof aluminium pendant reflector lamp. 100W LED = 800 watt halogen light. Energy economizing. LP-25-10</p> <p>Waterproof aluminium pendant reflector lamp. 150W LED = 1200 watt halogen light. Energy economizing. LP-25-15</p>
	<p>Pendant light 40cm PC MH 70W</p> 	<p>Polycarbonate + metal case. Energy saving, 70 w metal halide HQI = as bright as 280 w halogen light. LP-40PC-07M</p> <p>Prismatic polycarbonate shade 410mm, light-transparent with protection glass. Height 500mm. Low loss ballast and starter. Suitable for lamp HQI 70 Watt G12. With steel suspension cable 150cm IP20. Weight: 17 kg</p>
	<p>High Bay Lighting 40cm PC 2x 42W FL</p>	<p>Polycarbonate + metal case. Energy saving, for 2 x compact fluorescent lamp TC-TEL 42W. LP-40PC-42F</p>

High-Bay Light Fixtures

	<p>Pendant Light 41cm Alu 150W MH</p> 	<p>High-Bay fixture with aluminium reflector 410mm. For metal halide lamp 150 watt. LP-41A-M15</p> <p>Professional version with high light output. Aluminium reflector 410mm, outside silver, inside polished. Light distribution very wide. Lumen intensity: 13,500 lm Incl. ballast, starter + capacitor for HID lamp HQI 150W E27. The lamp has to be ordered extra. This lighting fixture is not dimmable. Starting after 30 seconds warm-up time. Very rigid aluminium die-cast body with wiring box and cable glands for connection of free cable length. With lifting eye for hanging up or for static wall / ceiling mount. Dimensions: Ø 415mm, height 465mm. High protection class, IP rating IP65. (without cover glass IP23)</p> <p>Optionally: Cover glass, protection grill, chain, wall-mount bracket. Special version: With additional lamp holder for instant-start or emergency lighting applications. Weight: 17 kg</p>
	<p>Low-Bay Light 41cm PC MH 150W</p> 	<p>High-Bay fixture with polycarbonate reflector 410mm. For metal halide lamp 150 watt. LP-41PC-15H</p> <p>Prismatic acrylic reflector 415mm, light-transparent. On request we also supply with polycarbonate screen. Incl. ballast Only suitable for metal vapor lamp HQI 150W E27. Please order lamps separately. The lamp is not dimmable. Height 465mm, incl. Cable gland for connecting any cable lengths and ceiling mounting. Operation only with optional safety screen or with lamps with splitter protection. Protection class: IP54 Moisture protection with diffusor, IP23 without diffusor. Weight: 17 kg</p>

Accessories for indoor lights



Protection cover for High-Bay Sherpa 41cm PC
LP-41Z-01



Protection cover for High-Bay 41cm Glass
LP-41Z-02



Protection Grill f. High Bay 41
LP-41Z-03



Goniometric Bracket for High Bay 41
LP-41Z-05

High-Bay Light Fixtures



**Pendant Light 42cm MH 150W
IP65**



Waterproof. Energy economizing, 150W metal halide = 550 watt halogen light.
LP-42AL-15E

Professional version with high light output.
Reflector outside silver, inside polished.
Incl. ballast, starter + capacitor for HID lamp HQI 150W E40.
Lamp has to be ordered separately.
Protection degree, IP rating IP65 (IP23 without cover lens).
Operation only with cover lens or with explosion protected light bulbs.
Dimensions: height 460mm, reflector diameter 430mm.
Optionally accessories:
Cover lens
Weight: 17 kg

Accessories for indoor lights



Protection cover for High-Bay 42cm Glass
LP-42Z-02

High-Bay Light Fixtures

LED High-Bay Light Atom 14000
Lumen

Bright LED pendant luminaire with optics. For shopping market, warehouse, workshop, factory, airport, train station and other high spaces.
Moisture-proof. 92W LED, as bright as 1000 Watt halogen or 150W HQI.
LP-4411

LED High-Bay Light Atom 21000
Lumen

Bright LED pendant luminaire with optics. For shopping market, high warehouse, factory, airport, railway station and other high buildings.
Moisture-proof. 138W LED, as bright as 1500 Watt halogen or 250W HQI.
LP-4413

LED High-Bay Light Atom 28600
Lumen

Bright LED pendant luminaire with optics. For shopping market, high warehouse, factory, airport, railway station and other high buildings.
Moisture-proof. 184W LED, as bright as 2000 Watt halogen or 400W HQI.
LP-4418

Accessories for indoor lights



Protection cover for High-Bay 48cm Glass
LP-48Z2

High-Bay Light Fixtures



PC Pendant Light 50cm MH 250W E40



High-Bay fixture with polycarbonate reflector. For metal halide lamp 250 watt = as bright as 1100w halogen light.
LP-50PC-2

Polycarbonate reflector 490mm light transparent.
Incl. Ballast, ignitor and capacitor compensation.
Suitable for metal halide lamp HQI-250W E40 (Please order separately).
Incl. cable gland for connecting any cable lengths and ceiling mounting.
Silver casing.
Overall height 560 mm
The lamp is not dimmable.
Protection: IP20 - suitable only for dry rooms.
Operation only with optional protection shield (splinter protection).
Weight: 7,1 kg

Accessories for indoor lights



PC Protection cover for High-Bay 50cm
LP-50Z-02

High-Bay Light Fixtures



High-Bay Fixture 50cm Alum, 2x 42W Fluorescent



Pendant light with aluminium reflector 510mm. Also for emergency lighting by instant starting fluorescent lamps.
LP-51AL-F08

Aluminium reflector 500mm, outside silver, inside polished.
Light distribution very wide (120°).
Luminous flux: 6400 Lm
Incl. ballast, starter + capacitor for 2 fluorescent lamps.
The lamps 42W TC-TEL GX24-q4 have to be ordered extra.
This lighting fixture is not dimmable.
Immediate starting, for emergency lighting applications, too.
Very rigid aluminium die-cast body with wiring box and cable glands for connection of free cable length.
With lifting eye for hanging up or for static wall / ceiling mount.
Dimensions: Ø 510mm, height 525mm.
High protection class, IP rating IP65. (without cover glass IP23)
Optionally: Cover glass, protection grill, chain, wall-mount bracket.
Special version: Dimmable, with electronic ballast at 8 pcs. MOQ
Weight: 17 kg



High-Bay Fixture 51cm PC, 250W MH



Pendant light with polycarbonate reflector 510mm. For metal halide lamp 250 watt.
LP-51PC-25H

Prismatic acrylic screen 515mm, light-transparent.
On request we also supply with acrylic screen.
Incl. ballast
Only suitable for metal vapor lamp HQI 250W E40.
Please order lamps separately.
The lamp is not dimmable.
Height 565mm, incl. Cable gland for connection of any cable length and ceiling mounting.
Operation only with optional safety screen or with lamps with splitter protection.
High protection class, IP rating IP65. (without cover IP23)
Optional:
Cover / diffusor
Weight: 17 kg

High-Bay Fixture 51cm PC, 400W MH

Pendant light with polycarbonate reflector 510mm. For metal halide lamp 250 watt.
LP-51PC-40M

Accessories for indoor lights



Protection cover for High-Bay Sherpa 51cm Acrylic
LP-51Z-01



Protection cover for High-Bay 51cm Glass
LP-51Z-02



Protection Grill f. High Bay 51cm
LP-51Z-03

High-Bay Light Fixtures



High-Bay Fixture L95 Alum 250W MH

Pendant light with aluminium reflector 500mm.
LP-53AL-M

Industrial version with high light output.
Reflector outside silver, inside polished. Light distribution very wide (120°).
Incl. ballast, starter + capacitor for HID lamp HQI 250W E40.
Protection degree IP55 with cover lens (IP 20 without lens)
Height 575mm, Ø 490mm.
Incl. cable gland and hook to hang down.
Optionally accessories:
Cover lens
Protection grill (ball-through protected).
Weight: 17 kg



LED High Bay Light 50W IP65

Waterproof aluminium pendant reflector lamp. 50W LED = 500 watt halogen light. Energy economizing.
LP-56-05



Professional pendant lamp with a very high light intensity.
Energy saving replacement for high bay fixtures with 125W HQL lamp.
Aluminum Reflector 51cm
Incl. power LED lamp 50 watt
Light color 4000K neutral white
Luminous flux 5000 Lm
Light distribution 90° (from 40 pcs available with 60° or 120°)
Light intensity 220 Lux / 6m height (135 lux / 8m)
At power on the light has the full brightness immediately - no waiting period.
Including power LED and driver.
Only power cord and chain can be ordered as needed.
The lamp is not dimmable.
The light is splash-proof and can even be used outside.
Operating voltage: 110V - 240V 50-60Hz
Incl. Cable gland for connecting any cable lengths and ceiling mounting.
Protection degree: IP rating IP65
Dimensions: Reflector diameter 510mm, height 380mm.
Weight: 5,4 kg

LED High Bay Light 120W IP65

Waterproof aluminium pendant reflector lamp. 120W LED = 1000 watt halogen light. Energy economizing.
LP-56-12

LED High Bay Light 200W IP65

Waterproof aluminium pendant reflector lamp. 200W LED = 2000 watt halogen light. Energy economizing.
LP-56-20

LED High Bay Light 110W IP65

Bright pendant luminaire with SMD LEDs. For medium height warehouse, factory, airport, railway station and other buildings. Moisture-proof. 15000 lumen, as bright as 1500 Watt halogen.
LP-59-11







LED High Bay Light 150W IP65





Bright pendant luminaire with SMD LEDs. For medium height warehouse, factory, airport, railway station and other buildings. Moisture-proof. 20000 lumen, as bright as 250 Watt HQI / MH / HPI
LP-59-15




LED High Bay Light 190W IP65

Bright pendant luminaire with SMD LEDs. For high warehouse, factory, airport, railway station and other buildings. Moisture-proof. 25000 lumen, as replacement for 400W HQL.
LP-59-19

Low Bay Fixtures 20 - 35cm

	<p>Pendant Light Bistro-Trendy 30cm Colour</p>	<p>With coloured prismatic acrylic diffusor. For lamp E27 max 150 w. LP-B30-27B</p>
		<p>With canopy and enclosure made of PVC With transparent-coloured screen in red, yellow, green or blue. Suitable for lamps up to E27 150W. (Energy saving lamps or LEDs are highly recommended). For installation in dry rooms, IP20, With subtle, light gray textile cable, about 1.5 m. Diameter 315mm, height 270mm. Weight: 2 kg</p>
	<p>Pendant Light Bistro-Trendy 30cm Prisma</p>	<p>With blind-free prismatic acrylic diffusor. For lamp E27 max 150 w. LP-B30-27C</p>
		<p>The acrylic reflector has a reflective coating to prevent glare side. Suitable for lamps up to E27. 150W. (Normal household bulbs or energy saving lamps are highly recommended). For installation in dry rooms, IP20, With subtle, light gray textile cable, about 1.5 m. With a canopy of silver PVC. Housing made of aluminum, silver. Reflector diameter 315mm, height 270mm Weight: 2 kg</p>
	<p>Pendant Light Bistro 30cm Fluorescent</p>	<p>With acrylic diffusor. For 2x compact fluorescent lamp 26w. LP-B30-Fluo</p>
		<p>With canopy and enclosure made of silver PVC. Built-in low-loss ballast. For G24d-3 26W lamps Please order lamp separately. IP20 for dry areas. Reflector diameter 315mm, height 420mm, pending height max. 2.4 m. Weight: 4,5 kg</p>
	<p>Pendant Light Alu Bistro 2 LED 33cm</p>	<p>Energy saving and decorative lamp with acrylic reflector and LED. Limited stock LP-B33-05</p>
		<p>PMMA Reflector 330mm. Decorative trim ring made of aluminum, grey painted. With electronic driver Including LED lamp 21W Light color: 3000 K warm white This lamp is not dimmable. The brightness corresponds to about 200 watt halogen light. Long lamp life, 25000 hrs</p> <p>Housing Aluminium grey or white. With suspension line, up to 1.5m ceiling canopy. Diameter 330mm, height 400mm Protection grade: IP20 Weight: 2,8 kg</p>

	<p>Pendant Light Alu Bistro 3 LED 37cm</p>	<p>Energy saving and decorative lamp with acrylic reflector and LED. Limited stock LP-B34-05</p> <p>PMMA Reflector 370mm. Decorative trim ring made of aluminum, grey painted. With electronic driver Including LED lamp 21W Light color: 3000 K warm white This lamp is not dimmable. The brightness corresponds to about 200 watt halogen light. Long lamp life, 25000 hrs</p> <p>Housing Aluminium grey or white. With suspension line, up to 1.5m ceiling canopy. Diameter 370mm, height 530mm Protection grade: IP20 Weight: 6,6 kg</p>
	<p>Pendant Light Alu Bistro 34cm MH 70W</p>	<p>Energy saving lamp with aluminium reflector and glass for metal halide lamp 70 watt G12. LP-B34-07</p> <p>Outer reflector consisting of an aluminium ring and satinized glass. Decorative, small inner aluminium reflector. With ballast for metal halide lamp G12 70W. (Please order lamp separately) The brightness corresponds to about 300 watt halogen light. Long lamp life, 10000 hrs Housing Aluminium silver gray. With suspension and up to 3m ceiling canopy. Diameter 350mm, height 550mm. IP20 Weight: 6,6 kg</p>
	<p>Pendant Light Bistro 33cm MH 70W</p>	<p>Energy saving and decorative lamp with acrylic reflector and ballast. Still 2 pcs. in stock LP-B35-07</p> <p>Transparent reflector 330mm PMMA. Decorative trim ring made of aluminum. With ballast for metal halide lamp G12 70W HQI. This lamp is not dimmable. (Please order the lamp separately) The brightness corresponds to about 250 watt halogen light. Long lamp life, 10000 hrs Housing Aluminium silver gray. With suspension and 150cm ceiling canopy. Diameter 330mm, height 400mm. IP20 Weight: 3,8 kg</p>
	<p>Pendant Light Bistro 42cm 42W Fluorescent</p>	<p>Energy saving and decorative lamp with acrylic reflector and ballast. LP-B40-04</p> <p>PMMA Reflector 420mm. Decorative trim ring made of aluminum, white painted. Ballast with electronic ballast for compact fluorescent lamp 42W GX24-q4 (on special order 70W HQI). This lamp is not dimmable. (Please order lamp separately) The brightness corresponds to about 200 watt halogen light. Long lamp life, 10000 hrs</p> <p>Housing Aluminium white. With suspension and up to 1.5m ceiling canopy. Diameter 420mm, height 530mm. IP20 Weight: 2,8 kg</p>

	<p>Pendant Light Bistro 40cm E</p>	<p>With acrylic reflector and E27 lamp holder. LP-B40-E</p>
	<p>Pendant LED Light Bistro 40cm</p>	<p>With acrylic reflector and bright LED lamp for shop, restaurant, kitchen. LP-B40-LED</p>
	<p>Pendant Light Vogue GTA-TI 41cm MH-150W</p>	<p>Suspension fixture with acrylic reflector. Powerful, for energy economizing metal halide lamp 150W. LP-V40R151</p> <p>Body in aluminium sheet painted in RAL 9075 grey colour Suspension by means of 1,5 m. of steel cable with safety fixing devices Polycarbonate ceiling rose with electric cable Acrylic prismatic reflector with 415 mm diameter and anti-glare coating With porcelain lamp holder E27, G12, GX12 or thermoplastic GX24q-3/4/5/6 lampholders Insulation class I Versions for metal halide discharge lamps up to 150W, Mini White SON lamps up to 100W and compact fluorescent lamps up to 70W Weight: 4,65 kg</p>