

Stage Floodlights



HAF 1250W AS, Stage Floodlight Asymmetric



Professional stage floodlight for continuous operation, with asymmetric reflector. EU manufacture
TA-1000A

Safety shut-off when the housing is opened.
Suitable for lamp R7s 189mm 650 /1000 /1250 W.
Light colour: 3000K (3200K with special lamps)
Colour rendering quality: 100
Light distribution: Asymmetrical, width approx. 65°. Incl. protective glass.
Please use HT colour foils or glasses only.
The luminaire is dimmable with a suitable dimmer.

Voltage: 220 - 230V
Housing: Steel, powder coated

Dimensions:
Width 320 mm
height 300 mm
depth 205 mm

Connection of several floodlights possible with optional connectors.
Weight: 5,25 kg



HAF 1250W S, Stage Floodlight Symmetric

Professional theater floodlight for continuous operation, with asymmetrical reflector. EU production
TA-1000S

Accessories for Stage Lighting



Barn Door for HAF 1250 Floodlight
TA-1002

Mechanical connector for HAF or Cyclo
TA-1003

Stage Floodlights



LAF 1000W A Stage Floodlight

Inexpensive 1000W floodlight for stages. With sturdy housing and asymmetrical reflector.
TA-1015A

with protective screen and filter frame.

Suitable for lamp R7s 189mm 650 /1000W.
Light colour: 3000K (3200K with special bulbs).
Colour rendering quality: 100
Light distribution: Asymmetrical, width approx. 65°. Incl. protective glass.
Please use HT colour foils or glasses only.
The luminaire is dimmable with a suitable dimmer.

Voltage: 220 - 230V
Housing: Steel, powder coated

Dimensions:
Width 320 mm
height 280 mm
Depth 205 mm
Weight: 5 kg

	Stage Floodlight 500W Asymmetric	<p>Professional stage spotlight with asymmetrical light distribution for lighting stage backdrops. TA-1020A</p> <p>The air gap between the lamp and the colour filter frame ensures less heat load and a long service life of lamp and colour foils. Supplied with colour filter frame and protective screen. There are 3 holes in the mounting bracket for hooks or also for swivel plates. Heat-resistant plastic set screws, removable front part for easy lamp replacement by means of quick-release fastener. Suitable for continuous operation. Can be fitted with halogens 300W or 400W R7s. Dimensions: Width 250mm (With knob 280mm) x Height 300mm, Depth 205mm. Weight: 4 kg</p>
	Stage Floodlight 500 W Symmetric	<p>Professional stage spotlight with symmetrical light distribution for general stage lighting. TA-1020S</p>

Accessories for Stage Lighting

	<p>Prosport Protection Glass TA-1042</p>
	<p>Colour filter frame for Prosport HID TA-1044</p>

Stage Floodlights

	Prosport Orion 150W MH Floodlight	<p>Stage spotlight for shop, trade fair, film and high-speed camera at golf courses or crash tests. 150W HQI = cool light with the brightness of 600W halogen. TA-1047-1</p> <p>Very low heat generation - also for exhibitions and shops. Light distribution 68°. Suitable for HQI-TS 150W lamp. Burning time of the lamp 6000h not dimmable. Built-in ballast. Optionally with low-cost magnetic ballast or with flicker-free electronic ballast. The electronic ballast spotlight is also suitable for high-speed photography and filming. Incl. front glass. No colour filter frame. Aluminium housing. Dimensions: 250 x 240 x 270mm. Protection class IP20 (only for dry rooms). Optional: barndoor Discontinued item, only limited availability Weight: 4 kg</p>
	Prosport Orion 250W MH Floodlight electronic	<p>Daylight luminaire for fair and exhibition. 250W metal halide = brightness of 1000W halogen. TA-1047-2</p> <p>Very low heat generation. Especially for trade fairs and exhibitions. Light beam 120° very wide. Suitable for HQI-TS 250W Fc2 lamp (please order separately). Burning time of the lamp 6000h not dimmable. Built-in magnetic ballast or electronic ballast flicker-free. The electronic ballast version is also suitable for high-speed photography. Incl. front glass. No colour filter frame. Aluminium housing, grey, with black fittings. Dimensions: W 330 mm, D 225 mm, H 285 mm. Protection class IP20 (only for dry rooms). Optional: barndoor Weight: 8,5 kg</p>

Accessories for Stage Lighting



Barn Door for Prospot Orion 150W
TA-1049-1



Barn Doors for Prospot Orion 250W
TA-1049-2



Barn Door for Prospot Orion 70W / 500W
TA-1049-5

Stage Floodlights



Halogen Floodlight HAF 500 Sym

Compact stage floodlight, symmetrical.
TA-1050-S



LAF 4x 500W, Flood Light Ramp, low-cost



Inexpensive halogen floodlight ramp with 4 chambers 500W. Symmetrical, for general stage lighting.
TA-1055

4 individually switchable light chambers, each has a 100cm cable with schuko plug.
Each chamber can be assembled with 300W or 500W R7s halogen lamp.
The bulbs ordered separately.
Vents prevent overheating of the chambers.
Supplied with grilles and color filters support.
Barndoors cannot be attached.
Attachment via M8 threaded connectors on the side ends, or via the supplied wall bracket for ceiling mounting.
Includes color slides of this washer can only max. 300W lamps are fitted.
With or without colors colored glasses can 500w lamps.
Dimensions: W 740mm, H 170mm, D 170mm.
Weight: 4,25 kg



HAF 6x 500W S, Theatre Flood Light Ramp

Floodlight ramp with 6 chambers 500W.
Symmetrical light distribution for general stage lighting.
TA-1056-S

4 individually switchable light chambers, each fitted with 300W or 500W R7s tubular halogen lamp.
The bulbs ordered separately.
Supplied with grilles and color filters support.
Optional barn doors can be fitted.
In combination with color filters may only be fitted with these floodlights 300W lamps. With or without colors colored glasses can 500w lamps.

Dimensions: W 1200 x H 155 mm.
Weight: 9,4 kg

Accessories for Stage Lighting



Barn Door for HAF 500 large, 2leaf
TA-1062



Barn Door for HAF 500 2 leaf stage floodlight
TA-1072

Stage Floodlights



Eurospot Halogen Floodlight 1000W



Stage floodlight for the inexpensive halogen lamps R7s up to 1000W.
Remaining stock 1 piece
TA-1080
Light beam 65°.
Please order separately: Illuminant R7s 300, 500, 1000W 118mm.
Incl. colour filter frame and protective screen.
When using 1000W lamps in combination with colour foils, an extension tube must be attached.
Aluminium housing.
Protection class IP20 (only for dry rooms).
W 290mm x H 300mm x D 260mm.
Optional: extension tube, barndoor
Weight: 3,3 kg

Accessories for Stage Lighting



Eurospot Extension Can

For use with colour filters with 650W or 1000W lamps in the Eurospot.
Remaining stock 1 piece
TA-1082

PAR Spots



PAR 16 Spot alu polished



Spotlight for MR16 Cool Beam lamp 50mm, 20 to 50 Watt 12V.
TA-1100
Suitable for dichroic reflector lamps 12V 50mm MR16 20W ... 50W.
Light distribution. 12°, 24°, 36° (depending on the lamp used).
With colour filter frame.
Connected voltage 12V (transformer required).
Light aluminium housing, polished.
Dimensions: h1 70mm, h2 150mm, w 92mm, l 130mm
Weight: 0,15 kg



Pinspot PAR 36 TUV GS chrome

PAR36 with transformer 35W produces a spot-shaped narrow beam of light.
For bar, club, table lighting, flower lighting ...
TA-1105C
with 50cm cable, without bulb. TÜV and GS tested.
Light distribution 4° - 6° depending on the lamp used.
Connected voltage 230 Volt.
Power consumption 40 Watt.
Length 150mm, width 115mm, height 120mm.
Weight: 1,1 kg



Pinspot PAR36 Economy, black

PAR36 spot with transformer 30W for creating very small cones of light.
TA-1106S



PAR Spot 30 E27 Aluminium



PAR30 spotlight aluminium polished or black for reflector lamps E27.
TA-1112-C
Suitable for reflector lamps E27 230V up to 75W, Ø max. 95 mm.
Please order the bulb separately.
Connection voltage: 230V
With connecting cable 40cm and safety plug.
With colour filter frame for the use of colour foils 100mm.
Dimensions: L 220 mm, W 120 mm, H 120 mm.
Weight: 0,4 kg

	PAR30 LED spotlight stage spotlight red / blue	<p>PAR30 spotlight aluminium polished or black with red or blue LED lamp. For shop windows, shops, decoration. Not very bright. TA-1112-F</p> <p>With LED reflector lamp E27 Available with light colour red or blue. Connection voltage: 230V With connecting cable 40cm and safety plug. With colour filter frame for the use of colour foils 100mm. Dimensions: L 220 mm, W 120 mm, H 120 mm. Weight: 0,4 kg</p>
	PAR30 LED spotlight stage spotlight	<p>PAR30 spotlight aluminium polished or black with LED. For shop windows, shops, decoration. TA-1112-L</p> <p>With LED reflector lamp E27 Light colour: warm white or cool white. Connection voltage: 230V With connecting cable 40cm and safety plug. With colour filter frame for the use of colour foils 100mm. Dimensions: L 220 mm, W 120 mm, H 120 mm. Weight: 0,4 kg</p>

Accessories for Stage Lighting

	<p>Barn Door for Par 30 Spot TA-1114-C</p>
--	--

PAR Spots

	PAR 30 Spot Exhibition, aluminium polished	<p>Halogen spotlight with 2m long connecting cable and plug. Suitable for reflector lamps E27. TA-1116-C</p> <p>Aluminium spotlight housing with swivelling bracket. Suitable for reflector lamps E27 230V up to 75W. Dimensions of the bulb: Ø max. 95 mm, length max. 95mm. Suitable lamps are available in different wattages and beam angles. Please order the bulb separately. Supply voltage: 230V Ready for use, with long mains cable and safety plug. Incl. colour butterfly frame 125 x 125mm. Dimensions: L 220 mm, W 120 mm, H 120 mm.... Weight: 0,5 kg</p>
	PAR 30 Spot Exhibition, black	<p>Halogen spotlight with 2m long connecting cable and plug. Suitable for reflector lamps E27. TA-1116-S</p>

Accessories for Stage Lighting

	<p>Barn Doors for Par 46 Spot aluminium TA-1119-C</p>
--	---

PAR Spots

	PAR 56 Spot 300W long	<p>Stage spotlight, polished aluminium or black, for PAR56 lamps up to max. 300W. The undesired stray light, as with PAR56 short, does not exist with this spot. TA-1120</p> <p>With suspension bracket, cable 60 cm, and 1 colour filter frame. The illuminant is not included in the delivery. Connection voltage: 230V Light aluminium housing Dimensions: L 340 mm, W 240 mm, H 240 mm. Weight: 1,4 kg</p>
--	------------------------------	--

Accessories for Stage Lighting



Barn Door for Par 56 Spot short, Aluminium
TA-1122-C

PAR Spots



**PAR 64 Can 1000W light,
aluminium polished**

Halogen stage spotlight for PAR 64 lamp up to max. 1000W.
TA-1124-C

This spotlight can be optionally equipped:
With a PAR64 reflector lamp made of pressed glass in 500W or 1000W
or with a Raylight reflector and a separate halogen lamp GY9.5 max. 500W.
The lamp is not included in the delivery.
For continuous operation, we recommend the use of pressed glass lamps,
as the heat radiation is more even here.
The greatest heat is generated when using Raylight reflectors together with
colour foils.
In this case, the spotlight should only be used in chaser or light organ mode,
but not in continuous operation.
Supply voltage: 230V
Ceramic socket GX16d
Light aluminium housing, polished chrome.
With suspension bracket, protective grille, colour filter frame and connecting
cable without plug.
Dimensions: L 400 mm, W 285 mm, colour filter frame 260 mm.
Weight: 1,6 kg



PAR 64 Can 1000W low-cost, black

Stage spotlight for PAR64 lamp up to max. 1000W.
TA-1124-S

Accessories for Stage Lighting



Barn Door for Par 56 Spot long
TA-1125



Barn Door for PAR 64 spotlight
TA-1127-C

PAR Spots



PAR 64 Floor Spot Professional






Rigid spotlight with 2 adjustable brackets for mobile stand-up use. For PAR64
lamp.
TA-1129-C

This spotlight can be optionally equipped:
With a PAR64 reflector lamp made of pressed glass in 500W or 1000W
or with a Raylight reflector and a separate halogen lamp GY9.5 max. 500W.
The lamp is not included in the delivery.
For continuous operation, we recommend the use of pressed glass lamps,
as the heat radiation is more even here.
The greatest heat is generated when using Raylight reflectors together with
colour foils.
In this case, the spotlight should only be used in chaser or light organ mode,
but not in continuous operation.
Supply voltage: 230V
Ceramic socket GX16d
Lightweight aluminium housing, polished or black coated.
Adjustable brackets for hanging or standing.
With protective grille, colour filter frame and connecting cable and tread-
proof plug.
Dimensions: L 350 mm, W 285 mm, colour filter frame 260 mm.
Weight: 1,6 kg



PAR 64 Floorspot Simple

Lightweight spotlight with 2 swivelling brackets for placing on the floor. For
PAR 64 lamp
TA-1130-C

	Raylight-Reflector PAR64 MFL	<p>PAR 64 reflector insert for use with 300 /500 W GY9.5 halogen lamps. Narrowly focused light emission. PAR 64, with GY9.5 socket and GX16d plug. Is plugged directly onto the previous socket. For use with halogen lamp 300 /500 W. These lamps react faster to switching on and off and are therefore and are therefore especially recommended for running light and light organ operation. Light distribution: 20° medium flood - medium narrow beam light Construction height of the pure reflector 60mm. Use of coloured foils not possible. TA-1131-F</p>
	PAR 46 Spotlight / 100W	<p>Stage spotlight suitable for reflector lamps E27 up to max. 150W. TA-1134</p> <p>With suspension bracket, colour filter frame, spiral cable and mains plug. Porcelain socket E27 suitable for PAR30 or PAR38 lamps. The bulb is not included in the delivery. Supply voltage: 230V Dimensions: L 320 mm, Ø 150 mm, colour filter frame 195 mm. Polished aluminium Weight: 1,5 kg</p>
	PAR 56 Spot 300W Set Eco	<p>Halogen floodlight incl. illuminant PAR56 300 W, 4 colour filters and colour filter frame. TA-1135-C</p> <p>Compact stage spotlight with 80cm cable and safety plug. Ready for use with colour frame and 4 colour foils. Connection voltage: 230V Length 230 mm. Weight: 2,3 kg</p>
	PAR 56 Spot Light LED RGB	<p>Colour-changing PAR 56 LED stage light, controllable via DMX or sound. Special price only while stocks last ! TA-1160</p> <p>With RGB colour mixing. 153 high-intensity LEDs (51x red, 51x green, 51x blue). Light range up to approx. 3 metres. Automatic colour change adjustable or via built-in microphone or DMX. DMX 512 input addressable (XLR 3-pin in and out) With 4 control channels (3x for colours and 1x for pre-programmed chaser effects) Connection voltage 230V / 15 Watt With mains cable and safety plug Dimensions: L 220mm, W 220mm, H 260mm Available in black or polished aluminium. Weight: 1,7 kg</p>
	Power PAR 64 Spot LED 20x 3W 60W RGB	<p>PAR spot with 20 x 3W power LEDs. Stepless colour change controllable via DMX or menu. Stock only 1 piece TA-1166</p> <p>With RGB colour mixing. 20 high-power LEDs 3 Watt. Beam angle 25°. Automatic colour change and brightness controllable via DMX-512 or via the control menu with LCD display. DMX 512 input addressable (XLR 3-pin in and out) Noiseless operation due to convection cooling. Connection voltage 230V / 75 Watt With mains cable and safety plug Dimensions: L 400 mm, W 285 mm. Available in black or polished aluminium. Weight: 2,2 kg</p>



LED trade fair lighting and stage spotlights



Powerful spotlight in professional aluminium housing. With white high-power LEDs, controllable via DMX512.

TA-1181

Discontinued item - 3 pieces left in stock

Spotlight with large power LEDs for indoor use.

151 white LEDs 10mm

Controllable via DMX512 (6 DMX channels)

Infinitely dimmable.

Strobe effect.

Automatic mode with internal programs.

Built-in microphone for sound control.

The LEDs have the brightness of approx. 120W halogen light.

Service life: 50,000 h

Beam angle: 35°

Protection class: IP20

Connection voltage: 110V ... 240V / 20 W

Housing Aluminium profile

Weight: 2,1 kg

Accessories for Stage Lighting



4 Leaf Barn Door for TV Spot 2500W

TA-1225

Fresnel Spotlights



Stage Spotlight 1000W PC Lens Europe



European-quality 1000W plano-convex theater spotlight with adjustable light cone and plano-convex lens.

TA-1241-PC

Plano-convex lens 150mm.

Light distribution adjustable via sliding carriage: 8-60°.

Suitable for halogen lamp GX9.5 650W or 1000W (CP67, CP70, T21, T29).

Please order lamp separately.

Connection voltage 220 - 240V

With mains cable 100cm.

Housing: aluminium profile with sheet steel, black powder coating.

Including colour filter frame with protective grid

Dimensions: L 350mm x H 208mm x W 210mm

Weight: 5,5 kg

Accessories for Stage Lighting



4 Leaf Barn Door for Lens Spot 1000W

TA-1245



Colour Filter Frame For Lens 1000W

TA-1247



4 Leaf Barn Door for Lens Spot 500W

TA-1255



4 Leaf Barn Door for 500W Lens Spot

TA-1265

Fresnel Spotlights



Fresnel Spotlight for exhibition MH 70W / 150W



TA-1260

Very bright HQI spotlight with adjustable light cone. Little heat. For trade fair or salesroom.

Only small quantities left in stock - can no longer be reordered.
TA-1280

Advantages due to metal vapour discharge lamp:

Increased luminous intensity (approx. 600 Watt halogen), energy saving and longer lamp life.

- Optics with Fresnel lens and adjustable light cone.
- Available as 70W or 150W version.
- For lamp: CDM-T or HQI-T (please order separately).
- With electronic ballast, flicker-free.
- Very low heat emission
- With mains cable 1m
- Operating voltage: 220/240V 50/60 Hz
- Aluminium housing, black (grey on order) epoxy powder coated.
- Dimensions: L 29, W 29, H 16/ 24 cm

Energy-saving, produces little heat, high brightness.

Reduced UV radiation.

Light circle adjustable over a wide range - can be precisely aligned to the object.

Light colour daylight, neutral white or warm tone.

70W model:

Light spread 10° - 58°

Light intensity 130 - 950 Lx at 5m distance

(corresponds to 300W halogen)

150W model:

Light spread 22° - 60°

Light intensity 350 - 1200 Lx at 5m distance

(corresponds to 600W halogen)

Weight: 5 kg

Accessories for Stage Lighting



Barn door f. lens spotlight CDM
TA-1283

Fresnel Spotlights



Stage spotlights for trade fairs and exhibitions Size adjustment



KELVIN

Very bright HQI spotlight with adjustable light cone and barn doors. Little heat. For trade fair or salesroom.
Only small quantities left in stock - can no longer be reordered.
TA-1284

Advantages due to metal vapour discharge lamp:
Increased luminous intensity (approx. 600 Watt halogen), energy saving and longer lamp life.

- Optics with Fresnel lens and adjustable light cone.
- Available as 70W or 150W version.
- For lamp: CDM-T or HQI-T (please order separately).
- With electronic ballast, flicker-free.
- Very low heat emission
- With mains cable 1m
- Operating voltage: 220/240V 50/60 Hz
- Aluminium housing, black (grey on order) epoxy powder coated.
- Dimensions: L 29, W 29, H 16/ 24 cm

Energy-saving, produces little heat, high brightness.

Reduced UV radiation.

Light circle adjustable over a wide range - can be precisely aligned to the object.

Light colour daylight, neutral white or warm tone.

70W model:

Light spread 10° - 58

Light intensity 130 - 950 Lx at 5m distance
(corresponds to 300W halogen)

150W model:

Light spread 22° - 60°

Light intensity 350 - 1200 Lx at 5m distance
(corresponds to 600W halogen)

Weight: 5 kg

Profile Spotlights



Profile Spot 1000/1200W 22-40°

Operating distance 4.5 m ... 10 m. Stepless focusing through zoom profile.
TA-1361

With high-intensity condenser optics.

Light intensity 585 /922 Lux /10m /1000W.

Stepless focusing between 22° and 40°.

With 4 diaphragm sliders.

Suitable for lamp G22 1000W or 1200W (available on special order for lamp GX9,5 650W or 1000W).

Please order lamp separately.

Supply voltage 220 - 240V

Colour filter size 200x 225mm.

Insertion possibility for iris or gobo (max. 160 x 135 x 19mm).

Dimensions: L 700mm x H 434mm x W 360mm.

Optional accessories: Iris, gobo holder

Weight: 15,5 kg



Profile Spot PSL 1000W 22-40°

Profile spotlight W1188. Operating distance 4.5 m ... 10 m. Stepless focusing with zoom profile.
TA-1361-C

Accessories for Stage Lighting



Iris diaphragm for Profiler 1000/1200W
TA-1365

Profile Spotlights



Zoom Profile Spot 500W 20°-40°

Profile spotlight, continuously focusable and adjustable light cone. Range of use up to approx. 8 m.
TA-1371

Light intensity 493 lux /10m.
Stepless focusing and light cone adjustment between 22° and 40° .
Light emission lens 100mm.
Powerful optics.
With 4-fold shutter and separate slots for iris and gobo M.
Suitable for lamp GY9,5 300W or 500W.
Supply voltage 220 - 240V.
Scratch resistant powder coating.

Similar to: W1181 650W ADB DW54
Weight: 8 kg

Accessories for Stage Lighting



Colour filter frame for profile spot 500W
TA-1376

Profile Spotlights



Profile-Spot CDM 150W



Zoom Profiler adjustable. Energy-saving. For trade fairs, exhibitions, theatres or projection. Light range up to approx. 10m.
TA-1396

Sharply defined light cone.
With ECG, electronic ballast, flicker-free or with low-loss ballast.
The light circle can be set razor-sharp or with soft edge transition.
Beam angle 20° - 36° adjustable.
The light beam can be limited to a rectangular, trapezoidal or triangular shape with the 4 diaphragm sliders.
A gobo holder size M is available as an accessory for projecting projection motifs, gobos or logos onto the wall.
Colour filter frame included.
Projection size at 5m distance: 1 cm ... 200 cm,
Light intensity approx. 1180 lux / 5m
Dimensions: L 550mm, W 200mm, H 310mm (with bracket)
Weight: 8,7 kg

Accessories for Stage Lighting



Iris diaphragm for Profiler 150W
TA-1398

Profile Spotlights



Profile Spotlight CDM 150W Mini Action



Zoom Profiler adjustable. Energy-saving. For exhibition stand, stage, projection. Distance up to approx. 10m.
TA-1399

Sharply defined light cone.

With low-loss ballast.

The light circle can be adjusted to be razor-sharp or with a soft edge transition.

Beam angle 22° - 35° adjustable.

The light beam can be limited to a rectangular, trapezoidal or triangular shape with the 4 diaphragm sliders.

A gobo holder size M is available as an accessory for projecting projection motifs, gobos or logos onto the wall.

Light beam diameter at 5m distance: 1 cm ... 200 cm,

Light intensity approx. 1180 lux / 5m

Dimensions: L 570mm, W 200mm, H 310mm (with bracket).

Weight: 12,6 kg

Accessories for Stage Lighting



Mechanic Dimmer Dowser for Followspot
TA-1461

Moving Lights / Scanners



Moving Head Kelvin M575 Spotlight



Head-mounted motorised spotlight with colour change and interchangeable gobos.

Very bright 575W MSR.

Demonstration unit

TA-1540S

Special price for 1 item on display,
small dent on the lower part of the case.
Perfect function with 12 months warranty.

Head-mounted spotlight motor-controlled with colour change.
Can be controlled via any suitable DMX light control panel.

Technical data:

Moving light Pan 530° (3 sec.)

Tilt 280° (2.2 sec.)

smooth, jerk-free movement,

2 colour wheels with 9 colours + white,

Gobo wheel with 9 gobos 27mm and shake function,

gobo wheel with 6 gobos and rotation/position,

3-position prism, motor focus, motor iris,

Motor zoom for 15°, 18°, 22°

Light intensity 600 lux /20m /15°

Motor dimmer, blackout, strobe effect,

16 DMX circuits with 16bit high resolution.

Please order the 575W MSR lamp GX9.5 separately.

Length 47cm, width 45cm, height 58cm.

Weight: 33 kg



Tripods, Lifts











T-Bar with Harting and 4 Schuko sockets




Aluminium crossbar with 4 Schuko sockets for light stand.
Connection via Harting 16-pin plug connector.

TA-1869-4




	<p>Speaker Stand 210cm 35mm up to 12 kg</p> <p>Height 1.26m ... 2,10m. Black.</p>	<p>Sturdy light stand made of aluminium. Tilt-resistant foot construction. The height is continuously adjustable by means of a surface-protecting clamping screw. An additional safety cotter pin guarantees a secure hold. Extension tube Ø 35 mm for attaching a loudspeaker box or a head clamp for mounting lights. TA-1877</p>
	<p>Tracker tripod</p> <p>Stable tripod for manually operated spotlights, loadable up to 45 kg.</p>	<p>Robust and tilt-resistant even on uneven terrain. Min. height: 90cm max. Height: 150cm With sleeve for TV spigot. With level compensation. TA-1881</p>

Hooks, Clamps for Stage Lights


	<p>G-Mounting Clamp 12 - 50 mm</p>	<p>Small hook for stage spotlights and luminaires TA-1901</p>
	<p>Light Clamp For 19mm Tubes</p>	<p>Luminaire fixing galvanised, with rubber pad. Clamping range 19 - 23mm TA-1902-19</p>
	<p>Light Clamp For 25mm Tubes</p>	<p>Headlight clamp galvanised 26 - 29mm. TA-1902-25</p>
	<p>Clamp for 50mm Pipe, Light</p>	<p>Headlight clamp galvanised 47 - 51mm. TA-1902-50</p>
	<p>Headlight clamp for 60mm tubes, lightweight</p>	<p>Luminaire fixing, suspension galvanised 57 - 61mm... TA-1902-60</p>
	<p>Headlight G-hook 50mm single</p>	<p>Suspension hook for headlamp silver (black as special version) TA-1903C</p>
	<p>Headlight G-hook 75mm</p>	<p>Suspension hook for headlamps on 75mm tubes. Loadable up to 50kg, colour silver. TA-1907</p>
	<p>Aluminium die-cast Swivel Truss Clamp 50mm Half Coupler</p>	<p>Truss aluminium clamp for attaching spotlights to tubes or trusses. Max. 100kg. No damage to the aluminium crossbars due to full-surface support. For tube diameter 48 - 51 mm With M10 fastening screw for headlight mounting. TA-1912-3</p>
	<p>Folding hook 50mm cast aluminium, 100 kg black</p>	<p>Half Coupler Aluminium clamp for attaching spotlights to tubes or trusses. Max. 100kg. No damage to the aluminium crossbars due to full-surface support. For tube diameter 48 - 51 mm With M10 fastening screw for headlight mounting. TA-1912-3B</p>
	<p>Folding hook 50mm cast aluminium, 500 kg</p>	<p>No damage to the aluminium crossbars due to full-surface support. Half Coupler. Max. 500 kg. For tubes with 48mm - 51mm diameter. With M10 fastening screw for headlamp mounting. TA-1912-5</p>







	Headlight Hook Trigger Clamp 50mm	Made of cast aluminium, hinged. Ideal for heavy loads: first hook in, then screw down at your leisure. For pipes with 44mm - 52mm diameter. Highly loadable up to 200kg Suitable for hexagon bolt M12. TA-1914
	Hinged hook 50mm with eye	Cast aluminium truss pick-up. Load capacity 200 kg. For pipes with 44mm - 52mm diameter. TA-1917-3
	Aluminium die-cast swivel Truss Clamp 30mm	To fix spotlights on aluminium trusses. Max. 100 kg. For tubes with 30mm - 32mm (1 1/4) inch diameter. To mount a spotlight or other fixtures with a screw M6 (not included) TA-1919

Safety Lines



	Safety Line Steel 50cm /2mm /Quick	Catch rope for barndoors, small lights, colour filter frames etc. With quick-release fastener. Complies with BGV-C1. Load to be secured max. 5kg. TA-1921
		Steel cable 2mm thick, galvanised. According to DIN 3055. Fulfils DIN 56926 and BGV-C1. Suitable for use at public events. Inserted thimbles in the loops at the rope ends protect against wear and damage. A quick-release screw connection NG3 serves as a lock. Weight: 0,03 kg
	Safety Line Steel 75cm /3mm /Quick captive	Catch line for stage lights with quick release. Load to be secured max. 10 kg. For PAR spots and small spotlights. TA-1922-U
	Safety Rope Steel 75cm 4mm Safety with quick release fastener	Catch line for stage lights. With quick release fastener. Complies with BGV-C1. Load to be secured max. 30 kg. TA-1923-S
	Safety Rope Steel 100cm /4mm with quick release fastener	Catch line for stage lights. With quick release fastener. Complies with BGV-C1. Load to be secured max. 30 kg. TA-1925-S
	Safety Rope Steel 100cm Safety 5mm with quick release fastener	Catch line for stage lights with quick release fastener. Complies with BGV-C1. Load to be secured max. 50 kg. TA-1927-S
	Safety Rope Steel 100cm /6mm Safety with quick release fastener	Catch line for event technology. Complies with BGV-C1. Max. load to be secured: 74 kg. TA-1928
	Safety Line Steel 100cm 8mm with quick release fastener	Catch rope for event technology. With quick release fastener according to DIN 3055. max. load to be secured 100 kg. TA-1929
	Pendant Line for Trusses up to 5m height	Length-adjustable wire rope 6mm Incl. freely fixable rope lock for continuous suspension 10 cm ... 500 cm height. Steel cable 6mm thick, galvanised. One side with thimble and quick connector, Breaking strength 1800 kg, according to DIN 3060. Permissible load max. 75 kg per rope. The rope is pulled through the rope lock and adjusted to the required length. The open, hanging-out end is placed in a loop shape at intervals of a few centimetres and fixed with the rope clamp. TA-1930-5

Hooks, Clamps for Stage Lights

	Exhibition luminaire clamp (spring) white	Spring clamp for fixing spotlights to exhibition partitions. TA-1932
---	--	---

	Exhibition luminaire clamp (spring) black	Large spring clamp for attaching spotlights to exhibition partitions. TA-1933S
	Truss-Tower Junction	Connector with 2 folding clamps and 1 pin for lift or crank stand 55mm. TA-1937
		TA-1938
	TV Spigot 28mm, w. drilling M10	Made of steel for attaching spotlights to tripods. TA-1940
	TV Spigot with plate	28mm Ø with M10 bolt and wing nut. For heavy headlights and for easier swivelling. TA-1941
	Tripod head clamp 35mm - DIN spigot	Suitable for holding a DIN spigot 35mm For tripods with 35 mm tube diameter. With M10 wing screw TA-1944

Light Effects

	Smoke-Liquid High Density, 5L	Fog fluid of simple quality. Odourless and harmless to health. Inexpensive fog fluid for occasional use in discos or parties. The fog stays for up to 10 minutes, depending on the room ventilation. Suitable for all vaporiser fog machines. TA-2022
	Smoke-Liquid High Density, 25L	Fog fluid. Odourless and harmless to health. TA-2025
	Fog Machine Baby Fog 4 with Remote Control	Handy, small smoke generator 450W for party effects - including the smoke liquid. TA-2067 Handy little fog machine for party effects, Built-in 0.5 L tank. Not suitable for continuous operation - Must be disconnected from the power supply after 1 hour. Operating voltage 230V Current consumption max. 450 W. Dimensions: 220 x 160 x 180 mm including handle. Weight: 3 kg

Accessories for outdoor fixtures

	Flexilight Rope Light Connector 13mm TA-2143I
	Flexilight End Cover TA-2148
	Flexilight Mounting Clip rigid TA-2150

Rope Lights



LED Flexilight Rope Light 45m blue

Finally, a light tube that lasts a long time and consumes little electricity. 45 metres long. Particularly robust IP44 design for market stall, garden party, outdoor decoration, Christmas lighting, garden pub, beer garden.
Stock: 1 piece
With special Leds.
Life time: 50.000 h
Operating voltage 230 volts, 4 watts /m
diameter 10mm
Length: 45 meter
Can be cut every meter. Extendable on up to 45 meters.
lamp distance 27mm
Splash-proof and temperature resistant -20° to +60°C
With power cord and schuko connector
Protection IP44, class 3
TA-2155

Light Consoles



Lighting Console LT TITAN 48 DMX



Robust lighting console for controlling max. 48 dimmers and colour changers and one positionable spotlight (scanner).
Storable groups, chaser effects, light scenes. Monitor connection.
TA-3030

Robust lighting console for controlling max. 48 dimmers and colour changers and one moving light (scanner).
Storable groups, chaser effects, light scenes.
Monitor connection.
Brand quality made in EU.

Professional lighting control desk with:
Joystick for controlling a positionable spotlight (moving light).
48 dimmer circuits with patch to 512 circuits.
24 circuit controllers switchable to low or high circuit numbers, plus 2 virtual presets.
12 submaster controllers for fast driving of individually stored groups or chaser effects, assignable to 99 pages.
400 presets / presets.
Sequence with 400 steps, run-in and run-out times and jumps,
Flash mode: normal or solo,
50 extensive chaser memories with any number of steps.
Any circles can be defined as colour changers.
With illuminated LCD display 2x 40 characters.
Possibility to connect 1 desk light TA-3123.

Outputs:
DMX-512 /1990,
Midi In /Out,
audio input,
Connection for VGA monitor.

Can be stored on a memory card (please order card separately) or via Midi connection on a PC (software can be downloaded free of charge from the Internet).
Brand quality made in EU.
Dimensions: Width 72cm, depth 50cm.
Weight: 16 kg



Lighting Console LT TITAN 72



Robust lighting control panel for controlling max. 72 dimmers and colour changers and one positionable spotlight (scanner).
Storable groups, chaser effects, light scenes. Monitor connection.
TA-3033

Robust lighting control desk for controlling max. 72 dimmers and colour changers and one moving light (scanner).
Storable groups, chaser effects, light scenes.
Monitor connection.
Brand quality made in EU.

Professional lighting control desk with:
Joystick to control a positionable spotlight.
72 dimmer circuits with patch to 512 circuits.
36 circuit controllers switchable to low or high circuit numbers, plus 2 virtual presets.
24 submaster controllers for fast driving of individually stored groups or chaser effects, assignable to 99 pages.
400 presets / presets.
Sequence with 400 steps, run-in and run-out times and jumps,
Flash mode normal or solo,
50 extensive chaser memories with any number of steps.
Any circles can be defined as colour changers.
With illuminated LCD display 2x 40 characters.

Connection possibilities:
from 1 desk light TA-3123.
Output DMX-512 /1990,
Midi In /Out,
audio input,
connection for VGA monitor.

Dimensions:
Width 96cm, depth 50cm.

Can be stored on memory card (please order card separately)
or via Midi connection on a PC
(software can be downloaded free of charge from the Internet).
Weight: 19,45 kg

Accessories for Light Controls



Overvoltage protection Device
protection adapter

Schuko adaptor with control indicator lamp.
TA-3117

Work Lights



Gooseneck Work Light with
Transformer

Flexible desk lamp with dimmer and 4W lamps as small work lamp, mixing desk lamp, reading lamp or music stand lighting. With transformer for 230V.
TA-3120

DMX Splitters, Data Boosters



DMX Splitter Booster 4 way GeoDim



DMX512 data signal amplifier and splitter. 19 inches. Made in Europe.
1 input, 4 outputs.
TA-3149

For use with long cable lengths, division into several DMX lines.
Increased operational safety: In the event of a fault on one DMX line, the other remains unaffected.
Connections XLR 3-pole
Operating voltage 230 V ac

Dimensions:
Width 483mm (19-inch)
Height 1 U
Weight: 1,5 kg



LT Splitter Plus, DMX-Booster 2x 3 way



DMX-512 data signal amplifier splitter, 2 inputs x3 outputs or 1 x 6 outputs. TA-3151

2 inputs XLR-5
2 feed-thru outputs XLR-5 for looping through to further splitters or for parallel connection to 6 outputs.
2 x 3 outputs XLR-5
All inputs and outputs are optically isolated.
2 LEDs on each input and output indicate the respective status.
Operating voltage 230V

Dimensions:
Width 483mm (19-inch), height 1 U.
Weight: kg



LT DMX splitter distributor 8-way



DMX-512 data signal amplifier and booster. 1 input, 8 outputs. TA-3152

For use with long cable lengths, division into several cable strands.
Increased operational safety: In the event of a fault on one DMX line, the other remains unaffected.
All inputs and outputs are optically isolated: Disconnects in case of potential differences, multiple earthing points.
Eliminates ground loops / hum loops.
2 LEDs on each input and output indicate the respective status.
Operating voltage 230 V ac.

Dimensions:
Width 483mm (19-inch), height 1 U.
Weight: 4,2 kg

DMX Multiplexors, Converters



DMX DeMultiplexer 1 Channel + Relay Board

Actuator converts 1 circuit DMX512 to analogue 0-10V and 1-10V. Additional relay output, for fluorescent lamps.
For controlling dimmable EVG fluorescent lamps or blinds, blackouts, curtains.
From 10% control signal, an additional relay contact 250V 6A switches.
The start address is adjustable via DIP switch.
Output voltage 0V - 10V max. 40mA
With ECG connection (operation as current sink) 1- 10V max. 10mA.
Operating voltage 12 V dc / 150 mA.
Dimensions of circuit board 45x 92 mm.

Order as accessory:
Plastic frame for snapping onto top-hat rail (width 48 mm, depth from top-hat rail 48 mm).
TA-3154



DMX DeMultiplexer 2 Channel Board

Demultiplexer converts 2 circuits DMX-512 to analogue 0-10 volts. Remaining stock 1 pc.
All connections are made via screw terminals.
The start address can be set via DIP switches.
Output voltage 0V ... + 10V max. 40mA
Operating voltage 12 Vdc / 200 mA.
Dimensions of the printed circuit board: 81 mm x 48 mm.

Remaining stock 1 pc. (Reproduction from 10 pcs.)
For single order, please see our demultiplexer TA-3157-8
TA-3155



LT Light Technology Pirone Merger, AVAB-DMX Converter



Converts AVAB protocol to DMX-512 and DMX512 to AVAB, as well as light scene memory.
Can merge 2 lighting consoles into one DMX line. MIDI, DMX RS232 SMPT EMTC, patch converter and USB control.
TA-3193

Stores light scenes and can run them time-controlled via internal and external midicode.
Converts various AVAB protocols (240 and 256) into DMX-512 and vice versa.
Merge function: Merging of two console signals (DMX or AVAB) into one DMX signal with single patch option.
1024 DMX channels can be managed.
Operating voltage 230V AC, 50Hz / 60Hz

In sturdy 19 inch metal housing:
Width 483mm (19 inch), 1 U, depth 250mm.
Weight: 4,5 kg

Dimming Packs 19 inch



LT Dimmer Pack LIBERTY 6x 2,5KW Schuko



Low noise digital dimmer pack. 19 inch. Analogue 0-10V and DMX. With mains cable and 6x double earthing contact.
TA-3200S

Reliable dimming pack, made in EU / service in Germany.

Inputs:

Analogue 0-10 V via Sub-D15 connector
and DMX-512 via XLR connectors.

All inputs can be used at the same time. HTP (the highest value takes priority)

Outputs: 6x Double schuko.

Each circuit is protected by a magnetic breaker.

Mains connection 3x 230V 32A with screw terminals (optional 1.5 m power cord).

Very quiet leading-edge dimmer.

Good noise suppression: Rise time > 120 µsec

Comfortable operation menu with illuminated display.

DMX starting address, preheat and individually selectable dim- and switching-curves can be set via the menu.

Saves an emergency lighting-scene on loss of DMX signal.

Temperature-controlled fan, super quiet.

Triacs / Thyristors and all boards are not soldered on, but plugged and screwed, to ensure ease of service.

19-inch rack: W 483mm x H 132mm (3U) x D 383mm.

Optional available: side carry handle.

Weight: 9,6 kg

LT Dimmer Pack LIBERTY 6x 2,5KW Harting w.cable

LT digital dimmer case, very low noise. Input: Analogue and DMX. Output Harting. With power cable.
TA-3201N

LT Dimmer Pack LIBERTY 6x 5KW Terminals

LT digital dimmer, very low noise. Input: Analogue 0-10V and DMX512. Mains connection and load outputs via screw terminals.
TA-3207



GeoDim LOG 12x 2.5kW DMX Dimming Pack



Digital dimmer from EU production 12 channel, 2500W each Harting. 19 inch, analogue 0-10V and DMX512.
TA-3240

Input DMX-512 in / out via XLR 5-pin socket.
Input analogue +10V via 2 x DIN 8-pin connectors with screw connection.

Outputs: Via 2x Harting 16-pin connectors.
Each circuit is fused via its own automatic circuit breaker.

Mains connection 3x 230V 63A via 1.5m mains cable.
High-quality interference suppression: > 120µsec risetime
Very high digital resolution 10 bit for flicker-free dimming transitions.
Comfortable operating menu with illuminated display for setting the DMX start address, preheating and individually adjustable switching and dimming curves for each channel.
With temperature-controlled, powerful fan for problem-free continuous operation,
Overtemperature protection.
Protection against overvoltage 400V or mains connection polarity reversal.
Manufactured in the EU / serviced in Germany.

Dimensions: W 483mm (19-inch) x H 132mm (3HE) x D 350mm.
Weight: 14,5 kg

Timer switches



DMX Light Controller 1 Week Year Timer



Programmable DMX512 lighting control for outdoor lighting, exhibition stand, façade lighting, shop window, cinema, swimming pool or animal stable.
TA-3320

Programmable DMX512 lighting control for outdoor lighting, exhibition stand, façade lighting, shop window, cinema, swimming pool or animal stable.
Range of application: Artificial sunrise and sunset in animal stables, zoo, animal breeding, exhibition stand, shop window, outdoor lighting, sauna world.

DMX512 output for controlling appropriate dimmers, LED lights or relays.
Controllable units: 16 pcs. max. 32 channels /unit = total 512 channels.
The fade times are freely selectable.

- 999 light scenes
- 999 sequences / 99 steps in each sequence
- 999 times can be stored.
- Each time point starts a scene or sequence number or a programme:
- 99 daily programmes
- 99 weekly programmes
- 99 monthly programmes
- 99 special programmes (special day programme)
- Fading time selectable up to max. 99 minutes.

Individual light scenes and sequences can be saved and combined into programmes.
Then, for example, a daily programme can be started, and the show or sequence will run automatically every day.
In the event of a power failure or when the unit is switched off, all information is retained in memory.

Additional PC software for quick creation of scenes, sequences and programmes,
as well as for transmission between console and PC via the RS-232 interface.

Connection voltage 230V AC (power supply 7.5V AC or DC is included).
Metal housing for standing or panel mounting.
Dimensions:
Width 110mm,
height 138mm
Installation depth 46mm

Optional: Daylight sensor for starting programme sequences.

Weight: 1,25 kg

Recessed Wall Dimmer Switches and Control Panels



Electronic Dimmer Potentiometer
Recessed f. ballasts

Electronic potentiometer for controlling dimmers or electronic ballasts with 1-10V current sink.
TA-3324

Din Rail Dimmers Varintens



DIN Rail Dimmer 1200W
SDK-AB-05 Varintens

Trailing-edge dimmer for resistive and capacitive loads max. 1200 watt. Input 0-10v or potentiometer.
Trailing-edge dimmer for dimmable electronic transformers and incandescent lamps.
Very low-noise dimmer for a smooth fading between 0% and 100%
Connection by screw terminals.
Input: 0 - 10 volt or 1 - 10 volts current sink (EIB, DALI).
Input for standard potentiometer or electronic pot.
Additional relay included, wich cuts off at 0% dimming. Max 10 amp. load
Operating voltage 220 - 240V AC
Width 105 mm, height 90 mm, depth 49 mm
TA-3334

Wall Dimming Multichannel



GeoDim Wall 4 Channel Wall Dimmer



Universal wall-dimming system with 4 channel, each 2500W (for all loads). EU made. Memories for lighting scenes. Inputs: Analog, EIB, DMX-512.
TA-3430

4 channel dimmer for wall mounting. 2500 W each (for all loads).
With memories for light scenes. Inputs: Analogue, EIB, DMX512.
Only 1 unit in stock - reproduction only from 40 units order quantity.

EU production, 10 years free support.

8 internal memories for light scenes, retrievable via the operating menu or via 8 external switching contacts.
Adjustable fade time from 0 ... 9 seconds.
Also suitable for electronic transformers, magnetic transformers and 230V ECGs.

Inputs:
Analogue 0-10V, 1-10V (EIB actuators), DMX512.
DMX start address adjustable from 1 - 512.

Each channel can be set as a dimmer or switch.
Each output is protected by a circuit breaker.

Connection 1 x 230V 40A.
Housing for wall mounting
Protection class: IP30
Dimensions: W 180 x H 480 x D 105 mm

Only 1 left in stock - Reproduction only from 40 pieces order quantity.
Weight: 6,5 kg

Several Lighting Controllers



SEK-02-10 Electronic Impulse Switch



24V controllable relay for controlling dimmers or switching luminaires. With central on-off function and 2 contacts.
TA-3669

Operation can be controlled via one button or up to 3 button functions.

Output: Two switching contacts for 2300 VA power each.

Max. 10A / 250V AC

Operating voltage 230V

The control buttons to be connected operate with 24V DC.

Key 1: ON

Key 2: OFF

Key 3: ON - OFF alternately by pulse

Therefore also suitable for automatic light control in cinemas, shop windows, animal stables, underground garages, etc.

Mounting by snapping onto top-hat rail.

W 105mm, H 80mm, D 60mm

Weight: 0,6 kg

Recessed Wall Dimmer Switches and Control Panels



Wall mount light operating Panel DPL-H-ETE Varintens

1 push-button on-off with control LED. For installation in flush-mounted switch box

TA-3680-1

Colour Light Controllers



4 Channel Colour Mixing Controller RGB 1-10V

Colour light control with 4 channels for switching and dimming of fluorescent ballasts or LED drivers.

TA-3725

Many dynamic lighting scenes can be called up and programmed.

The 4-channel control unit enables the individual creation of colour change programmes for RGB applications. Four programmable programme slots are available for this purpose.

In eight scenes per programme, colours, colour life and the type of colour transitions (soft/hard) can be set. Four colour programmes are already integrated.

The fourth channel can be used, for example, to add white light to influence colour saturation.

The unit also has an external switching input with which a panic circuit can be realised.

A special feature is the optionally available remote control, which ensures convenient operation of your RGB application.

The unit is suitable for both recessed and surface mounting.

4 output channels 1-10V

Operating voltage 230V

Operation via the operating keys or via an IR remote control to be ordered

Illuminated LCD display

Weight: 0,45 kg



IR Remote Control for 4 Channel Colour Controller

TA-3726

Light Effects



Mirror Ball Motor 30cm

For hanging mirror balls up to max. 30cm Ø. 230V



Speed: 1,5 UPM

Load capacity: max. 2kg





Voltage: 230 Volt




with mains plug.

TA-5050


	Water-Reflections Projector	<p>Creates the effect of water reflections for party cellars, bars or theatres. Halogen 150 W TA-5165</p> <p>With automatic colour change red, green, yellow, blue. Suitable for halogen lamp EFR 150W 15V - please order separately. Connection voltage 230V. Weight: 6,8 kg</p>
	Strobe-Controller 1-Channel	<p>Control unit for up to 8 stroboscopes. Output pulse 10V. Adjustment of flash speed and brightness. (The dim function only works with dimmable flash units). In robust metal housing. Voltage: 230V Control voltage: 10V TA-6421</p>

Lighting Chains

	Light Mesh with 100 lamps	<p>Safe light net with transformer for indoor and outdoor use, clear lights. Christmas decoration. Low stock TA-8120</p> <p>Line colour green. Dimension approx. 100 x 100cm Power 20VA Suitable for indoor and outdoor use. Protection class IP44 Weight: 0,9 kg</p>
	Light Mesh with 176 lamps	<p>Light net for indoor and outdoor use, lights clear.christmas decoration. Stock: 2 pieces Line colour green. Power 92W Connected voltage 230V Lamps not replaceable. Suitable for indoor and outdoor use Dimensions approx. 120cm x 200cm TA-8125</p>
	LED Light Mesh Outdoor 120 micro bulbs	<p>With 120 LEDs in pleasant warm white colour. Low power consumption, long-lasting. Christmas decoration. Stock: 1 piece Supply cable 1.5m Connection voltage 230V Power consumption only 9,7 Watt Extremely long lamp life LED not replaceable Can be used indoors and outdoors Protection class IP44 TA-8130</p>
	LED Curtain of Lights 3.5m for Outdoorsr	<p>24 light strands. 456 LEDs. Energy-saving, long-lasting, safe.Christmas decoration. Stock: 2 pieces TA-8140</p> <p>24 light strands made of robust rubber cable with 19 LEDs each. Supply cable 1.5m Connection voltage 230V Power consumption only 62 Watt Extremely long lamp life LED not replaceable. Can be used indoors and outdoors Total length: approx. 350cm Strand length: approx. 150cm Weight: 2 kg</p>

	LED Light Chain Outdoor 40 LEDs with Transformer	<p>Outdoor lamp chain, low power consumption, very long life, safe indoor and outdoor operation. Christmas decoration with white lambs. Stock: 1 piece TA-8429-04</p> <p>Particularly safe due to the transformer - the fairy lights only have a non-hazardous voltage of 24 volts. With white LED lights. For indoor or outdoor use. With transformer 24V Connected voltage 230V / 1,9 Watt Supply line 10m Length 4m LEDs are not replaceable. Weight: 0,5 kg</p>
	LED Light Chain Outdoor 40 coloured LEDs with Transformer	<p>Outdoor lamp chain, low power consumption, very long life, safe indoor and outdoor operation. Christmas decoration with colourful bulbs. Stock: 1 piece TA-8429-04B</p> <p>Particularly safe due to the transformer - the light chain has only 24 volts non-hazardous voltage. With coloured LED lights. For indoor or outdoor use. With transformer 24V Connected voltage 230V / 1,9 Watt Supply line 10m Length 4m LEDs are not replaceable. Weight: 0,5 kg</p>
	LED Light Chain Outdoor 100 LEDs with Transformer	<p>Outdoor lamp chain, low energy consumption, 100,000 hrs lifetime, safe indoor and outdoor use. Christmas decoration. Stock: 1 piece TA-8429-10</p> <p>Splash-proof light chain for indoor and outdoor use. Particularly safe due to the transformer - the light chain has only 24 volts non-hazardous voltage. With 100 colourful LED lamps on 10m chain length. LEDs are not replaceable. Incl. 24V transformer and mains plug, cable in black. Connected voltage 230V / 4,8 Watt Protection class II, IP44 Supply cable 10m Weight: 0,9 kg</p>

Fibre Optics Lighting

	Light Generator for Fiber Optics 100W Halogen	<p>With powerful 100W halogen lamp (2000h lifetime). For operating glitter fibres (e.g. starry sky) or side light (e.g. pool lighting or façade lighting.) Stock: 1 piece TA-8873W</p> <p>Built-in quiet fan for continuous operation. The generator may only be operated in horizontal position. The scope of delivery includes a connection adapter optionally: for 19 fibre bundles 8mm Ø or for 4 fibre bundles 16mm or for 1 fibre 13 - 18mm or 1 fibre bundle 30mm. Connection: 230V ac / 125W Dimension 400x 185x 148mm Weight: 5,5 kg</p>
---	--	--

Standard Colour Gels



Color Filter Gel 120 x 50cm green

Colour filter heat-resistant, for headlights and lamps.
Material: Polyester
Maximum operating temperature: 180 degrees Celsius.
High light transmission.
We recommend placing in a colour filter frame or attaching with 4 strips of Tesa film at the corners.
Air should be able to circulate around the colour film during operation to avoid overheating.
TA-F-124-12

HT gels extreme resistant



Color Filter Gel 117x 50cm HT green (124) heat resistant

Colour filter film for headlights and lamps. Comparable with: 089 Fern green, normal 139
Material: polycarbonate
Maximum operating temperature: 220 degrees Celsius.
High light transmission.
We recommend inserting in a colour filter frame or fixing with 4 strips of Tesa film at the corners.
Air should be able to circulate around the colour film during operation to avoid overheating.
TA-F-124H-12



Color Filter Gel 117 x 50cm HT purple heat resistant

Colour filter sheet for headlights and lamps. Lavender extremely heat resistant
Material: polycarbonate
Maximum operating temperature: 220 degrees Celsius.
High light transmission.
We recommend inserting in a colour filter frame or fixing with 4 strips of Tesa film at the corners.
Air should be able to circulate around the colour film during operation to avoid overheating.
TA-F-126H-12

Standard Colour Gels

Color Filter Gel 60 x 50cm rose

Colour filter heat-resistant, for headlights and lamps. For cutting to size.
TA-F-128-6

HT gels extreme resistant



Color Filter Gel 117 x 50cm HT 132 blue, heat resistant

Colour filter film for headlights and lamps. Colour shade similar to LEE 068 (light), (075), (141), (80) extremely heat resistant
Material: polycarbonate
Maximum operating temperature: 220 degrees Celsius.
High light transmission.
We recommend inserting in a colour filter frame or fixing with 4 strips of Tesa film at the corners.
Air should be able to circulate around the colour film during operation to avoid overheating.
TA-F-132H-12



Color Filter Gel 117 x 50cm HT turquoise heat resistant

Colour filter sheet for headlights and lamps. (HT 115) extremely heat resistant
Material: polycarbonate
Maximum operating temperature: 220 degrees Celsius.
High light transmission.
We recommend inserting in a colour filter frame or fixing with 4 strips of Tesa film at the corners.
Air should be able to circulate around the colour film during operation to avoid overheating.
TA-F-137H-12

Standard Colour Gels

	Color Filter Roll 120x 700cm white diffusion (216)	<p>Colour film heat resistant. For equalized light distribution and less shadows. Material: Polyester Maximum operating temperature: 180 degrees Celsius. (cf. White Frost.) High light transmission.</p> <p>We recommend placing in a colour filter frame or fixing with 4 strips of Tesa film at the corners. Air should be able to circulate around the colour film during operation to avoid overheating. Dimensions: 122 x 762 cm TA-F-159-R</p>
	Color Filter Gel 120cm conversion daylight (203)	<p>Colour filter 50cm x 120cm, for spotlights and photography. 1/4 CT blue, raises the light temperature. Correction from 3200K to 3600K, (halogen light in daylight). Material: Polyester Maximum operating temperature: 180 degrees Celsius. High light transmission. We recommend placing in a colour filter frame or attaching with 4 strips of Tesa film at the corners. Air should be able to circulate around the colour film during operation to avoid overheating. TA-F-160-12</p>
	Color Filter Roll 120 x 700cm Magenta Red	<p>Roll of filter foil, heat-resistant. Material: Polyester Maximum operating temperature: 180 degrees Celsius. TA-F-S-R</p>
Colour foil set 10 x 10cm, 4 colours		<p>4 colour foils in different colours, heat-resistant. Suitable for spotlights and small halogen PAR spots. TA-F-SET10</p>
Colour Filter Gel Set for Spot 20x 20cm, 4 pcs.		<p>Heat resistant. With 4 colours in the size of 200 by 200mm TA-F-SET20</p>

Colour filter glass

	Color filter glass round 117mm blue heat resistant for spotlight	<p>Glass colour filter blue 117 mm Ø, heat-resistant for luminaires and spotlights. TA-FG-100</p> <p>Thickness 2,75mm Weight: 0,1 kg</p>
	Color filter glass 160 x 140mm for floodlight	<p>Coloured glass heat-resistant 160 x 140 mm for coloured light. Choice of red, yellow, green or blue. TA-FG-160</p>
	Colour glass colour filter 175 x 135mm for LAF 500	<p>Headlight colour glass 175 x 135 mm in red or blue TA-FG-175B</p>
	Colour glass colour filter 245 x 165mm for HAF 500 floodlight	<p>Heat-resistant coloured glass 245 x 165mm for headlights. Optionally yellow or green. TA-FG-245</p>
	Colour Filter Glass for PAR56	<p>Glass Dicro filter 220 x 220mm for intense colours, long durability. Red, yellow, blue. TA-FG-PAR56 Weight: kg</p>



Colour glass dichro filter PAR64 heat-resistant 250mm

Glass Dichro filters for intense colours, long shelf life. Red, green, blue.
250mm x 250mm,
heat resistant.
TA-FG-PAR64

Standard Colour Gels



Colour Filter Foil f. Fluorescent Tube 120cm



Coloured tube for fluorescent tube T8 with 1200mm length.
Only small remaining stocks: Available in green and blue.
TA-FR-120R

Coloured foil to cover white fluorescent tubes with 26mm Ø.
Only small remaining stocks: Available in green and blue.
Weight: kg



Coloured cover for fluorescent tubes 120 /150cm T8



Colour filter tube to cover for fluorescent tube T8 1200mm or 1500 mm.
Low remaining stock
TA-FR-150R

Coloured plastic tube to slide over white fluorescent tubes with 26mm Ø.
Available in red, green, blue or orange.
Weight: kg

Complete Stage Lighting Packages



Stage Lighting Package Kit 2



Simple complete package for lighting the stage in school auditoriums,
gymnasiums.
TA-SETI2

High-quality system with 10 lights, control and all necessary accessories.
The installation must be performed by a specialist.

Included:

- 2 load bar for hanging the lights 300cm.
 - 4 folding hook with eyelet + 4 steel cables for hanging up to 500cm.
 - 8 lens spotlights 1000W + halogen lamps
 - 8 color filter + color filter frame
 - 8 folding hook + 4mm safety rope
 - 2 Wall Brackets Folding
 - 2 profile spots 1000W + halogen lamps + safety rope
 - 1 lighting console Aurora 12 + PSU
 - 2 Wall Dimmers, each of 4 x 2300W
 - 1 DMX control cable 10m assembled
 - 1 DMX control cable 40 m
 - 2 wall plug points for selectively connecting the control console.
- Weight: kg



Stage Lighting Package Kit 3



Inexpensive complete package for stage lighting in schools with theatre clubs, multi-purpose halls.
TA-SETI3

High-quality system with 14 lights, control and all necessary accessories.
The installation must be performed by a specialist.

Included:

- 2 load bar for hanging the lights 300cm.
- 4 hinged hook with eyelet + 8 steel cables for hanging up to 500cm.
- 6 lens spotlights 1000W + halogen lamps
- 6 color filter + color filter frame
- 16 Clamps + 4mm safety rope
- 6 Stage Floodlights + 500W halogen lamp
- 6 barndoors
- 2 single stands 240 cm + TV Spigot
- 2 profile spots 1000W with halogen lamps
- 1 lighting console Piccolo LT 24
- 1 Wall Dimmer 12x 2500W
- 2 Schoko extension cable 25m
- 1 DMX control cable 10m assembled
- 1 DMX control cable 75 meters
- 2 wall plug points for selectively connecting the control console.
- 1 DMX jumper cable.

Weight: kg



LED Party + Show Lighting Kit



Entry-level set for bands, sales presentations, solo entertainers.
TA-SETM09

Versatile system with 4 LED spotlights, control unit and all necessary accessories.
Everything is ready to plug in for quick set-up and dismantling for events.

Included in delivery:

- 4 LED spotlights with RGB colour change
- 2 light show stands 3.2 m + crossbars
- 1 light control panel DMX with plug-in power supply unit
- 2 Schuko extension 10m
- 2 DMX control cable 10m
- 2 DMX control cable 1m
- 2 Multiple socket
- 4 Safety cable 3mm

Description Spotlight:

Bright stage spotlight.
7 RGB power LEDs with pre-mounted lenses.
Pure colours and colour transitions are produced as the colour mixing takes place behind the lenses.
Stepless RGB colour mixing with 16.7 million colour tones.
Controllable via DMX512.
Automatic mode with internal programmes and soft colour transitions.
Built-in microphone for sound control.
The LEDs have the brightness of approx. 200W halogen light.
Beam angle: 30
Protection class: IP20
Connection voltage: 110V - 240V
Power consumption: 25 W
Housing aluminium profile.
Dimensions: H 270mm, W 260mm, D 110mm

Description control unit:

16 storable light scenes
Arbitrarily assignable RGB and dimmer channels
Individual RGB and master dim control
Adjustable fade times
LED display
Incl. 12V plug-in power supply unit
Housing for standing or installation.
Dimensions: 370 x 160 x 60 mm (LxWxH)
Weight: 43 kg



Mobile Stage Lighting Package 2



The standard lighting set for normal requirements. Also for amateur play groups.

TA-SETM2

High-quality system with 6 spotlights, steering and all necessary accessories. Everything is ready to plug in for rapid assembly and dismantling of events.

Included:

- 4 Lens projectors 1000W
- 4 halogen lamps 1000W
- 4 color frame
- 2 Colour Filter Set for projectors 20x20cm / 4 filters per set
- 2 HAF 500 watt halogen floodlight symmetrical
- 2 color glasses for HAF 500 in red, yellow, green or blue
- 2 500 watt halogen lamp R7s tubular
- 1 lighting console PSL Set 12
- 1 Dimmer Pack 6 x 2500W Liberty
- 2 Tripod stand 300cm
- 2 T-Bar 6-channel Harting / Schuko
- 6 Schuko connectors female/ rubber
- 6 Security cable 4 mm
- 1 DMX control cable 20 m

Weight: kg



Mobile Stage Lighting Package 3



The professional lighting set for mobile theatres or theatre schools.

TA-SETM3

High-quality system with 12 spotlights, steering and all necessary accessories. Everything is ready to plug in for rapid assembly and dismantling of events.

Included:

- 6 pcs. 1000W Fresnel lens spotlights
- 6 halogen lamps 1000W
- 6 Colour filter frame
- 6 barndoors
- 6 Color Filter Sets
- 4 floodlights 500W
- 4 color filter glasses
- 2 Eco 500W profile spot
- 2 halogen lamps 500W
- 2 crank stands 380cm / 50 kg
- 2 cross-bars with built-Harting / Schuko divisions.
- 2 single stands 240 cm
- 1 lighting console GeoDim Control 24
- 2 dimmer packs LT 2500 W Liberty 6x
- 2 multi-core cable 10 m
- 2 Schuko extension cables 25 m
- 10 safety rope 3 mm
- 1 DMX control cable 20 m
- 1 DMX control cable 10 m

Flight case for the dimmers, the control console and accessories.

Weight: kg



Mobile Stage Lighting Package PAR 2



The standard lighting set for normal requirements. Also for amateur play groups.

TA-SETP2

High-quality system with 6 spotlights, steering and all necessary accessories. Everything is ready to plug in for rapid assembly and dismantling of events.

Included:

- 4 PAR 64 Spot 1000W
- 4 halogen lamps 1000W
- 4 color frame
- 2 Colour Filter Set for projectors 20x20cm / 4 filters per set
- 2 HAF 500 watt halogen floodlight symmetrical
- 2 color glasses for HAF 500 in red, yellow, green or blue
- 2 500 watt halogen lamp R7s tubular
- 1 lighting console PSL Set 12
- 1 Dimmer Pack 6 x 2500W Liberty
- 2 Tripod stand 300cm
- 2 T-Bar 6-channel Harting / Schuko
- 6 Schuko connectors female/ rubber
- 6 Security cable 4 mm
- 1 DMX control cable 20 m

Weight: 52 kg



Stage Lighting Package 8 Floodlights + Spotlight



Simple complete package for lighting the stage in school auditoriums, gymnasiums.

TA-SETS2

High-quality system with 9 lights, control and all necessary accessories. The installation must be performed by a specialist.

Included:

- 2 load bar for hanging the lights 300cm.
- 4 folding hook with eyelet + 4 steel cables for hanging up to 500cm.
- 8 lens spotlights 1000W + halogen lamps
- 8 color filter + color filter frame
- 8 folding hook + 4mm safety rope
- 2 Wall Brackets Folding
- 2 profile spots 1000W + halogen lamps + safety rope
- 1 lighting console Aurora 12 + PSU
- 2 Wall Dimmers, each of 4 x 2300W
- 1 DMX control cable 10m assembled
- 1 DMX control cable 40 m
- 2 wall plug points for selectively connecting the control console.

Weight: kg